

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB900P, WB1500, WB500.1, Fabric Ink L3

Data Sheet No: DS500

Version No: 002

Issue Date: 10th January 2020

Page 1

1.0 – Identification of the substance/mixture and of the company/undertaking

1.1 – Product Identification

Trade name: Whiteboard Ink WB900P, WB1500, WB500.1, Fabric Ink L3
Substance name: n/a
Index No: n/a
CAS-No: n/a
EC-No: n/a

1.2 – Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture: Preparation for use in writing instruments
Recommended restrictions on use: No information available

1.3 – Details of the supplier of the safety data sheet

Company: Multichem Limited, Tyne Mills Industrial Estate, Hexham, Northumberland NE46 1XL, UK
Telephone: +44 1434 606 085
Fax: +44 1434 601 804
e-mail: mail@multichem.net

1.4 – Emergency telephone number

+44 7887 612 787

2.0 - Hazards Identification

2.1 – Classification of the substance or mixture

Regulation (EC) No. 1272/2008			
Hazard class	Hazard category	Target organs	Hazard statements
Flammable liquids	2	n/a	H225
Serious eye damage/eye irritation	2	eyes	H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

Most important adverse effects: Highly flammable liquid and vapour. Causes serious eye irritation.

2.2 – Label Elements

Labelling according to Regulation (EC) No. 1272/2008

Hazard Symbols:



Signal word:

DANGER

Hazard statements:

H225 Highly flammable liquid and vapour
H319 Causes serious eye irritation

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment
P243 Take precautionary measures against static discharge

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB900P, WB1500, WB500.1, Fabric Ink L3

Data Sheet No: DS500

Version No: 002

Issue Date: 10th January 2020

Page 2

P280 Wear protective gloves/protective clothing/eye protection
P305/P351/P338 IF IN EYES: rinse cautiously with water for several minutes
Remove contact lenses, if present and easy to do. Continue rinsing
P337/P313 If eye irritation persists: get medical advice/attention
P403/P235 Store in a well-ventilated place. Keep cool.

2.3 – Other hazards

No other information available.

3.0 - Composition / information on ingredients
3.1 – Substances

Chemical nature: mixture

Chemical name	REACH Reg. No.	CAS No.	EC No.	Amount (%)
Ethanol	01-2119457610-43	64-17-5	200-578-6	<75%
Propan-2-ol	01-2119457558-25	67-63-0	200-661-7	10%

Chemical name	Classification according to Regulation (EC) No. 1272/2008
Ethanol	H225 (2), H319 (2)
Propan-2-ol	H225 (2), H319 (2), H336 (3)

For the full text of the H-Statements mentioned in this Section, see Section 16.

4.0 - Description of first aid measures
4.1 – Description of first aid measures

General advice: Take off all contaminated clothing immediately
In case of inhalation: Remove to fresh air. If symptoms persist, seek medical advice. If unconscious place in recovery position
In case of skin contact: Wash off with plenty of water. If skin irritation persists, seek medical advice
In case of eye contact: Rinse thoroughly with plenty of water, also under the eyelids. Consult an eye specialist immediately

4.2 – Most important symptoms and effects, both acute and delayed

No information available

4.3 - Indication of immediate medical attention and special treatment needed

Treat symptomatically. No further information available

5.0 – Firefighting measures
5.1 – Extinguishing media

Suitable extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide
Unsuitable extinguishing media: High volume water jet

5.2 – Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: Highly flammable. Vapours may form explosive mixtures with air. In case of fire hazardous decomposition products may be produced, such as carbon monoxide (CO) and carbon dioxide (CO₂).

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB900P, WB1500, WB500.1, Fabric Ink L3

Data Sheet No: DS500

Version No: 002

Issue Date: 10th January 2020

Page 3

5.3 - Advice for firefighter

Special protective equipment for firefighters:	In the event of fire, wear self-contained breathing apparatus. Wear appropriate body protection (full protective suit)
Further information:	Cool closed containers exposed to fire with water spray. Heating will cause a pressure rise – with risk of bursting. Collect contaminated fire extinguishing water separately. This must not be discharged into drains

6.0 – Accidental release measures**6.1 – Personal precautions, protective equipment and emergency procedures**

Personal precautions:	Use personal protective equipment. Provide adequate ventilation. Keep away from heat and sources of ignition. Avoid contact with skin and eyes. Do not breathe vapours.
-----------------------	---

6.2 – Environmental precautions

Environmental precautions:	Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration
----------------------------	---

6.3 – Methods and materials for containment and cleaning up

Procedure:	Contain spillage, and then collect with non-combustible absorbent material (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see Section 13)
Further information:	Treat recovered material as described in Section 13

6.4 – Reference to other sections

For personal protection see Section 8

7.0 – Handling and storage**7.1 – Precautions for safe handling**

Advice on safe handling:	Keep container tightly closed. Ensure adequate ventilation. Avoid contact with skin and eyes. Do not breathe vapours. Emergency eye wash fountains and emergency showers should be available in the immediate vicinity
Hygiene measures:	Keep away from food, drink and animal feeding stuffs. Smoking, eating and drinking should be prohibited in the application area. Wash hands before breaks and at the end of the working day. Take off all contaminated clothing immediately. Avoid contact with skin and eyes. Do not breathe vapours of spray mist

7.2 – Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers:	Keep in an area equipped with solvent resistant flooring. Store in original container
Advice on protection against fire and explosion:	Combustible liquid. Keep away from sources of ignition – no smoking. Take measures to prevent the build-up of electrostatic charge. Vapours may form explosive mixtures

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB900P, WB1500, WB500.1, Fabric Ink L3

Data Sheet No: DS500

Version No: 002

Issue Date: 10th January 2020

Page 4

Further information on storage conditions: in air. Use only in an area containing explosion proof equipment
Keep tightly closed in a dry and cool place. Keep in a well-ventilated place. Keep away from heat. Keep away from direct sunlight

Advice on common storage: Incompatible with oxidizing agents. Keep away from food, drink and animal feeding stuffs

7.3 – Specific end uses

Specific uses(s): No information available

8.0 – Exposure controls/personal protection
8.1 – Control parameters
Ethanol (CAS No. 64-17-5)

Regulatory basis: UK. EH40 Workplace Exposure Limits (WELs)
Regulatory list: EH40 WEL
Value type: Time Weighted Average (TWA)
Value: 1000 ppm
Value : 1920 mg/m³

Propan-2-ol (CAS No. 67-63-0)

Regulatory basis: UK. EH40 Workplace Exposure Limits (WELs)
Regulatory list: EH40 WEL
Value type: Time Weighted Average (TWA)
Value: 400 ppm
Value : 999 mg/m³
Regulatory basis: UK. EH40 Workplace Exposure Limits (WELs)
Regulatory list: EH40 WEL
Value type: Short Term Exposure Limit (STEL)
Value: 500 ppm
Value : 1250 mg/m³

8.2 – Exposure controls

Engineering measures: Refer to protective measures listed in Sections 7 and 8

Respiratory protection : Required, if exposure limit is exceeded (e.g. OEL). Respirator with a gas filter. Recommended filter type: A

Hand protection: Wear suitable gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Protective gloves should be replaced at first signs of wear
Butyl rubber, 0.5 mm, Fluorocarbon rubber, 0.4 mm

Eye protection: Tight fitting safety goggles

Skin and body protection: Wear suitable protective clothing

Environmental protection: Do not let product enter drains. If the product contaminates rivers and lakes or drains inform respective authorities

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB900P, WB1500, WB500.1, Fabric Ink L3

Data Sheet No: DS500

Version No: 002

Issue Date: 10th January 2020

Page 5

9.0 – Physical and chemical properties**9.1 – Information on basic physical and chemical properties**

Appearance:	Various colours, liquid
Odour:	Alcohol-like
Odour threshold:	No data available
pH:	No data available
Melting point / freezing point:	-114.5°C
Initial boiling point/boiling range:	78.3°C
Flash point:	12°C
Evaporation rate:	No data available
Flammability:	No data available
Upper/lower flammability or explosive limits:	15% (V), 3.5% (V)
Vapour pressure:	No data available
Vapour density:	No data available
Relative density:	No data available
Solubility:	Miscible in water, readily miscible with solvents
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	425°C
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidising properties:	No data available

9.2 – Other information

No further information available

10.0 – Stability and reactivity**10.1 – Reactivity**

Advice: Stable under recommended storage conditions

10.2 – Chemical Stability

Advice: Stable under normal conditions

10.3 – Possibility of hazardous reactions

Hazardous reactions: No information available

10.4 – Conditions to avoid

Conditions to avoid: Heat, flames and sparks

10.5 – Incompatible materials

Materials to avoid: Alkali metals, alkaline earth metals, strong oxidizing agents, nitric acid, sulphuric acid, peroxides (e.g. hydrogen peroxide)

10.6 – Hazardous decomposition productsHazardous decomposition: Under fire conditions: carbon monoxide (CO), carbon dioxide (CO₂)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB900P, WB1500, WB500.1, Fabric Ink L3

Data Sheet No: DS500

Version No: 002

Issue Date: 10th January 2020

Page 6

11.0 – Toxicological information**11.1 – Information on toxicological effects****Ethanol (CAS No. 64-17-5)**

Oral

Value type: LD50
Value: >2000 mg/Kg
Species: rat

Inhalation

Value type: LC50
Value: >20 mg/L
Exposure time: 4 h
Species: mouse

Dermal

Value type: LD50
Value: >2000 mg/Kg
Species: rabbit

Propan-2-ol (CAS No. 67-63-0)

Oral

Value type: LD50
Value: 5840 mg/Kg
Species: rat

Inhalation

Value type: LC50
Value: >25 mg/L
Exposure time: 6 h
Species: rat

Dermal

Value type: LD50
Value: >13900 mg/Kg
Species: rabbit

12.0 – Ecological information**12.1 – Toxicity****Ethanol (CAS No 64-17-5)**

Fish

Species: Pimephales Promelas (Fathead Minnow)
Value type: LC50

Value:

Exposure time: 96 h

Daphnia and other aquatic invertebrates

Species: daphnia magna
Value type: EC50

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB900P, WB1500, WB500.1, Fabric Ink L3

Data Sheet No: DS500

Version No: 002

Issue Date: 10th January 2020

Page 7

Value:

Exposure time: 48 h

Algae

Species: Chlorella vulgaris (Fresh water algae)

Value type: EC50

Value: 275

Exposure time: 72 h

Bacteria

Species: Paramaecium caudatum

Value type: EC50

Value: 5800

Exposure time: 4 h

Propan-2-ol (CAS No 67-63-0)

Fish

Species: Pimephales promelas (fathead minnow)

Value type: LC50

Value:

Exposure time: 96 h

Daphnia and other aquatic invertebrates

Species: daphnia magna

Value type: EC50

Value:

Exposure time: 24 h

Algae

Species: Scenedesmus subspicatus

Value type: EC50

Value: >100

Exposure time: 72 h

Bacteria

Value type: EC50

Value: >100 mg/L, no harming action

12.2 – Persistence and biodegradability

No data available

12.3 – Bioaccumulative potential

No data available

12.4 – Mobility in soil

Mobile in water environment

12.5 – Results of PBT and vPvB assessment

No data available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB900P, WB1500, WB500.1, Fabric Ink L3

Data Sheet No: DS500

Version No: 002

Issue Date: 10th January 2020

Page 8

12.6 – Other adverse effects

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

13.0 – Disposal considerations
13.1 – Waste treatment methods

Product:	Disposal together with normal waste is not allowed. Special disposal required according to local regulations. Do not empty into drains. Contact waste disposal services
Contaminated packaging:	Empty contaminated packaging thoroughly. They can be recycled after thorough and proper cleaning. Packaging that cannot be cleaned is to be disposed of in the same manner as the product. Do not burn, or use a cutting torch on the empty drum. Risk of explosion

14.0 – Transport Information
14.1 – UN Number

1993

14.2 – UN proper shipping name

ADR:	Flammable Liquid n.o.s (contains ethanol)
RID:	Flammable Liquid n.o.s (contains ethanol)
IMDG:	Flammable Liquid n.o.s (contains ethanol)
IATA-DGR :	Flammable Liquid n.o.s (contains ethanol)

14.3 – Transport hazardous class(es)

Labels/classification code/ hazard identification number /tunnel restriction code

ADR:	3; F1 ; 33 : (D/E)
RID:	3 ; F1 ; 33
IMDG :	3 ; (F-E, S-E)
IATA-DGR :	3

14.4 – Packing group

ADR:	II
RID:	II
IMDG:	II

14.5 – Environmental hazards

Labelling according to 5.2.1.8 ADR:	No
Labelling according to 5.2.1.8 RID:	No
Labelling according to 5.2.1.6.3 IMDG:	No
Labelling according to IATA-DGR :	No
Classification as environmentally hazardous according to 2.9.3 IMDG:	No
Classified as 'P' according to 2.10 IMDG:	No

14.6 – Special precautions for user

Not applicable

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB900P, WB1500, WB500.1, Fabric Ink L3

Data Sheet No: DS500

Version No: 002

Issue Date: 10th January 2020

Page 9

14.7 – Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IMDG: Not applicable

15.0 – Regulatory Information**15.1 – Safety, health and environmental regulations/legislation specific for the substance or mixture**

All components are REACH registered or are exempt from REACH registration

Our inks do not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57)

All components are listed on TSCA list of active substances

15.2 – Chemical safety assessment

No information available

16.0 – Other Information**16.1 – Full text of H-Statements referred to under Sections 2 and 3**

H225: Highly flammable liquid and vapour

H319: Causes serious eye irritation

H336: May cause drowsiness or dizziness

16.2 – Further information

Other: The information provided in this safety data sheet is correct to our knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements and is not to be considered as a warranty or quality specification and does not constitute a legal relationship. The information contained in this safety data sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text

HS Tariff code: 32159070