



Justrite Safety Group

# 656SFR Cushion Ease Solid™ Nitrile FR

Heavy duty modular rubber tiles



# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting 656SFR Cushion Ease Solid™ Nitrile FR

Ergonomic benefit derived from a 19 mm thick worker platform with a closed anti-slip pebble structure surface for maximum anti-fatigue comfort in dry industrial environments.

- Heavy duty rubber tiles can be easily assembled for coverage of large areas or individual workstations, wall-to-wall or as islands
- Resistant to most industrial oils and suitable for welding areas
- Compatible with patented MD Ramp System™ for smart safety bevelling solutions; allows outside and inside corners.

#### Recommended use

- Wet/Dry and Oily Areas
- For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
- Heavy duty

#### Colors:

- Black

#### Sizes:

- 91cm x 91cm
- per m2

#### Accessories:

- 552 MD-X Ramp System™ Nitrile
- INS Installation Service Available on Request
- 651 M.D. Fire Retardent Ramp System
- 551 MD Ramp System™ Nitrile



# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting Cushion Ease Solid™ Nitrile FR

## General

Brand	Notrax
Category	Dry Areas Modular Matting
Product Number	656SFR
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Cushion Ease Solid™ Nitrile FR
Recommended use	For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
Series	Cushion-Ease®
Shipping Location	Chicago, IL 60638, United States, Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands
Type	Dry Areas - Heavy Duty Modular Rubber Mats
Update trigger	20210310-1301
Usage Intensity	Heavy duty

## Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	True
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
Warranty (years)	1

## Tests

Abrasion Resistance 1000	1.50% weight loss @ 5000 cycles
Compression Deflection 1.4	37.0 lb/in <sup>2</sup>
Compression Deflection 2.8	98.9 lb/in <sup>2</sup>
Elongation	451.8%
Fire rating EU	EN 13501-1 Bfl-S1
Fire rating US	Pass
Hardness	50 Shore A
Coefficient Friction Dry	0.88
Surface Flammability	Pass

## Technical Specifications

Application	Industrial Environments
Edges	Attachable bevelled edges are available
Material	100% nitrile fire retardant rubber compound
Material Group	Nitrile rubber
Process	Compression Moulding

## Niru® Cushion-Ease® Solid Black

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
656SFR00BL	per m2	13.6	19

## CUSHION-EASE® SOLID NITRILE FR BLACK

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
656SFR33BL	91cm x 91cm	12.7	19
656SFR00BL	per m2	13.6	19

### Accessories

552 MD-X Ramp  
System™ Nitrile

INS Installation Service  
Available on Request

651 M.D. Fire Retardent  
Ramp System

551 MD Ramp System™  
Nitrile