

040 Slabmat Carré™

Modular shock absorbing rubber mats



Ergonomic, Anti-fatigue & Safety Matting - Industrial Specialties

040 Slabmat Carré™

High quality 100% natural rubber mat that absorbs shock of fallen materials and protects floors and equipment. The thick platform can withstand heavy weights while the nonslip textured top surface ensures sure footing and freedom of movement.

- Made of tough rubber compounds that make the mats virtually indestructible
- Interlocking mats allow on-site customization in units of 91 cm x 91 cm
- Bevelled solutions; allow out and inside corners

Recommended use

- Dry Areas
- Areas where heavy industrial equipment is stored. It is also suitable for gyms, weight rooms, skating rinks, golf courses, trailers and stables.
- Heavy duty

Colors:

- Black

Sizes:

- 91cm x 91cm

Accessories:

- 041 Slabmat Carré™ Safety Ramps



WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE



Ergonomic, Anti-fatigue & Safety Matting - Industrial Specialties

Slabmat Carré™

General

Brand	Notrax
Category	Industrial Specialties
Product Number	040
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Slabmat Carré™
Recommended use	Areas where heavy industrial equipment is stored. It is also suitable for gyms, weight rooms, skating rinks, golf courses, trailers and stables.
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Chicago, IL 60638, United States
Type	Industrial Specialties - Shock Absorbing Matting
Update trigger	20210310-1301
Usage Intensity	Heavy duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	True
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material, 100% recycled PVC top surface
Warranty	1

Tests

Abrasion Resistance 1000	5000 cycles 2.90 gr weight loss
Compression Deflection 1.4	@ 25% 33.3 lb/in ²
Compression Deflection 2.8	@ 50% 33.3 lb/in ²
Elongation	165.7%
Fire rating US	Pass
Hardness	67 Shore A
Coefficient Friction Dry	0.68
Surface Flammability	Pass
Tear Strength	55.4 lb

Technical Specifications

Application	Industrial Environments
Breaking Load	44 lb
Chemical Resistance	Cat. I Natural Rubber
Edges	Attachable bevelled edges are available
Material	Natural rubber
Material Group	Natural rubber
Process	Compression Moulding
Temperature Range	- 40 ° C up to + 120 ° C

Slabmat Carré™ Black

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)	Recommended accessories
040S0033BL	91cm x 91cm	16	13	041M0003YL 041F0003YL 041F0003BL 041M0003BL

Accessories

041 Slabmat Carré™
Safety Ramps