



Justrite Safety Group

572 De-Flex[®] Nitrile

Modular mat with dual locking connection



572 De-Flex® Nitrile

Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting

Extremely comfortable heavy duty anti-fatigue matting system with popular diamond plate traction surface that can be easily assembled for coverage of large areas or individual workstation mats.



- Modular rubber tiles are designed with a universal double-locking system on all sides to ensure an extra strong yet seamless connection for fast installation
- The 19 mm thick platform insulates the worker from the hard ground while the bulleted domes underneath allow the mat to bend and flex with every movement
- Unique extended ramp prevents tripping and allows cart access with smart bevelling solutions for inside and outside corners
- Resistant to most industrial oils

- Wet/Dry and Oily Areas
- For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
- Heavy duty

Recommended use

WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE

GOOD BETTER BEST



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting De-Flex® Nitrile

General

Brand	Notrax
Category	Dry Areas Modular Matting
Product Number	572
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	De-Flex® Nitrile
Recommended use	For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
Series	De-Flex®
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Chicago, IL 60638, United States
Type	Dry Areas - Heavy Duty Modular Rubber Mats
Update trigger	202319101214
Usage Intensity	Heavy duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	True
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Warranty (years)	1

Tests

Fire rating US	Pass
Hardness	69 Shore A
Slip Rating	R10
Surface Flammability	Pass

Technical Specifications

Application	Industrial Environments
Edges	Attachable bevelled edges are available
Material	100% Nitrile rubber
Material Group	Nitrile rubber
Process	Compression Moulding

De-Flex™ Nitrile Black

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
572B1818BL	45cm x 45cm	26.4	19
572S1818BL	45cm x 45cm	3.3	19

Accessories

571 De-Flex® Safety
Ramp Nitrile

INS Installation Service
Available on Request