

# Product Datasheet

## Removable insulated, or heated and insulated jackets for the Optiwash®

Retrofittable jackets designed for use with the Optiwash self-contained eye wash when located outdoors. The insulated jacket offers protection both from the the frost and solar radiation, while the heated jacket provides freeze protection down to -34C (-30F).

The Optiwash is ideal where a continuous supply of water is not available. The 38 litre, wall-mounted eye wash station delivers a controlled flow of a minimum 1.5 litres per minute of potable water for 15 minutes, meeting EN15154 and ANSI Z358.1-2014 requirements.

Also available with ATEX approved heating



II 2G IIA & IIB T3 X  
II 2D IIIC T135 X

Supplied with a wall mounted ATEX approved junction box for client's electrical connection.

Voltage 230V - 110V available upon request



## Specifications

INSULATED JACKET	
OUTER FABRIC	PE560, grey and green PVC coated polyester
INSULATION	12mm needle felt
INNER FABRIC	Silicone coated glass cloth
FASTENINGS	FR hook and loop with draw cord
DOCUMENT POUCH	Zippered A4
DIMENSIONS - PACKAGED (WxDxH)	762mm (30in) x 508mm (20in) x 102mm (4in)

  

HEATED AND INSULATED JACKET	
OUTER FABRIC	PE560, grey and green PVC coated polyester
INSULATION	12mm needle felt
INNER FABRIC	Silicone coated glass cloth
FASTENINGS	FR hook and loop with draw cord
DOCUMENT POUCH	Zippered A4
VOLTAGE	230V (110V available upon request)
POWER RATING	60W
HEAT SOURCE	Self-regulating trace tape heating
POWER CONNECTION	Cable entry size M20 x 1.5
DIMENSIONS - PACKAGED (WxDxH)	762mm (30in) x 508mm (20in) x 102mm (4in)