



# 569 Cushion Ease Solid™ Nitrile Marking Line

5S modular floor marking line

# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting 569 Cushion Ease Solid™ Nitrile Marking Line

Heavy duty rubber tiles that can be easily assembled for 5s in manufacturing areas. The ergonomic benefit is derived from a 19 mm thick worker platform with a closed anti-slip pebble structure surface for maximum anti-fatigue comfort in dry industrial environments.

- 5S marking line for marking borders, walkways, zones and safety barriers
- 5S Marking line compatible with the Cushion Ease and Safety Stance series
- Anti-slip pebble surface pattern is rated R9
- Resistant to most industrial oils

## Recommended use

- Dry Areas
- For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
- Heavy duty

## Colors:

- Yellow

## Sizes:

- 10cm x 91cm

## Accessories:

- 552 MD-X Ramp System™ Nitrile
- 656SG Cushion Ease Solid™ Nitrile 5S
- 656S Cushion Ease Solid™ Nitrile
- 551 MD Ramp System™ Nitrile
- 556 Cushion Ease Solid™



# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting Cushion Ease Solid™ Nitrile Marking Line

## General

Brand	Notrax
Category	Dry Areas Modular Matting
Product Number	569
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Cushion Ease Solid™ Nitrile Marking Line
Recommended use	For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
Series	Cushion-Ease®
Shipping Location	Barendrecht 2992SB, The Netherlands
Type	Dry Areas - Heavy Duty Modular Rubber Mats
Update trigger	20210310-1301
Usage Intensity	Heavy duty

## Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Warranty	1

## Tests

Abrasion Resistance 1000	1.50% weight loss (5000 cycles)
Compression Deflection 1.4	37.0 lb/in <sup>2</sup> (at 25%)
Compression Deflection 2.8	98.9 lb/in <sup>2</sup> (at 50%)
Fire rating US	Pass
Slip Rating	R9
Coefficient Friction Dry	0.88
Surface Flammability	Pass

## Technical Specifications

Application	Industrial Environments
Edges	Attachable bevelled edges are available
Material	100% Nitrile rubber
Material Group	Nitrile rubber
Process	Compression Moulding
Temperature Range	- 40 ° C up to + 120 ° C

# Cushion Ease Solid™ Nitrile Marking Line - Yellow

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
569S0003YL	10cm x 91cm	1.1	19

## Accessories

552 MD-X Ramp System™ Nitrile  
556 Cushion Ease Solid™

656SG Cushion Ease Solid™ Nitrile 5S

656S Cushion Ease Solid™ Nitrile

551 MD Ramp System™ Nitrile