



Justrite Safety Group

455 Skystep™

Ergonomic rubber mat with moulded edges



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Standalone Matting 455 Skystep™

Ergonomically and economically engineered, the Skystep™ utilizes the power of air. Skystep™ is designed to suction to the ground to prevent the mat from shifting while trapping air in its chambers. These air pockets combined with the resiliency of the rubber create an ultimate cushioning effect while keeping the mat lightweight.

- Loose lay with no installation required
- Integrated bevelled edges on all four sides to prevent tripping on the mat
- Slip resistance rating R9 according to DIN 51130 and BG-rule BGR181

Recommended use

- Dry Areas
- For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
- Medium duty

Colors:

- Black

Sizes:

- 60cm x 90cm
- 90cm x 120cm
- 90cm x 150cm



WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Standalone Matting Skystep™

General

Brand	Notrax
Category	Dry Areas Standalone Matting
Product Number	455
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Skystep™
Recommended use	For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Chicago, IL 60638, United States
Type	Dry Areas - Standalone Rubber Mats
Update trigger	20210310-1301
Usage Intensity	Medium duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	True
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
Warranty	1

Tests

Abrasion Resistance 1000	0.824
Elongation	210%
Fire rating US	Pass
Hardness	67 Shore A
Slip Rating	R9
Surface Flammability	Pass
Tear Strength	10.5 N/mm

Technical Specifications

Application	Industrial Environments
Breaking Load	4.80 Mpa
Edges	Moulded bevelled edges on all sides
Material	Natural rubber
Material Group	Natural rubber
Process	Compression Moulding
Temperature Range	- 40 ° C up to + 120 ° C

Skystep™ Black

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
455S0034BL	90cm x 120cm	11.8	13
455S0023BL	60cm x 90cm	5.5	13
455S0035BL	90cm x 150cm	16	13