

470 Marble Sof-Tyle[™]

Marble Sof Tyle[™] marbled rubber anti-fatigue mat.



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths 470 Marble Sof-Tyle™

Heavy duty anti-fatigue mat with a smooth rubber surface with marbled pattern laminated with UniFusion™ technology and RedStop™ slip-resistant backing. Combines style with exceptional comfort and durability. Ideal for commercial, laboratory, and tertiary environments.

- Resistant to most industrial fluids and chemicals.
- Featured with RedStop™ slip resistant backing to prevent mats from shifting.
- UniFusion™ technology, engineered to resist in the harshest work environments.

Recommended use

- Dry Areas
- For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
- Heavy duty

Colors:

- Grey

Sizes:

- 60cm x 91cm
- 91cm x 150cm
- 122cm x linm
- 60cm x linm
- 91cm x linm
- 122cm x 19.8m
- 60cm x 19.8m
- 91cm x 19.8m



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths Marble Sof-Tyle™

General

Brand	Notrax
Category	Dry Areas Linear Lengths
Product Number	470
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Marble Sof-Tyle™
Recommended use	For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Moselle, MS 39459, United States
Type	Dry Areas - Heavy Duty Industrial
Update trigger	20210310-1301
Usage Intensity	Heavy duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
Warranty	1

Tests

Abrasion Resistance 1000	0.85%
Abrasion Resistance 500	0.91%
Compression Deflection 1.4	0.60 cm
Compression Deflection 2.8	0.82 cm
Elongation	100%
Fire rating US	Pass
Foam Battery	40 lb/in ²
Hardness	80 Shore A
Coefficient Friction Dry	0.73
Surface Flammability	Pass
Tear Strength	23.3 lb

Technical Specifications

Application	Industrial Environments
Backing	Microcellular vinyl
Breaking Load	34 lb
Edges	Bevelled edges on all sides
Material	PVC
Material Group	PVC
Process	Lamination

Marble Sof-Tyle™ Grey

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
470R0036GY	91cm x 19.8m	121	12.7
470C0036GY	91cm x linm	5.3	12.7
470C0048GY	122cm x linm	7.1	12.7
470R0024GY	60cm x 19.8m	80	12.7
470S3660GY	91cm x 150cm	10	12.7
470S2436GY	60cm x 91cm	4	12.7
470C0024GY	60cm x linm	3.5	12.7
470R0048GY	122cm x 19.8m	162	12.7