

# 830 Switchboard Matting<sup>™</sup> Class 2

Class 2 insulation matting



# Ergonomic, Anti-fatigue & Safety Matting - Switchboard Matting

## 830 Switchboard Matting™ Class 2

Insulating matting prevents workers from being “grounded” and provides safety in case of electrical shock. The corrugated saw-tooth top surface increases traction and is easy to sweep clean.

- Each square inch of matting is tested in conformance with ANSI/ASTM D-178 specifications
- The corrugated saw-tooth top surface increases traction and is easy to sweep clean
- Recommended maximum usage: 17.000 Volts.
- Must be replaced every 12 months for optimum safety

### Recommended use

- Dry Areas
- Around electric sub-stations, transformers and switches, electrical panels, engine and generator rooms
- Heavy duty

### Colors:

- Black

### Sizes:

- 90cm x 150cm
- 91cm x linm
- 91cm x 22.8m



# Ergonomic, Anti-fatigue & Safety Matting - Switchboard Matting

## Switchboard Matting™ Class 2

### General

|                   |  |
|-------------------|--|
| Brand             | Notrax   |
| Category          | Switchboard Matting  |
| Product Number    | 830  |
| Product Family    | Industrial & Commercial Matting  |
| Product Group     | Ergonomic, Anti-fatigue & Safety Matting   |
| Product Name      | Switchboard Matting™ Class 2   |
| Recommended use   | Around electric sub-stations, transformers and switches, electrical panels, engine and generator rooms |
| Shipping Location | Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Moselle, MS 39459, United States       |
| Type              | Industrial Specialties - Electrical Protective Matting   |
| Update trigger    | 20210310-1301  |
| Usage Intensity   | Heavy duty   |

### Sustainability

|          |   |
|----------|---|
| REACH    | Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals). |
| Rohs US  | Rohs compliant (Restriction of Hazardous Substances).                                   |
| Warranty | 1   |

### Tests

|                      |            |
|----------------------|------------|
| Elongation           | 317%       |
| Hardness             | 91 Shore A |
| Surface Flammability | Pass       |
| Tear Strength        | 2505 PI    |

### Technical Specifications

|                     |                         |
|---------------------|-------------------------|
| Application         | Industrial Environments |
| Edges               | No borders              |
| Material            | PVC                     |
| Material Group      | PVC                     |
| Process             | Calendering             |
| Voltage Class       | 2                       |
| Voltage Maximum     | 20000                   |
| Voltage Recommended | 17000                   |

## Switchboard Matting™ Class 2 Black

| Art. nr.   | Dimension (cm) | Weight (kg) | Thickness (mm) |
|------------|----------------|-------------|----------------|
| 830S0035BL | 90cm x 150cm   | 11.6        | 6.4            |
| 830R0375BL | 91cm x 22.8m   | 174         | 6.4            |
| 830C0036BL | 91cm x linm    | 7.6         | 6.4            |