

661 Cushion Ease Solid™ ESD Nitrile FR

ESD Nitrile FR modular mat



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting 661 Cushion Ease Solid™ ESD Nitrile FR

Ergonomic benefit derived from a 19 mm thick worker platform with a closed anti-slip pebble structure surface for maximum anti-fatigue comfort in dry industrial environments.

- Heavy duty rubber tiles can be easily assembled for coverage of large areas or individual workstations, wallto-wall or as islands
- Compatible with patented MD Ramp System[™] for smart safety bevelling solutions; allow out and inside corners
- Resistant to most industrial oils and suitable for welding areas

Recommended use

- Dry Areas
- For placement in ESD assembly lines, picking, packing and logistics warehouses, individual work stations.
- Heavy duty

Colors:

Black

Sizes:

- 91cm x 91cm
- per m2

Accessories:

- 552 MD-X Ramp System™ Nitrile
- INS INSTALLATION
- 551 MD Ramp System™ Nitrile
- 057 ESD Mat Cleaner
- 056 ESD Wrist Band
- 052 ESD Common Grounding Cord
- 055 ESD Heel Grounder
- 051 ESD Floor Grounding Cord
- 054 ESD Earth Bonding Plug
- 053 ESD Coil Cord



SLIP RESISTANCE

























Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting Cushion Ease Solid™ ESD Nitrile FR

General

Brand	Notrax	
Category	Dry Areas Modular Matting	
Product Number	661	
Product Family	Industrial & Commercial Matting	
Product Group	Ergonomic, Anti-fatigue & Safety Matting	
Product Name	Cushion Ease Solid™ ESD Nitrile FR	
Recommended use	For placement in ESD assembly lines, picking, packing and logistics warehouses, individual work stations.	
Series	Cushion-Ease®	
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands	
Туре	Dry Areas - Heavy Duty Modular Rubber Mats	
Update trigger	20210310-1301	
Usage Intensity	Heavy duty	

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).	
Recycled	True	
Sustainability	Recyclable material	
Warranty	1	

Tests

Abrasion Resistance 1000	2.2% (5000 cycles)	
ESD Rg	Rp 10 ⁶ - 10 ⁹ Ω	
ESD Rp	Rp 10 ⁶ - 10 ⁹ Ω	
Fire rating EU	EN 13501-1 Bfl-S1	
Fire rating US	Pass	
Hardness	56 Shore A	
Slip Rating	R9	
Coefficient Friction Dry	0.81	
Surface Flammability	Pass	

Technical Specifications

Application	Industrial Environments	
Edges	Attachable bevelled edges are available	
Material	Static dissipative and fire retardant nitrile rubber compound	
Material Group	Nitrile rubber	
Process	Compression Moulding	

Cushion Ease Solid™ ESD Nitrile FR Black

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
661S0000BL	per m2	13.6	19
661S0033BL	91cm x 91cm	12.7	19

Accessories 552 MD-X Ramp System™ Nitrile 056 ESD Wrist Band

INS INSTALLATION

551 MD Ramp System™ 057 ESD Mat Cleaner

052 ESD Common

Nitrile

055 ESD Heel Grounder 051 ESD Floor Grounding

Cord

Grounding Cord 053 ESD Coil Cord 054 ESD Earth Bonding

Plug