

175 Déco Design™ Standard



- These decorative dust control mats come in a large assortment of fashionable, attractive, funky, retro and fun printed mats to coordinate to any interior design and atmosphere.
- This high quality multi-functional dust control mat cleans and dries shoes, to prevent dirt and moisture getting tracked into facilities.
- Superior colour-fastness is ensured, in accordance with DIN 54006. For more designs go to www.notrax.eu.
- Suitable for light traffic conditions.
- For placements inside entrance of offices, shops, restaurants, grocery shops, bakeries, specialty stores.
- Vacuum or use injection/extraction method to clean.

175 Déco Design™ Standard

| PRODUCT SPECIFICATIONS | | | |
|--|--|---|----------|
| Designation | Dust Control Matting | | |
| Description | Absorbent carpet mat with printed design | | |
| Material | | | |
| | Top | Tufted cut loop pile consisting of 100% non-crush polyamide 6.0 high twist yarn 405 grams of yarn per m ² | |
| | Backing | Black vinyl (DOP free) | |
| Process | Tufted | | |
| Category | Indoor absorbent | | |
| Recommended use | Indoor - light traffic conditions | | |
| Colours | Ardois, Ashanti, Autumn Leaves, Ghana, Diagonal, Giraffe, Johnstone, Half Moons, Orientrax Blue, Panther, Zebra, Twine, Steelplate, Raster, New Welcome, Chalk White, Modern 70's, Connect One | | |
| Weight | 2.7 kg/m ² | | |
| Thickness | 6 mm | | |
| Standard sizes | 60 cm x 90 cm 90 cm x 120 cm 90 cm x 150 cm 90 cm x 300 cm 120 cm x 180 cm | | |
| Custom sizes | 90 cm per linear meter 120 cm per linear meter | | |
| Special remarks | | | |
| PRODUCT TESTING | | | |
| Tests | Norms | Results | |
| Abrasion resistance | ASTM D3884 | | |
| Colour fastness to light | AATCC 16E | | |
| Accelerated wear test by sim floor machine | U.S. | | |
| Accelerated soiling | U.S. | | |
| Anti-slip | DIN51130 BGR181 | | |
| Water retention | U.S. | 3 l/m ² | |
| Sanitary epidemiologic test | GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV | | |
| Graves tear strength | | | |
| Hardness a shore | | | |
| Elongation | | | |
| FIRE TESTING | | | |
| | | | |
| | Classification of the reaction to fire performance | EN ISO 9239-1 | Efl - S1 |
| Sustainability | <ul style="list-style-type: none"> • Recyclable material • REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals) • Contributes to cleaner environment by reducing need of cleaning chemicals | | |