## 7.2V LI-ION CORDLESS DRIVER-DRILL WITH AUTO-STOP CLUTCH



### CONTROL



21 clutch settings and auto-stop clutch increases fastening control

### SPEED



2-speed gear selection (200 RPM / 650 RPM) for high or low torque applications

### VERSATILITY



Comfortable grip design operates in straight or pistol grip positions

### **PERFORMANCE**



Li-lon batteries charge in 30 minutes, run longer, and deliver 2.5X more cycles than Ni-Cd

# EXTRA CONTROL

## 7.2V LI-ION CORDLESS DRIVER-DRILL

### **Model DF010DSE**

### **FEATURES & BENEFITS**

- Auto-stop clutch: motor automatically stops when the clutch disengages; prevents overdriving the fastener
- 21 clutch settings and drill mode for added fastening control (fastening torque range: 2.7 in.lbs. - 27.0 in.lbs.)
- 2-speed gear selection (200 RPM / 650 RPM) for high or low torque applications
- Comfortable grip design operates in straight or pistol grip positions
- Built-in L.E.D. light illuminates the work area via a separate switch (light will turn off automatically after 5 minutes if the switch is left in the "on" position)
- Low battery indicator: the built-in L.E.D. light blinks when the battery needs to be recharged
- Ultra-lightweight and compact tool that weighs just over a pound
- Li-lon batteries charge in 30 minutes, run longer, and deliver 2.5x more cycles than Ni-Cd
- 30 minute charge time
- 3-year warranty on tool and 1-year warranty on battery and charger

### STANDARD EQUIPMENT

- Tool Case (824842-6)
- 2 ea. 7.2V Lithium-Ion 1.0Ah Battery (BL7010)
- 7.2V 10.8V Lithium-Ion Charger (DC10WA)
- Phillips #1 Double-End Bit
- Phillips #2 Double-End Bit

CDECIFICATIONS

SPECIFICATIONS		
Capacity:	Steel Wood	3/16" 1/4"
No load speed:	Low High	200 RPM 650 RPM
Maximum torque		44 in.lbs.
Watt hours		7.2
Lithium-lon battery		7.2V DC (1.0Ah)
Overall length:	Straight Pistol	11" 8-7/8"
Net weight		1.2 lbs. (w/battery)
Shipping weight		5.0 lbs.
Master carton qty.		4
UPC code		(DF010DSE) 088381-091060

#### **OPTIONAL ACCESSORIES**

■ Phillips #2 Double Ended Bit 1-3/4" (784614-0)











