




HX 5000 T

Product advantages

- Solid and compact frame
- Circuit breaker
- OHV Honda professional engine
- Oil level safety

Miscellaneous

Exceptional robustness for outdoor site work.



This product is QUALIGEN certified. Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After Sales Service) in order to provide the highest level of quality of our and thus to guarantee the users safety.

HX 5000 T

General specifications

Range	Intens
Frequency (Hz)	50
Max. power (kW)	4.00
Max power. (kVA)	5.00
Nominal voltage (V)	400
Number of phase	Three phase - 400 V
Acoustic pressure level Lw	97
Noise level dB(A) - 7m	74

Engine specifications

Engine trademark	Honda
Engine type	GX 270
Distribution	O.H.V.
Start	Launcher
Fuel	Petrol (unlead)
Autonomy (h)	2.5
Consumption (L/h)	2.1
Tank (L)	5.3
Oil Guard	Yes
HP 3600 tr/mn max.	8
Capacity (cm3)	270
Oil capacity (L)	1.1

Alternator specifications

Type	With collar and brush
Regulation	Mechanical
Protection class	IP 23
Insulation class	H

Plugs and panels descriptive

1 x 2P+T 230V 10/16A - circuit breaker + 1 x 3P+T+N 400V 16A - circuit breaker

Dimensions and weight

Length (cm)	71.5
Width (cm)	57
Height (cm)	49
Dry Weight (kgs)	68

Packaging

Packaging type	Box
Length (cm)	73
Width (cm)	58
Height (cm)	49.5
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	168



HX 5000 T

Options

--