



HPU8

Tracked Conventional Tail Excavators



HPU8 - The future of emission-free work.

The electric-hydraulic generator HPU8 is specially developed for the operation of the compact excavator 803 and can be quickly and easily used indoors. The powerful generator is also designed for the loads during breaker operation. If the excavator leaves the premises afterwards, the generator can then simply be continued in electric mode or the diesel operation can be resumed.

- Emission-free drive system for work indoors and in sensitive environments.
- Constant first-class work performance thanks to the 7.5 kW electric motor - even in breaker operation.
- Simply flexible: The HPU8 is easy to transport and can be connected to the excavator undercarriage with a few easy steps.
- 12 meters of hose and 360° operating range offer a generous freedom of movement.
- Sturdy hose feedthrough that protects the hose from damage during application.

Technical specifications

Operating data



**WACKER
NEUSON**
all it takes!

Shipping weight	190 kg
Engine / Motor	
Engine / Motor Voltage, power consumption	3 x 400 volts, 16 amps
Engine performance	7.5 kW
Hydraulic system	
Flow rate	20 l/min
Operating pressure	180 bar
Undercarriage	
Dozer Blade	
Sound level	

Compact excavator 803: Additional weight dual power option equivalent to 23 kg

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE.