



ZFSF 250EBCS/21/3322-402 EN SEFI - Main cabinet 250A

Art.nr.: **EB12782**

Incoming circuit breaker 100-250A (Main circuit breaker).

Connects the network owner's supply and is normally installed as the first exchange. Meter cabinet separately mounted on end with own lockable door.

El-Björn AB

Box 29, SE-334 21 Anderstorp

Tel: (+46) 0371-588 100

E-mail: info@elbjorn.se

About Product

- Enclosure in powder coated, corrosion-resistant galvanized sheet steel
- Frame and lifting eyes are hot-dip galvanized
- Hinges and outer screws of stainless steel
- The frame is designed for pallets and truck transport
- Service friendly plug-in system (BCS)

Technical data

Rated current	250A
Voltage	400V
Incoming Connectable area Al/Cu	95 - 240 mm ²
Incoming MCCB (0.36-1)*250A 3P	1
Measurement Unit Current transformer	300/5A
Measurement Unit Meter bay	1
Outgoing Permanent connection NH00 160A 10-95mm²	2
Outgoing Permanent connection NH1-2 250A 95-240mm²	1
Outgoing 2-pol/230V Schuko Type F	3
Outgoing 5-pol/400V 16A CEE 416-6	3
Outgoing 5-pol/400V 32A CEE 432-6	2
Outgoing 5-pol/400V 63A CEE 463-6	2
RCD 0,03A	4
RCD 0,3A	2
Free module space	1
Short-circuit strength I_{cc}	50 kA
IP rating	IP44
Dimensions H x W x L	1700 x 1300 x 800 mm
Net weight (kg)	204.5
Warranty Length (months)	60
Dimensions (mm)	1700mm x 1305mm x 500mm

El-Björn AB

Box 29, SE-334 21 Anderstorp

Tel: (+46) 0371-588 100

E-mail: info@elbjorn.se