

SCANCLIMBER® SC1300 Mast climbing work platform



SC1300



Platform can be turned 90° to the side of the main platform

Technical data	SC1300 single	SC1300 twin
• Max. platform length / loading capacity	4,2 m / 1300 kg 7,4 m / 1000 kg 10,5 m / 700 kg	11,9 m / 2320 kg 18,3 m / 1700 kg
• Max. freestanding height - with full extended outriggers - with extended outriggers on one side	20 m 15 m	20 m 15 m
• Max. height with top anchor	25 m	25 m
• Max. height with mast anchored	100 m	100 m
• Distance between anchors	18,5 m	18,5 m
• Max. jack load	50 kN	50 kN
• Transport weight	3500 kg	2 x 3500 kg
• Lifting speed	6,0 m / min.	6,0 m / min.
• Mast section, hot dip galvanized	1,25 m / 82 kg	1,25 m / 82 kg
• Electric system - lifting motors - drive motor	400 V/50 Hz/3,0 kW 3 phase/32 A 400 V/1,1 kW	2x400 V/50 Hz/3,0 kW 3 phase/32 A 2x400 V/1,1 kW
• Safety devices - overspeed safety brake - emergency stop and limit switches - electromagnetic brake - phase sequency relay - residual current device	◆ ◆ ◆ ◆ ◆	◆ ◆ ◆ ◆ ◆

Technical data