

GROUND CARE

EQUIPMENT CATALOGUE
2022



Everything for experienced
and professional gardeners





INTRODUCTION

We have everything you need for a perfect garden – whether you are an everyday or expert home gardener or a groundcare and turf care professional.

EXPERT RANGES:-

Lawnflite from petrol mowers to lawn tractors, from spreaders and trailers to scarifiers we have a wide range for the everyday and expert home gardener.

Agri-Fab® lawn products are designed for homeowners who want a beautiful lawn. The quality, time saving products including spreaders, dethatchers and trailers, will ensure you get the most out of your lawn tractor.

Mantis’ range of tillers will help you grow great gardens and keep your lawns looking their best.

GTM’s range of compact and powerful wood chippers are designed to offer a portable option for chipping branches and crops – perfect for tree care, landscaping, forestry and garden maintenance for expert gardeners and professionals.

PROFESSIONAL RANGES:-

Lawnflite PRO’s range of lawnmowers and roller mowers are built to professional specifications with shaft driven gear boxes, heavy duty alloy decks and sealed roller bearings.

Little Wonder offers a range of landscaping debris management equipment that will stand up to your needs, season after season.

Classen professional turf care equipment comes with productivity-enhancing features to help professionals complete more projects quickly and easily to increase profit.

CONTENTS

LAWNMOWERS

OPTIMA PETROL MOWER4

ROLLER MOWERS5

SCYTHE MOWER6

PROFESSIONAL

LAWNFLITE PRO – PROFESSIONAL MOWERS 7-11

LAWN TRACTORS

SMART MINI-RIDERS 12-13

OPTIMA MINI-RIDERS 14-15

SMART LAWN TRACTORS..... 16-19

OPTIMA LAWN TRACTORS 20-21

LAWN TRACTOR ACCESSORIES

LAWNFLITE..... 22-25

AGRI-FAB 26-41

LAWN AND GARDEN CARE PRODUCTS

SCARIFIERS 42-43

WHEELED TRIMMER44

LOG SPLITTERS 45-46

CHAINSAW46

MANTIS - TILLERS AND CULTIVATOR..... 47-55

MANTIS - COMPOSTUMBLER 56-57

GTM - WOOD CHIPPERS AND TREECARE 58-65

GROUND CARE AND TURF CARE PRODUCTS

CLASSEN - PROFESSIONAL TURF CARE EQUIPMENT 66-73

LITTLE WONDER - LANDSCAPING DEBRIS MANAGEMENT EQUIPMENT 74-79

PROFESSIONAL

PROFESSIONAL

OPTIMA PETROL MOWER

The Optima lawnmower is manufactured to suit expert gardeners who want quality, style and additional features at an affordable price.

With a cutting width of 53cm / 21" the Optima has an easy to operate single lever height adjustment with settings from 28mm to a maximum of 92mm. The higher settings allow the machine to cope with longer grass on uneven ground.

Powered by a Briggs & Stratton engine which offers high power with low fuel consumption, low emissions and low noise and is renowned for quality, easy starting and long life.

MODEL AVAILABLE

Model	OPTIMA 53SPBHWIS
Cutting width	53 cm / 21"
Engine	B&S 675 EXi IS, 163 cc
Rated power (kW/min ⁻¹)	2.6 / 2,700
Drive	Self propelled, Hi/Wheel
Deck material	Steel
Start	Electric
Height adjustment	6 positions, central
Handle	Ergo 2 Handle fully foldable
Grass bag (approx.)	70 ltr, soft bag
Mulch kit	Standard
Wheels (f/r)	200 mm / 280 mm
Cutting height	28-92 mm
Weight (approx.)	38 kg
LpA/LwA/LwAg (dB)	86 / 96 / 98



KEY BENEFITS

- 1 Easy mowing on uneven lawns thanks to power drive and high rear wheels
- 2 Choose between bagging or discharge of the clippings
- 3 Mulch kit included as standard
- 4 Powerful engine



2 YEARS WARRANTY*

*2 years for domestic providing the machine is serviced by the supplying dealer.

ROLLER MOWERS

The Lawnflite range of roller mowers enhance the mowing experience whilst delivering the perfect traditional striped finish.

The comfort handles and rear roller makes manoeuvring around the lawn a pleasure, whilst the self-propelled drive takes the effort out. The central height adjustment lever has 5 cutting height settings

from 25mm up to 76mm and a large 60 litre grass bag with bag full indicator.

The range has been developed with cutting performance and comfort at the heart of the lawn mower.

All models in the roller range come complete with the reassurance of a two year domestic warranty.

MODELS AVAILABLE

Model	LRM19PDR
Cutting width	48 cm / 19"
Engine	Loncin, 196 cc
Drive	Split rear roller
Deck material	Steel
Start	Recoil
Speed	Self propelled propulsion
Grass bag (approx.)	60 ltr, soft bag
Cutting height	25-76 mm



KEY BENEFITS

- 1 Large 60 ltr grass bag
- 2 Comfort handle
- 3 Powerful Loncin engines
- 4 Steel deck with washport and metal blade
- 5 Split rear roller



Model	LRM21PDR
Cutting width	53 cm / 21"
Engine	Loncin, 196 cc
Drive	Split rear roller
Deck material	Steel
Start	Recoil
Speed	Self propelled / 4 speed propulsion
Grass bag (approx.)	60 ltr, soft bag
Cutting height	25-76 mm



Model	LRM21PDRES
Cutting width	53 cm / 21"
Engine	Loncin, 196 cc
Drive	Split rear roller
Deck material	Steel
Start	Electric
Speed	Self propelled / 4 speed propulsion
Grass bag (approx.)	60 ltr, soft bag
Cutting height	25-76 mm



WARRANTY*

*2 years for domestic providing the machine is serviced by the supplying dealer.



SCYTHE MOWER

With a working width of 87cm / 34" and a powerful Briggs & Stratton engine, the scythe field mower is the ideal mower for long grass, meadows and paddocks. Optional dozer blade is available for snow clearing and moving soil, making the scythe field mower a valuable helper throughout the year.

MODEL AVAILABLE



KEY BENEFITS

- 1 Non clogging universal knife bar with hardened knife blades
- 2 Handle adjustable to suit height of operator
- 3 87cm / 34" cutting width with adjustable skid plates and side bumper
- 4 Pneumatic wheels



Model	BM87-35
Cutting width	87 cm / 34"
Engine	B&S OHV 450 E Series, 125 cc
Rated power [kW/min ⁻¹]	1.7 / 3,100
Drive	Standard
Cutting system	Universal sickle bar with 4 bar guides
Start	Pull
Height adjustment	10 - 30 mm
Handle	Foldable
Fuel capacity	0.8 ltr
Chassis	Steel
Wheels	13" x 5" x 6", pneumatic
Weight (approx.)	53 kg
LpA/LwA/LwAg (dB)	86 / 98 / 99



MOWERS FOR PROFESSIONALS

Built to professional specifications, with shaft driven gear boxes, heavy duty alloy decks, sealed roller bearings and strong handles, the Lawnflite Pro range offers a machine to suit all applications.

For that fine lawn finish, the 448HR and 553HRS roller drive models are single speed with full width steel rollers producing a pronounced stripe on your lawn. They are quiet in operation, have fan assisted collection and a blade brake clutch which means you don't have to re-start the engine when emptying the grassbag. The 553HRS-PROHS sports a high speed gear to make short work of long lawns, 18% faster than the standard model 553HRS.

The top of the range 553HRSP-HST is a hydrostatic roller lawn mower which is 50% faster than the 553HRS-PROHS.

The four models in the wheeled range have all the features and benefits of the Lawnflite Pro roller mowers. The 448HW, 553HWS and 553HWS-PRO have 2 speed shaft drive gearboxes giving selectable speed to suit differing conditions.

The Pro models also offer additional features for the professional user including a front mounted bumper, strong handle tubes of 25mm plus an additional handle support bracket, a steel deck liner and on the wheeled models, 23cm / 9" alloy twin bearing wheels. The 553HWSP-HST has the additional benefit of Hydrostatic drive.

KEY BENEFITS

- 1 Heavy duty alloy decks built for professional use
- 2 Shaft driven gearbox offers extra durability
- 3 Blade brake clutch stops the blade turning when emptying the grass bag
- 4 Roller mower options provide the fine traditional striped finish
- 5 Large heavy duty 70 or 75 litre fabric grass bag enables longer mowing time
- 6 Quiet operation with fan assisted collection
- 7 Mulch kit and deflector available as accessories (71902-218 and 71901-924)



WARRANTY**

*12 months commercial warranty. 2 years for domestic use providing the machine is serviced by the supplying dealer. 90 days when sold and used for hire.





MODELS AVAILABLE



POWERED BY
HONDA
ROLLER
MOWER

Model	553HRS
Cutting width	53 cm / 21"
Engine	Honda
Rated power (kW/ min ⁻¹)	3.4 / 3,600
Drive	Self propelled
Speed (km/h)	3.9
Deck material	Alloy
Start	Easy pull
Height adjustment	Lever height adjustment
Handle	Folding bolted
Grass bag (approx.)	75 ltr
Mulch kit	Optional - 71902-218
Deflector	Optional rear - 71901-924
Wheels (f/r)	200 mm
Cutting height	15-77 mm
Weight (approx.)	56 kg
Vib. value body	2.4 m/s ²

POWERED BY
HONDA
ROLLER
MOWER
HIGH
SPEED

Model	553HRS-PROHS
Cutting width	53 cm / 21"
Engine	Honda
Rated power (kW/ min ⁻¹)	3.4 / 3,600
Drive	Self propelled
Speed (km/h)	4.6
Deck material	Alloy with steel deck liner
Start	Easy pull
Height adjustment	Lever height adjustment
Handle	Strengthened, folding bolted
Grass bag (approx.)	75 ltr
Mulch kit	Optional - 71902-218
Deflector	Optional rear - 71901-924
Wheels (f/r)	200 mm
Cutting height	15-77 mm
Weight (approx.)	58 kg
Vib. value body	2.4 m/s ²

MODELS AVAILABLE



POWERED BY
HONDA
ROLLER
MOWER

Model	448HR
Cutting width	48 cm / 19"
Engine	Honda
Rated power (kW/ min ⁻¹)	3.7 / 3,600
Drive	Self propelled
Speed (km/h)	3.9
Deck material	Alloy
Start	Easy pull
Height adjustment	Lever height adjustment
Handle	Folding wing nut
Grass bag (approx.)	70 ltr
Mulch kit	N/A
Deflector	N/A
Wheels (f/r)	200 mm
Cutting height	15-77 mm
Weight (approx.)	50 kg
Vib. value body	2.2 m/s ²

POWERED BY
HONDA
ROLLER
MOWER

Model	553HRSP-HST
Cutting width	53 cm / 21"
Engine	Honda
Rated power (kW/ min ⁻¹)	3.4 / 3,600
Drive	Hydrostatic
Speed (km/h)	0 - 6.5
Deck material	Alloy with steel deck liner
Start	Easy pull
Height adjustment	Lever height adjustment
Handle	Strengthened, folding bolted
Grass bag (approx.)	75 ltr
Mulch kit	N/A
Deflector	N/A
Wheels (f/r)	200 mm
Cutting height	15-77 mm
Weight (approx.)	66 kg
Vib. value body	2.4 m/s ²

MODELS AVAILABLE



POWERED BY
HONDA
POWER DRIVE

Model	448HW
Cutting width	48 cm / 19"
Engine	Honda
Rated power (kW/min ⁻¹)	3.7 / 3,600
Drive	Self propelled, 2 speed
Speed (km/h)	3.9
Deck material	Alloy
Start	Easy pull
Height adjustment	Lever height adjustment
Handle	Folding wing nut
Grass bag (approx.)	70 ltr
Mulch kit	N/A
Deflector	N/A
Wheels (f/r)	200 mm / 200 mm
Cutting height	15-77 mm
Weight (approx.)	50 kg
Vib. value body	2.2 m/s ²

MODELS AVAILABLE



POWERED BY
HONDA
POWER DRIVE

Model	553HWS-PRO
Cutting width	53 cm / 21"
Engine	Honda
Rated power (kW/min ⁻¹)	3.4 / 3,600
Drive	Self propelled, 2 speed
Speed (km/h)	3.9
Deck material	Alloy with steel deck liner
Start	Easy pull
Height adjustment	Lever height adjustment
Handle	Strengthened, folding bolted
Grass bag (approx.)	75 ltr
Mulch kit	Optional - 71902-218
Deflector	Optional rear - 71901-924
Wheels (f/r)	230 mm / 230 mm
Cutting height	22-82 mm
Weight (approx.)	62 kg
Vib. value body	2.4 m/s ²



POWERED BY
HONDA
POWER DRIVE

Model	553HWS
Cutting width	53 cm / 21"
Engine	Honda
Rated power (kW/min ⁻¹)	3.4 / 3,600
Drive	Self propelled, 2 speed
Speed (km/h)	3.9
Deck material	Alloy
Start	Easy pull
Height adjustment	Lever height adjustment
Handle	Folding bolted
Grass bag (approx.)	75 ltr
Mulch kit	Optional - 71902-218
Deflector	Optional rear kit - 71901-924
Wheels (f/r)	200 mm / 200 mm
Cutting height	15-77 mm
Weight (approx.)	56 kg
Vib. value body	2.4 m/s ²




POWERED BY
HONDA
POWER DRIVE

Model	553HWS-PRO
Cutting width	53 cm / 21"
Engine	Honda
Rated power (kW/min ⁻¹)	3.4 / 3,600
Drive	Hydrostatic
Speed (km/h)	0 - 6
Deck material	Alloy with steel deck liner
Start	Easy pull
Height adjustment	Lever height adjustment
Handle	Handle strengthened, folding bolted
Grass bag (approx.)	75 ltr
Mulch kit	Optional - 71902-218
Deflector	Optional rear - 71901-924
Wheels (f/r)	230 mm / 230 mm
Cutting height	22-84 mm
Weight (approx.)	68 kg
Vib. value body	2.4 m/s ²

Mulch kit and deflector available as accessories (71902-218 and 71901-924)



MODELS AVAILABLE



Model	MINIRIDER60SDE
Cutting width	60 cm / 24"
Height adjustment	5 positions, 38-95 mm
Engine	MTD, 1 cylinder, 196 cc
Start	Electric
Rated power (kW/min ⁻¹)	3.3 / 3,000
Fuel capacity (approx.)	1.2 ltr
Transmission	Transmatic
Grass catcher (approx.)	-
Mulch kit	Mulch plug only: available as accessory (731-2505)
Deflector	Standard
Turning radius	46 cm / 18"
Wheels (f/r)	13" x 5" / 16" x 6.5"
Measurements (approx.)	L158 / W 78 / H 110 cm
Weight (approx.)	111 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	86 / 96 / 98

KEY BENEFITS


- 1 Laterally displaced deck allows mowing close to edges
- 2 Space saving storage thanks to small dimensions
- 3 Large grass catcher (Standard on MINIRIDER60RDE)
- 4 "Shift-on-the-go" transmatic transmission with 6 speeds
- 5 Step through frame makes getting on and off easy
- 6 Optimal mulch kits and hitch kits available as accessories

SMART MINI-RIDERS

Our Smart mini-riders provide all the benefits of a lawn tractor in a more compact size. They are easy to operate, have an attractive design and are really versatile: they can bag, discharge or mulch grass clippings (optional kits may be required).

They are ideal for gardens where the use of a tractor is restricted by flowerbeds, bushes or corners.

The step through frame makes getting on and off easy and the choice of transmissions delivers a smooth and comfortable ride. After use they can be stored away easily.



Model	MINIRIDER60RDE
Cutting width	60 cm / 24"
Height adjustment	5 positions, 38-95 mm
Engine	MTD, 1 cylinder, 196 cc
Start	Electric
Rated power (kW/min ⁻¹)	3.3 / 2,850
Fuel capacity (approx.)	1.2 ltr
Transmission	Transmatic
Grass catcher (approx.)	150 ltr
Deflector / Mulch	Available as accessory (Part no.: 196-707-678)
Turning radius	46 cm / 18"
Wheels (f/r)	13" x 5" / 16" x 6.5"
Measurements (approx.)	L192 / W 83 / H 112 cm
Weight (approx.)	140 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	86 / 96 / 98



2 YEARS WARRANTY*


*2 years for domestic providing the machine is serviced by the supplying dealer.



OPTIMA MINI-RIDERS

If you need to cut around a third of an acre up to one acre and are looking for a machine that is well equipped, simple to use and easy to store with small dimensions, then the Optima mini-riders are for you.

These mini-riders combine all the advantages of a mini-rider with the performance of a lawn tractor. The level indicator conveniently allows you to monitor the large 4.9 litre fuel tank at any time. The step-through frame has no pedals or switches to get in the way, making getting on and off the machine safe and easy.



Model	MINIRIDER76RDHE
Cutting width	76 cm / 30"
Height adjustment	5 positions, 38-95 mm
Engine	MTD, 1 cylinder, 382 cc
Start	Electric
Rated power (kW/min ⁻¹)	7.9 / 2,900
Fuel capacity (approx.)	4.9 ltr
Transmission	Hydrostatic
Grass catcher (approx.)	150 ltr
Mulch kit	Available as accessory (Part no.: 196-334-600)
Deflector	Available as accessory (Part no.: 196-334-600)
Turning radius	46 cm / 18"
Wheels (f/r)	13" x 5" / 16" x 6.5"
Measurements (approx.)	L192 / W 86 / H 112 cm
Weight (approx.)	145 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100

KEY BENEFITS


- 1 Smooth and powerful MTD engine with convenient electric start
- 2 Six speed transmatic transmission with continuous variable shifting or hydrostatic transmission
- 3 Laterally displaced deck allows mowing close to lawn edges
- 4 Compact design with a small turning radius of only 46cm / 18"
- 5 Step through frame makes getting on and off safe and easy
- 6 200 ltr twin bag collector. NOTE: Will require additional high lift bagging blade 742-05621A. (Optional on MINIRIDER76SDE)



MODELS AVAILABLE



Model	MINIRIDER76SDE
Cutting width	76 cm / 30"
Height adjustment	5 positions, 38-95 mm
Engine	MTD, 1 cylinder, 382 cc
Start	Electric
Rated power (kW/min ⁻¹)	7.9 / 2,900
Fuel capacity (approx.)	4.9 ltr
Transmission	Transmatic
Grass catcher (approx.)	Available as accessory (Part no.: 19A3001400EM)
Mulch kit	Available as accessory (Part no.: 731-09312)
Deflector	Standard
Turning radius	46 cm / 18"
Wheels (f/r)	13" x 5" / 16" x 6.5"
Measurements (approx.)	L157 / W 85 / H 112 cm
Weight (approx.)	127 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100



Model	MINIRIDER76RDE
Cutting width	76 cm / 30"
Height adjustment	5 positions, 38-95 mm
Engine	MTD, 1 cylinder, 382 cc
Start	Electric
Rated power (kW/min ⁻¹)	7.9 / 2,900
Fuel capacity (approx.)	4.9 ltr
Transmission	Transmatic
Grass catcher (approx.)	150 ltr
Mulch kit	Available as accessory (Part no.: 196-334-600)
Deflector	Available as accessory (Part no.: 196-334-600)
Turning radius	46 cm / 18"
Wheels (f/r)	13" x 5" / 16" x 6.5"
Measurements (approx.)	L192 / W 83 / H 112 cm
Weight (approx.)	145 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100



Tow Hitches are available as an optional accessory for side (196-397-000) and rear discharge (196-398-000) mini-riders.

2 YEARS WARRANTY*

*2 years for domestic providing the machine is serviced by the supplying dealer.



SMART LAWN TRACTORS

If you have a large lawn to mow and want the job done as quickly as possible, a Smart lawn tractor is the perfect choice for you, whether you opt for a rear discharge or side discharge model.

Smart lawn tractors are practical, robust and reliable, and with a cutting width of 76cm / 30" to 105cm / 41", they are ideal for areas measuring 1000m² to 3000m².

Thanks to the small turning radius of 46cm / 18", mowing around bushes and flowerbeds is safe and simple. For your comfort a step through frame, makes it easy to get on and off, as well as an adjustable seat, headlights and ergonomically designed controls for deck engagement and transmission.

The cutting height can be easily adjusted to five positions between 30mm and 95mm.

KEY BENEFITS


- 1 Step through frame makes getting on and off easy
- 2 Large grass bag offers the ability to cover large areas in a short time
- 3 Small turning radius of only 46cm / 18"
- 4 Offset deck allows mowing close to the edge
- 5 Floating deck and pivoting front axle enables smooth engagement
- 6 "Direct Collect"[®] A large turbo fan assister on the RC125 and MTD76, coupled with the heavy duty cutter blade, physically throws and blows grass cuttings, leaves and other debris direct! into the large capacity collector.
- 7 Shift-on-the-go with continuous variable shifting.




2 YEARS WARRANTY*

*2 years for domestic providing the machine is serviced by the supplying dealer.

MODELS AVAILABLE



Model	RF125
Cutting width	96 cm / 38"
Height adjustment	5 positions, 30-95 mm
Engine	MTD, 1 cylinder, 382 cc
Start	Electric
Rated power (kW/min ⁻¹)	7.6 / 2,800
Fuel capacity (approx.)	3.8 ltr
Transmission	Transmatic
Grass catcher (approx.)	Available as accessory (Part no.: OEM-190-180A)
Mulch kit	Available as accessory (Part no.: OEM-190A116)
Deflector	Standard
Turning radius	46 cm / 18"
Wheels (f/r)	13" x 5" / 18" x 6.5"
Measurements (approx.)	L170 / W 107 / H 100 cm
Weight (approx.)	150 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100



Model	RG145
Cutting width	107 cm / 42"
Height adjustment	5 positions, 30-95 mm
Engine	MTD, 1 cylinder, 547 cc
Start	Electric
Rated power (kW/min ⁻¹)	12.5 / 2,800
Fuel capacity (approx.)	3.8 ltr
Transmission	Transmatic
Grass catcher (approx.)	Available as accessory (Part no.: OEM-190-180A)
Mulch kit	Available as accessory (Part no.: OEM-190A116)
Deflector	Standard
Turning radius	46 cm / 18"
Wheels (f/r)	15" x 6" / 20" x 8"
Measurements (approx.)	L 170 / W 115 / H 100 cm
Weight (approx.)	175 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100

2 YEARS WARRANTY*

*2 years for domestic providing the machine is serviced by the supplying dealer.



MTD
10000 **AV**

TRANSMATIC

2-in-1

REAR DISCHARGE

2000m²

Model	RC125
Cutting width	76 cm / 30"
Height adjustment	5 positions, 30-95 mm
Engine	MTD, 1 cylinder, 382 cc
Start	Electric
Rated power (kW/min ⁻¹)	6.5 / 2,400
Fuel capacity (approx.)	3.8 ltr
Transmission	Transmatic
Grass catcher (approx.)	200 ltr, soft bag
Mulch kit	-
Deflector	Standard
Turning radius	46 cm / 18"
Wheels (f/r)	13" x 5" / 18" x 6.5"
Measurements (approx.)	L224 / W 91 / H 103 cm
Weight (approx.)	185 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100



MTD
10000 **AV**

TRANSMATIC

3-in-1
Option

REAR DISCHARGE

2000m²

Model	RE125
Cutting width	92 cm / 36"
Height adjustment	5 positions, 30-95 mm
Engine	MTD, 1 cylinder, 382 cc
Start	Electric
Rated power (kW/min ⁻¹)	7.5 / 2,750
Fuel capacity (approx.)	3.8 ltr
Transmission	Transmatic
Grass catcher (approx.)	240 ltr, soft bag with hard top
Mulch kit	Available as accessory (Part no.: 196-749A678)
Deflector	Available as accessory (Part no.: 196-750A678)
Turning radius	46 cm / 18"
Wheels (f/r)	13" x 5" / 18" x 6.5"
Measurements (approx.)	L225 / W 99 / H 103 cm
Weight (approx.)	195 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100



MTD
10000 **AV**

HYDROSTAT

3-in-1
Option

REAR DISCHARGE

2500m²

Model	RE130H
Cutting width	92 cm / 36"
Height adjustment	5 positions, 30-95 mm
Engine	MTD, 1 cylinder, 382 cc
Start	Electric
Rated power (kW/min ⁻¹)	7.5 / 2,750
Fuel capacity (approx.)	3.8 ltr
Transmission	Hydrostatic
Grass catcher (approx.)	240 ltr, soft bag with hard top
Mulch kit	Available as accessory (Part no.: 196-749A678)
Deflector	Available as accessory (Part no.: 196-750A678)
Turning radius	46 cm / 18"
Wheels (f/r)	13" x 5" / 18" x 6.5"
Measurements (approx.)	L225 / W 99 / H 103 cm
Weight (approx.)	195 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100



MTD
10000 **AV**

TRANSMATIC

2-in-1

REAR DISCHARGE

2000m²

Model	MTD76
Cutting width	76 cm / 30"
Height adjustment	5 positions, 30-95 mm
Engine	MTD, 1 cylinder, 382 cc
Start	Electric
Rated power (kW/min ⁻¹)	6.5 / 2,400
Fuel capacity (approx.)	3.8 ltr
Transmission	Transmatic
Grass catcher (approx.)	200 ltr, soft bag
Mulch kit	-
Deflector	Standard
Turning radius	46 cm / 18"
Wheels (f/r)	13" x 5" / 18" x 6.5"
Measurements (approx.)	L224 / W 91 / H 103 cm
Weight (approx.)	185 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100



MTD
10000 **AV**

TRANSMATIC

3-in-1
Option

REAR DISCHARGE

3000m²

Model	RN145
Cutting width	105 cm / 41"
Height adjustment	5 positions, 30-95 mm
Engine	MTD, 547 cc
Start	Electric
Rated power (kW/min ⁻¹)	8.9 / 2,600
Fuel capacity (approx.)	3.8 ltr
Transmission	Transmatic
Grass catcher (approx.)	240 ltr, soft bag with hard top
Mulch kit	Available as accessory (Part no.: 196-749A678)
Deflector	Available as accessory (Part no.: 196-750A678)
Turning radius	46 cm / 18"
Wheels (f/r)	15" x 6" / 18" x 9.5"
Measurements (approx.)	L225 / W 110 / H 103 cm
Weight (approx.)	198 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100



MTD
10000 **AV**

TRANSMATIC

3-in-1
Option

SIDE DISCHARGE

2500m²

Model	MTD96
Cutting width	96 cm / 38"
Height adjustment	5 positions, 30-95 mm
Engine	MTD, 1 cylinder, 382 cc
Start	Electric
Rated power (kW/min ⁻¹)	7.6 / 2,800
Fuel capacity (approx.)	3.8 ltr
Transmission	Transmatic
Grass catcher (approx.)	Available as accessory (Part no.: OEM-190-180A)
Mulch kit	Available as accessory (Part no.: OEM-190A116)
Deflector	Standard
Turning radius	46 cm / 18"
Wheels (f/r)	13" x 5" / 18" x 6.5"
Measurements (approx.)	L170 / W 107 / H 100 cm
Weight (approx.)	150 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100

Tow Hitches are available as an optional accessory for rear discharge lawn tractors (196-399-000).



OPTIMA LAWN TRACTORS

Comfortable and versatile – you won't have to sacrifice a thing with Optima lawn tractors. With a cutting width of 105cm / 41" and 107cm / 42" they are ideal for mowing large areas. Optima lawn tractors are fitted with a high-performance engine, guaranteeing long service life, as well as a low-maintenance robust hydrostatic transmission as standard for a smooth and comfortable ride.

The forward-folding and removable hood gives easy access for maintenance work at any time. The floating deck adapts to uneven ground on rough terrains and can be cleaned with the utmost ease and convenience, thanks to the deck wash nozzle.

MODELS AVAILABLE



Model	LG200H
Cutting width	107 cm / 42"
Height adjustment	5 positions, 30-95 mm
Engine	MTD, V Twin 679 cc
Start	Electric
Rated power (kW/min ⁻¹)	12.5 / 2,800
Fuel capacity (approx.)	3.8 ltr
Transmission	Hydrostatic
Grass catcher	Available as accessory (Part no.: OEM-190-180A)
Mulch kit	Standard
Deflector	Standard
Turning radius	46 cm / 18"
Wheels (f/r)	15" x 6" / 20" x 8"
Measurements (approx.)	L170 / W 115 / H 100 cm
Weight (approx.)	175 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100

KEY BENEFITS

- 1 Powerful and quiet MTD engine
- 2 Small turning radius of only 46cm / 18"
- 3 Deck wash nozzle makes for easy deck cleaning
- 4 Step through frame makes getting on and off easy
- 5 Floating deck and pivoting front axle enables smooth engagement
- 6 Large grass bag offers the ability to cover large areas in a short time
- 7 The LN200H with rear discharge has a grass catcher which is easy to empty from the driver's seat



Model	LN200H
Cutting width	105 cm / 41"
Height adjustment	5 positions, 30-95 mm
Engine	MTD, V Twin 679 cc
Start	Electric
Rated power (kW/min ⁻¹)	11.6 / 2,600
Fuel capacity (approx.)	3.8 ltr
Grass catcher (approx.)	240 ltr
Mulch kit	Available as accessory (Part no.: 196-749A678)
Deflector	Available as accessory (Part no.: 196-750A678)
Turning radius	46 cm / 18"
Wheels (f/r)	15" x 6" / 18" x 9.5"
Measurements (approx.)	L225 / W 1109 / H 103 cm
Weight (approx.)	198 kg
Vib. value body (K Factor)	1 / 0.5 m/s ²
LpA/LwA/LwAg (dB)	88 / 98 / 100

Tow Hitch is available as an optional accessory for the LN200H (196-399-000).



2 YEARS WARRANTY*

*2 years for domestic providing the machine is serviced by the supplying dealer.



LAWNFLITE LAWN TRACTOR PRODUCTS

Our Lawnflite range of equipment includes trailers, de-thatchers, spreaders and rollers. To help you get the maximum out of your lawn tractor most products can be towed behind to help with your jobs around the garden.

TRAILERS are ideal for loading/unloading soil, gravel and sand
A **DETHATCHER** will remove moss and thatch from your lawn
SPREADERS are suitable for distributing fertiliser, grass seed and salt
A **STEEL ROLLER** will help you achieve the traditional green stripes in your lawn

TRAILERS

UTILITY STEEL TRAILER LSC500

Ideal for unloading soil, gravel and sand as well as carrying tools, animal feed, landscaping materials and firewood

Removable tailgate and foot pedal release help with loading and unloading and the trailer can easily convert into a flat-bed trailer without the need for tools

Suitable to use with all makes of lawn tractor, it has a capacity of 500lbs and a trailer bed that measure 97 cm x 71.5 cm x 30 cm



UTILITY STEEL TRAILER LSC1200

Ideal for unloading soil, gravel and sand as well as carrying tools, animal feed, landscaping materials and firewood

Foot pedal release mechanism for easy dumping and can be assembled in 25 minutes

A multi hitch makes it suitable to use with all makes of lawn tractor, it has a capacity of 1200 lbs and a large trailer bed that measure 150 cm x 77.5 cm x 51.6 cm

Limited stock for 2022



QUICK ASSEMBLY STEEL TRAILER LSC750

The steel trailer with a capacity of 750 lbs has folding sides and can be assembled in less than 15 minutes. It features a foot pedal release mechanism for easy dumping including a safety lock pin

The trailer bed measure 107 x 70 x 34 cm

A multi hitch makes it suitable to use with all makes of lawn tractor

Limited stock for 2022



T-HANDLE PUSH/TOW POLYPROPYLENE TRAILER LPC650

The versatile Polypropylene trailer can be used with your lawn tractor as a tow behind trailer or as a hand wheeled trailer with a comfortable T-handle

The one piece Polypropylene bed is quiet and resistant to rust with a slanted tail end and foot pedal release mechanism for easy tipping

With a 650 lbs capacity, it's a versatile choice for your garden



UTILITY POLYPROPYLENE TRAILER LPC1200

The Polypropylene dump trailer has a quick release tipper latch for its 1200 lbs capacity load

It features a rugged Polypropylene bed and all steel durable tilt and pivot frame with a powder coat finish. Sealed ball bearing 'wheels' mean no greasing is required



DETHATCHER



40" TINE DETHATCHER LST40

The LST40 is a 40" /102 cm steel tine dethatcher that used regularly will remove moss and thatch from your lawn to keep it looking its best

It features 20 heat treated steel spring-loaded tines for long life. The whole unit is constructed from steel and features a heavy-duty tray to add weight for extra penetration.

SPREADERS



125 LBS WALK BEHIND SPREADER LPS125A

The LPS125A is ideal for medium to large areas, which may be difficult to access. The Polypropylene hopper can hold up to 125 lbs / 60 ltr and the spreader plate is rust proof ensuring long life

The pneumatic tyres enable this spreader to be easily pushed along the ground and its rain cover ensures materials are kept dry. A rate setting control on the handle helps with precise flow adjustments. As with all our spreaders, it is suitable for both fertiliser, seed and ice melt



125 LBS WALK BEHIND SALT SPREADER TPSS125

The TPSS125 is a 125lb walk behind salt spreader for fertiliser and seed. With a rate setting control, 14" pneumatic tyres, stainless steel parts and solid linkage.



100 LBS WALK BEHIND SALT SPREADER TPSS100

The TPSS100 is a 100 lbs walk behind salt spreader that can also be used for fertiliser and seed. It features a rate setting control, 12" pneumatic tyres, stainless steel parts and a spread width of 10' - 12'.



125 LBS TOW SPREADER LTS125

The LTS125 is ideal for medium to large areas. The Polypropylene hopper can hold up to 125 lbs / 60 ltr, whilst the spreader plate is rust proof ensuring long life. The pneumatic tyres ensure this spreader can be easily towed behind most lawn tractors with a tow bar and its rain cover keeps everything dry

The flow lever can be easily operated from the driver's seat and can cover 25,000 sq. ft. suitable for use with both fertiliser, seed and ice melt

ROLLER



36" STEEL ROLLER LSR36

The LSR36 heavy duty puncture proof steel roller helps you achieve the traditional green stripe lawn effect as well as packing down new sod, seed and to level your uneven lawn.

The easy fill fitting means you can add water or sand easily to adjust the pressure placed on the ground - use less for soft ground and more for hard ground. It can be towed behind most lawn tractors or ride-on mowers.



AGRI-FAB LAWN TRACTOR PRODUCTS

Agri-Fab® is the largest supplier of tractor accessories in the world. Made in the US, they know what accessories lawn tractor users need.

Agri-Fab® lawn tractor products are designed for homeowners who want a beautiful lawn, yet want the job of lawn care to be quick and easy. Agri-Fab's quality and time-saving products will ensure you get the most out of your lawn tractor, making lawn care easy, year after year.

SMARTLINK™ SYSTEM

The Agri-Fab SmartLINK™ system is an incredibly innovative system which allows different tools to be fitted to the main attachment, saving you space in your shed or garden; and is ideal for fitting on lawn tractors and other ride-on mowers. No tools are required as a simple locking-mechanism holds the tools in place on the master platform.

SmartLINK™ Master Platform 45-0473

The Agri-Fab base is the foundation of the SmartLINK™ lawn-care system. It's robust and highly durable, with a welded drawbar and durable heavy-gauge steel deck to ensure a lengthy service-life. It runs on a pair of pneumatic tyres, so rolls smoothly over rough ground; and has a weight tray which can be loaded should added pressure be required when aerating or dethatching. Switch from one lawn implement to another, in seconds, without using any tools.

SMARTLINK™ SPIKE AERATOR 45-0458

The tractor-towed spike aerator with 100 super-sharp aeration-spikes with a large 104cm/41" working-width, achieves thorough soil-penetration across a substantial area and a level of productivity that can't be achieved with a conventional walk-behind aerator. Once the spikes have done their work, moisture, light, air and nutrients will be able to better penetrate the root-network, which in turn will encourage vigorous, healthy grass-growth. The spike aerator is fitted to the master platform via a simple locking-mechanism.

(While stocks last)

SMARTLINK™ CORE AERATOR 45-0474

The tractor-towed core aerator penetrates far more deeply than a surface aerator, ensuring water, air and nutrients reach the whole root system across its large 104cm/41" working-width whilst helping with surface drainage. The 20 aeration knives are rust-proof for longevity and the deck is made of heavy gauge steel. The core aerator is fitted to the master platform via a simple locking mechanism.

SMARTLINK™ TINE DETHATCHER 45-0457

When moss and thatch build-up on the surface of the lawn, the supply of nutrients and water is cut off, leaving the grass discoloured and unhealthy. The SmartLINK tine dethatcher will loosen and lift the offending growth, allowing the turf to breathe again. With a working width of 107cm/42", it's equipped with 20 heat treated tines for strength and durability. Weights can be added to the master-platform for increased penetration where conditions suit. The dethatcher is fitted to the master platform via a simple locking mechanism.

SMARTLINK



SMARTLINK



SMARTLINK



SMARTLINK





WHY USE AN AERATOR?

Aeration is the process of inserting holes in the ground which opens up the soil surface to let grass roots get the air and moisture they need for healthy growth. When undertaken regularly, this process will leave you with an enviably lush and green-looking lawn

Spike Aerator 45-0544

A towed spike aerator for easy and quick coverage of large areas, designed to achieve excellent soil penetration without leaving soil plugs behind with a large working width of 102cm / 40". Its 10 galvanised aeration discs cut into the turf, with the resulting slits allowing fertiliser, air, water, light and nutrients to better penetrate the surface - you'll notice a gradual but marked improvement in grass-condition. The aeration depth can be adjusted by stacking the weight tray. The spikes can be raised to a transport position when moving from lawn to lawn; a foldable hitch makes for easy storage. Supplied with a universal hitch-pin, it can be paired-up with any lawn tractor.



Spike Aerator 45-0544	
Towing Mechanism	Hitchpin and Hole
Working Width	102cm / 40"
Aeration Depth	Up to 6.5cm
Blades	10 x Aeration Discs - Galvanised Steel
Weight Tray	Yes
Transport Handle	Yes
Axle	Heavy Duty
Wheels	With Semi-Pneumatic Tyres

Plug Aerator 45-0299

Thanks to the 140lbs weight-tray, this plug aerator is capable of penetrating the toughest soil-types, adjustable up to to 8cm / 3" aeration depth. The heat-treated steel aeration spools won't buckle or break under heavy loads. It has a generous 122cm / 48" working-width, so you'll be able to cover a lot of ground with each pass. The wide-profile pneumatic tyres provide traction and manoeuvrability, while also being gentle on the turf. The aeration spools can be raised from the driver's seat with a single cantilevered handle. A universal hitch-pin is included.



Plug Aerator 45-0299	
Towing Mechanism	Hitchpin and Hole
Working Width	122cm / 48"
Aeration Depth	Down to 75mm / 0.3"
Blades	8 with 32 Hollow Coring-Points
Weight Tray	Yes - Capacity: 80kg / 176lbs
Transport Handle	Yes
Axle	Heavy Duty
Wheels	250mm x 100mm / 10" x 4" - Solid Tyres
Dimensions	L: 89cm x W: 132cm x H: 91cm / L: 35" x W: 52" x H: 36"
Weight	36.5kg

Aerator/Seeder 45-0545

The dual-purpose Aerator/ Seeder uses a set of 10 galvanised steel spike disks that cut tiny slits in the surface-pan, allowing water, light and nutrients to access the root system. Its robust build quality, corrosion-proof Polyethylene hopper and chain-driven transmission all work to ensure a lengthy product life. A 107cm / 42" working-width and 176lb hopper make it suitable for areas of up to 40,000sq. ft, you can aerate and seed in one pass saving time. Ideal for spreading seeds and granular fertiliser. It has smooth-running rib-tread wheels, and is supplied with a universal hitch-pin, for use with any lawn tractor.




Aerator / Seeder 45-0545	
Towing Mechanism	Hitchpin and Hole
Hopper Capacity	80kg / 176lbs
Hopper Construction	Polypropylene
Spreading Width	107cm / 42"
Flow Rate Control	Lever - Adjustable from Driving-Seat
Gearing	Chain
Axle	Steel
Wheels	254mm x 45mm / 10" x 1.7"
Ideal for Spreading	Seeds, Granular Herbicides, Granular Fertilisers
Also Suitable for Spreading	Ice Melt
Weight	37.6kg

WHY USE A DETHATCHER?

When moss and thatch build up on the surface of the lawn, the supply of nutrients and water to the roots is cut off, leaving the grass discoloured and unhealthy. A dethatcher will loosen and lift off the moss and thatch allowing the grass to breathe again.

Spring Tine Dethatcher 45-0294


This dethatcher has a 102cm / 40" working-width, with 20 heat treated/spring loaded tines, making it possible to cover very large areas. It sits on a pair of flat-free tyres that run smoothly over bumpy ground; and it comes with a universal link-pin, which facilitates use with all makes of ride-on mower. Other benefits include a cantilevered handle, which makes it easy to raise the tines for transport; and a heavy duty weight tray, which can be ballasted when more tine-pressure is required.



Spring Tine Dethatcher 45-0294	
Working Width	102cm / 40"
Number of Tines	20
Tine Diameter	80mm / 3"
Weight Tray	Yes - 31.5kg / 70lbs
Transport Handle	Yes
Axle	Steel
Wheels	180mm x 40mm / 7" x 1.5" - Flat-Free Tyres
Weight	15.5kg

Spring Tine Dethatcher 45-0295

A key feature of this dethatcher is its weight tray, which can take up to 70lbs of ballast for more effective thatch removal. It has a large 122cm / 48" working-width for the fast coverage of large areas. An easy-to-use cantilevered handle allows the tines to be raised for transportation; and flat-free tyres ensure the unit rolls smoothly, even on rough ground. The 24 tines on this model are heat-treated for strength and durability. A universal link-pin is included.



Spring Tine Dethatcher 45-0295	
Working Width	122cm / 48"
Number of Tines	24
Tine Diameter	80mm / 3"
Weight Tray	Yes - Capacity: 31.5kg / 70lbs
Transport Handle	Yes
Axle	Steel
Wheels	180mm x 40mm / 7" x 1.5"
Dimensions	L: 100cm x W: 122cm x H: 105cm / L: 39" x W: 48" x H: 41cm
Weight	18kg



Towed Broadcast Spreader 45-0530

This towed broadcast spreader has been built to keep performing season-after-season, with its fully enclosed transmission; tubular-steel frame; and rust-proof Polypropylene hopper. This model also features fully pneumatic tyres, which provide traction and manoeuvrability, while ensuring a smooth ride on rough ground. For convenience, the on/off control can be accessed from the driver's seat of your lawn tractor. Thanks to its lightweight design (17lbs) and universal hitch, it is suitable for use with lower-powered lawn-tractors.



Towed Broadcast Spreader 45-0530	
Towing Mechanism	Hitchpin and Hole
Hopper Capacity	85lbs / 39kg
Hopper Construction	Polypropylene
Spreading Width	2.5m-3m / 8ft.-10ft.
Coverage Per Fill (Max.)	1300m ² / 14,000 sq. ft.
Flow Rate Control	Yes
Gearing	Fully Enclosed
Axle	13mm / 0.5"
Wheels	250mm x 100mm / 10" x 4" - with Pneumatic Tyres
Ideal for Spreading	Seeds, Granular Herbicides, Granular Fertilisers, Pellet Fertilisers
Also Suitable for Spreading	Rock Salt, Ice Melt
Weight	8.2kg

Deluxe Broadcast Push Spreader 45-0531

This push spreader features a direct rod control that opens the slide gate for precise spreading and reliable coverage up to 125cm / 10" width. The 85lbs / 39kg capacity Polypropylene hopper and spreader plate are rustproof. 10" pneumatic tyres allow for smooth transport over rough terrain.



Deluxe Broadcast Push Spreader 45-0531	
Hopper Capacity	39kg / 85lbs
Hopper Construction	Polypropylene
Spreading Width	2.4m-3.5m / 8ft.-10ft.
Coverage Per Fill (Max.)	Up to 14,000 sq.ft
Flow Rate Control	Yes - Handlebar-Mounted Lever
Gearing	Single
Axle	13mm / 0.5"
Wheels	10" / 25cm with Pneumatic Tyres
Ideal for Spreading	Granular Herbicides, Granular Fertilisers
Also Suitable for Spreading	Ice Melt, Seeds, Pellet Fertilisers

WHY USE A SPREADER?

Using a spreader allows you to have the most accurate and even distribution of seeds and fertilisers, getting the job done more efficiently and quickly. Agri-Fab has a variety of tow and push spreaders with a large range of capacities. Most models include pneumatic tyres for easy manoeuvrability on any surface.

Push Spreader 45-0566

This compact push spreader has a 50lb / 23kg capacity rust-proof Polypropylene hopper. The built-in deflector and easy-to-use controls help spread the material evenly every time. 25cm / 10" Polypropylene wheels move over terrain easily and never need air. The fold up kickstand allows for easy storage.



Push Spreader 45-0566	
Hopper Capacity	50lbs / 23kg
Hopper Construction	Polypropylene
Flow Rate Control	Yes - Handlebar-Mounted Lever
Gearing	Single
Wheels	10" / 25cm Polypropylene Wheels
Ideal for Spreading	Granular Herbicides, Granular Fertilisers
Also Suitable for Spreading	Ice Melt, Seeds, Pellet Fertilisers

Pro Push Spreader 45-0532

This push spreader features a direct rod control that opens the slide gate for precise spreading and reliable coverage up to 125cm / 10" width. The 85lbs / 39kg capacity Polypropylene hopper and spreader plate are rustproof. 10" pneumatic tyres allow for smooth transport over rough terrain.



Pro Push Spreader 45-0532	
Hopper Capacity	39kg / 85lbs
Hopper Construction	Polypropylene
Spreading Width	14,000 sq.ft
Flow Rate Control	Yes - Handlebar-Mounted Lever
Gearing	Single
Axle	13mm / 0.5"
Wheels	255mm x 100mm / 10" x 4" - with Pneumatic Tyres
Ideal for Spreading	Granular Herbicides, Granular Fertilisers
Also Suitable for Spreading	Ice Melt, Seeds, Pellet Fertilisers

Push Broadcast Spreader 45-0526

This push broadcast spreader features setting recommendations for multiple materials. The large Polypropylene hopper 110lbs / 50kg covers an approx. area of 17,500 sq.ft and has soft grip handles for working in comfort on such a large area. The large pneumatic tyres make for easy manoeuvrability.

(While stocks last)



Push Broadcast Spreader 45-0526	
Hopper Capacity	50kg / 110lbs
Hopper Construction	Polypropylene
Flow Rate Control	Yes - Handlebar-Mounted Lever
Gearing	Single
Axle	13mm / 0.5"
Wheels	255mm x 100mm / 10" x 4" - with Pneumatic Tyres
Ideal for Spreading	Granular Herbicides, Granular Fertilisers
Also Suitable for Spreading	Ice Melt, Seeds, Pellet Fertilisers

Push Spreader 45-0576

The large rustproof Polypropylene hopper and spreader plate will increase the product life of this spreader. The large hopper 110lbs / 50kg covers an area of approx. 17,500 sq.ft. Spreader setting recommendations are included for easy use. Pneumatic tyres let you go anywhere to get the job done.



Push Spreader 45-0576	
Hopper Capacity	50kg / 110lbs
Hopper Construction	Polypropylene
Flow Rate Control	Yes - Handlebar-Mounted Lever
Gearing	Single
Axle	13mm / 0.5"
Wheels	255mm x 100mm / 10" x 4" - with Pneumatic Tyres
Ideal for Spreading	Granular Herbicides, Granular Fertilisers
Also Suitable for Spreading	Ice Melt, Seeds, Pellet Fertilisers

Push Broadcast Spreader 45-0462

With an enclosed commercial grade gear box for smooth rolling and easy maintenance this large spreader is ideal for covering approx. 25,000 sq. ft. Key to the spreader is its professional-style control system. Quick and simple use, it allows for precise calibration of the spread-rate, in turn ensuring wastage is kept to a minimum.

It weighs just 37lbs and runs on a set of smooth-rolling bearing-mounted wheels, so it couldn't be easier to push. Large-diameter pneumatic tyres make it highly manoeuvrable and provide plenty of traction on muddy ground.



Push Broadcast Spreader 45-0462	
Hopper Capacity	56kg / 130lbs
Hopper Construction	Polypropylene
Spreading Width	Up to 3.6m / 12'
Coverage Per Fill (Max.)	2325m ² / 25,000 sq.ft. (Approx.)
Flow Rate Control	Yes - Professional
Gearing	Commercial-Duty
Axle	Steel
Wheels	255mm x 100mm / 10" x 4" - Pneumatic Tyres
Ideal for Spreading	Rock Salt, Granular Fertilisers
Also Suitable for Spreading	Granular Herbicides, Ice Melt, Pellet Fertilisers
Weight	16kg

Push Salt Spreader 45-0548

This large 56kg/130lb capacity hopper is ideal for covering approx. 25,000 sq.ft and is suitable for spreading dry and free flowing salt. The deflector helps narrow the spread when required and the flow rate can also be adjusted. The large turf tread pneumatic tyres make manoeuvring the spreader an easy task.



Push Salt Spreader 45-0548	
Hopper Capacity	56kg / 130lbs
Hopper Construction	Polypropylene
Spreading Width	Up to 3.6m / 12'
Coverage Per Fill (Max.)	2325m ² / 25,000 sq.ft. (Approx.)
Flow Rate Control	Yes
Gearing	Fully Enclosed
Axle	Steel
Wheels	255mm x 100mm / 10" x 4" - Pneumatic Tyres
Ideal for Spreading	Dry and free flowing salt

Tow Broadcast Spreader 45-0527

The towed broadcast spreader will spread everything from fertiliser to seed and ice melt. It features a durable Polypropylene hopper, coated components and long lasting stainless steel closure plates which resist corrosion. The positive over-centre flow adjustment ensures accurate calibration.

With an 50kg (110lb) capacity, it is suitable for areas around 17,500 square feet or around one third of an acre. It has a spread width of 8' - 10' and acetal gear drive. The axle is 1/2" in diameter and it has 10" x 4" pneumatic tyres for smooth transport. Fitted with a universal hitch pin it can be towed behind all makes of lawn tractor.



Tow Broadcast Spreader 45-0527	
Towing Mechanism	Hitchpin and Hole
Hopper Capacity	110lbs / 50kg
Hopper Construction	Polypropylene
Flow Rate Control	Yes
Gearing	Fully Enclosed
Axle	13mm / 0.5"
Wheels	250mm x 100mm / 10" x 4" - with Pneumatic Tyres
Ideal for Spreading	Seeds, Granular Herbicides, Granular Fertilisers, Pellet Fertilisers
Also Suitable for Spreading	Ice Melt
Weight	8.2kg

Tow Broadcast Spreader 45-0463

The spreader is highly durable, with its fully-enclosed commercial-grade gearbox; tubular steel frame and rust-free Polypropylene hopper all combining to ensure you'll get years of service. With professional style easy-set controls for precise application and a large 130lb / 56kg hopper capacity it's perfect for areas of approx. 25,000 sq.ft

This model also features large-sized pneumatic tyres for enhanced manoeuvrability and improved traction on difficult ground; and it comes with a universal hitch-pin, so it can be used with any lawn-tractor.



Tow Broadcast Spreader 45-0463	
Towing Mechanism	Hitchpin and Hole
Hopper Capacity	56kg / 130lbs
Hopper Construction	Polypropylene
Spreading Width	Up to 3.6m / 12'
Coverage Per Fill (Max.)	Up to 2325m ² / 25,000 sq.ft. (Approx.)
Flow Rate Control	Yes - Lever
Gearing	Commercial-Duty
Axle	Steel
Wheels	255mm x 100mm / 10" x 4" - Pneumatic Tyres
Ideal for Spreading	Seeds
Also Suitable for Spreading	Ice Melt
Weight	15kg

ATV Spreader 45-0329

This towed broadcast spreader offers robust build-quality and premium components – its steel gearing, rust-resistant hopper and spread-plate and ball-bearing mounted wheels all work to ensure it will stand-up to season after season of intensive use.

Other key features include large pneumatic tyres, that provide plenty of grip without damaging the lawn surface; and a raised on/off control, which can be easily accessed from the driver's seat of your ATV.



ATV Spreader 45-0329	
Hopper Capacity	79kg / 175lbs
Hopper Construction	Polypropylene
Spreading Width	3.6m / 12ft.
Coverage Per Fill (Max.)	Up to 3715m ² / 40,000 sq.ft.
Flow Rate Control	Adjustable from ATV Seat
Gearing	Heavy-Duty Steel
Axle	Steel
Wheels	380mm x 150mm / 15" x 6"
Ideal for Spreading	Seeds, Granular Fertilisers, Pellet Fertilisers
Also Suitable for Spreading	Granular Herbicides, Rock Salt

Tow Drop Spreader 45-0288

A practical and convenient way to apply grass-seeds, granular fertilisers and herbicides over very large-areas. The distribution of spread-medium is kept within the area between the wheels, so wastage is virtually eliminated and you won't end-up applying material to areas where it's not required.

The large 175lb hopper makes it possible to cover a huge 40,000-square-feet on one hopper's worth of spread-medium. It has a 42" controlled spread-width.

It is built to last, with its rust-proof Polypropylene hopper and galvanised-steel spreader both contribute to a long product-life. Wide, large-diameter tyres ensure you won't damage the turf when turning, while also aiding manoeuvrability and traction.



Tow Drop Spreader 45-0288	
Towing Mechanism	Hitchpin and Hole
Hopper Capacity	77 Litres / 17 Gallons / 79kg / 175lbs
Hopper Construction	Polypropylene
Spreading Width	105cm
Coverage Per Fill (Max.)	Up to 3715m ² / 40,000 sq.ft. (Approx.)
Flow Rate Control	Lever - Adjustable from Driving-Seat
Axle	Steel
Wheels	with Pneumatic Tyres
Ideal for Spreading	Seeds, Granular Herbicides, Granular Fertilisers
Also Suitable for Spreading	Ice Melt
Weight	21kg

Push Ice Melt Spreader 45-0575

This spreader is the perfect size for pavements and smaller applications. With a welded steel tubular frame and a rustproof Polypropylene hopper, this spreader will stand up to a long product-life. The direct rod control opens the slide gate with precision for reliable coverage.



Push Ice Melt Spreader 45-0575	
Hopper Capacity	38kg / 85lbs
Hopper Construction	Polypropylene
Flow Rate Control	Yes
Handlebar-Mounted	Lever
Wheels	255mm x 100mm / 10" x 4" with Pneumatic Tyres
Ideal for Spreading	Ice Melt

WHY USE A SWEEPER?

Using a lawn sweeper to clear away leaves, grass clippings and garden debris is quicker and easier on you and your lawn than using a rake.

Push Lawn Sweeper 45-0218

Thanks to its infinitely-variable sweep-height, this push sweeper can be set-up to suit the surface – the brushes can be raised when working on gravel drives and lawns; and lowered for more brushing power on hard surfaces. It comes with a very large-capacity 200-litre debris-catcher, so you'll be able to get plenty done between each emptying-break (the debris-bag is collapsible for more compact storage). This model also features 10" x 1.75" semi-pneumatic tyres, a steel handle, 4 replaceable brushes and a working width of 26" / 66cm. It will clear debris 50% faster than a garden rake.



Push Lawn Sweeper 45-0218	
Sweeping Width	66cm / 26"
Brush Diameter	25cm / 10"
Hopper Capacity	6.2 cu. ft
Height Adjustment	Yes
Wheels	25 cm x 4cm / 10" x 1.75"
Surface Types	Lawns and Hard Surfaces

Tow Smart Sweeper 45-0492

This sweeper is a fast and efficient performer over very large areas – up to 8000m². It's supplied with a huge debris-bag (25 cu. ft.), which keeps emptying-stops to a minimum and can be collapsed to save space in the storage area. The bag can be emptied from the seat of your tractor. Another key benefit is its offset hitch, which allows you to simultaneously cut and sweep, while also making it easier to work alongside obstacles. Flexibility of use is further enhanced thanks to an adjustable brush-height, which is quick-and-easy to set using a single button.



Tow Smart Sweeper 45-0492	
Towing Mechanism	Hitchpin and Hole
Sweeping Width	112cm / 44"
Brush Diameter	25cm / 10"
Hopper Capacity	710 Litres / 156 Gallons
Height Adjustment	Yes
Wheels	30.5cm x 7.6cm / 12" x 3"
Surface Types	Lawns and Hard Surfaces
Suitable for Areas Up To	8000 m2

Tow Lawn Sweeper 45-0320

With a sweeper width of 42" / 107cm this tow lawn sweeper will clear debris quickly. The unique design provides more traction on the sweeper wheels for greater debris pick up. The stamped steel housing provides durability to withstand season after season of use.



Tow Lawn Sweeper 45-0320	
Towing Mechanism	Hitchpin and Hole
Sweeping Width	107cm / 42"
Hopper Capacity	340 Litres
Height Adjustment	Yes
Housing	Stamped Steel
Wheels	28cm x 6.3cm / 11" x 2.5" semi-pneumatic
Surface Types	Lawns and Hard Surfaces

Tow Lawn Sweeper 45-0546

Agri-Fab's largest towed sweeper will enable you to remove grass-clippings, pine-cones, twigs, leaves and other debris from large lawns and lengthy driveways quickly and easily. It combines a massive 708-litre debris-bag with an extra-substantial 132cm working-width. It runs on high-traction semi-pneumatic tyres that ensures effective operation in typically damp British conditions.

Thanks to its high-torque gearing and heavy-duty adjustable brushes, it guarantees a comprehensive pick-up whatever the surface- or debris-type. Bag dumping from your lawn tractor seat makes life easier for you. A rugged stamped-steel housing provides robust impact-resistance and means you'll get season after season of great performance from your lawn sweeper.



Tow Lawn Sweeper 45-0546	
Towing Mechanism	Hitchpin and Hole
Sweeping Width	132cm / 4.2ft.
Brush Diameter	30.5cm / 52"
Hopper Capacity	708 Litres
Height Adjustment	Yes
Housing	Stamped Steel
Wheels	28cm x 6.3cm / 11" x 2.5" semi-pneumatic
Surface Types	Lawns and Hard Surfaces
Suitable for Areas Up To	10,000 m2

WHY USE A ROLLER?

Tow behind rollers are ideal whether you're looking to bed-in freshly laid turf, level-out mole hills, flatten frost-heaves or pack-down newly sown seed.

Tow Roller 45-0268

This tow roller weighs an impressive 400lbs when fully water-ballasted, and just 47lbs when empty, making it easy to move to and from the shed or garage and suitable for levelling and sod packing. It's supplied with a fill-plug that's quick and easy to remove; and a universal link-pin, for linking up to your lawn tractor. The Polypropylene construction makes for rust proof durability. Rounded roller edges prevent damage to the lawn surface.

Tow Roller 45-0268	
Working Width	92cm / 36"
Drum Diameter	46cm / 18"
Drum Material	Polypropylene
Fill Plug	Yes
Weight with Water	181kg / 400lbs
Weight Empty	21kg / 46.3lbs



Push / Tow Roller 45-0267

The Push / Tow Lawn & Garden Roller weighs just 40lbs when unballasted (251lbs when the drum is full of water), making it easy to transport and store. It comes with a removable fill-plug that doesn't require tools for removal; and a universal link-pin, for linking up to your lawn tractor. The Polypropylene construction makes for rust proof durability. Rounded roller edges prevent damage to the lawn surface.



Push / Tow Roller 45-0267	
Working Width	60cm / 24"
Drum Diameter	46cm / 18"
Drum Material	Polypropylene
Fill Plug	Yes
Weight with Water	114kg / 251lbs
Weight Empty	18kg / 40lbs

Tow Roller 45-0269

This wide tow roller is equipped with a rust-resistant Polypropylene-roller that's reinforced with a centre baffle to prevent flexing on rough ground. The roller's rounded edges ensure the surface won't be damaged and the fill-plug can be quickly fitted and removed without using tools. As with all Agri-Fab lawn rollers, this model comes with a universal hitch-pin, for linking up to your lawn tractor. It weighs less than 60lbs without water for easy storage and transport and has a wide working width of 122cm / 48".



Tow Roller 45-0269	
Working Width	122cm / 48"
Drum Diameter	46cm / 18"
Drum Material	Polypropylene
Fill Plug	Yes
Weight with Water	250kg / 550lbs
Weight Empty	27kg / 59lbs

Steel Lawn Roller 45-0216

With a welded seam steel construction for strength and durability this wide lawn roller has a large drum capacity of 910lbs/412kg. It also comes with a scraper bar to prevent clumps of soil from being compacted on the roller drum and a universal hitch-pin for linking up with your lawn tractor.



Steel Lawn Roller 45-0216	
Working Width	122cm / 48"
Drum Diameter	60cm / 24"
Drum Material	Steel
Fill Plug	Yes
Weight with Water	412kg / 910lbs
Weight Empty	52kg / 114lbs

WHY USE A SPRAYER?

Liquid fertilisers, herbicides and pesticides are convenient and effective for large lawn applications. Agri-Fab sprayers are available in four sizes: 15-gallon, 25-gallon, 45-gallon and 60-gallon. Both models include a hand wand for targeted spraying around trees and bushes, smooth rolling wheels for easy manoeuvrability and are compatible with ride-on lawn mowers from any manufacturer.

Tow Sprayer 45-0292

This sprayer is compact enough to fit through narrow shed doors and gateways, but the 203cm / 80" spraying width allows for the fast coverage and it offers a very low centre-of-gravity for stability during use. Its heavy-duty Polypropylene tank will not corrode and has a large 15-gallon capacity. Markings on the tank aid the correct water/chemical mixing; and a drain makes it easy to flush-out. The Agri-Fab 45-0292 Pro Towed Sprayer features a long-lasting and efficient 12v pump that will give you years of problem-free service with wiring to connect it to your lawn tractor's battery. A handy on/off control stops the battery draining when the sprayer is connected but not in use.



Tow Sprayer 45-0292	
Towing Mechanism	Hitchpin and Hole
Tank Capacity	68 Litres / 15 Gallons
Spray Width	Up to 203cm / 80"
Spray Pressure	40psi
Flow Rate	6.3 Litres / 1.8 Gallons per Minute
Coverage Per Fill (Max.)	1400m ² / 15,000 sq. ft. (approx.)
Spray Lance	Yes - with 4.5m / 14.5ft. Hose
Pump	SHURflo®
Axle Diameter	13mm / 0.5"
Wheels	250mm x 100mm / 10" x 4" - Solid Tyres
Weight	20kg

Tow Sprayer 45-0293

A heavy-duty, commercial-grade unit, this sprayer features a corrosion- and weather-proof Polypropylene tank with a large capacity of 25 gallons, allowing you to treat large areas quickly with its 203cm / 80" spray width. The tank has level-markers for the accurate mixing of chemicals and water; and there's a drain for easy flushing. Thanks to its sturdy 3/4-inch axle and extra-large 14 x 4 pneumatic tyres, the Agri-Fab 45-0293 will easily handle rough terrain. The inclusion of ample wiring ensures you'll have no trouble hooking it up to your tractor battery. A handy on/off control stops the battery draining when the sprayer is connected but not in use.



Tow Sprayer 45-0293	
Towing Mechanism	Hitchpin and Hole
Tank Capacity	114 Litres / 25 Gallons
Spray Width	Up to 205cm / 80"
Spray Pressure	70psi
Flow Rate	6.3 Litres / 1.4 Gallons per Minute
Coverage Per Fill (Max.)	3230m ² / 35,000 sq.ft. (approx.)
Spray Lance	Yes - with 4.5m Hose
Pump	SHURflo®
Axle Diameter	20mm
Wheels	355mm x 100mm / 14" x 4"
Weight	22kg

Tow Sprayer 45-0589

A heavy-duty, commercial-grade unit, this sprayer features a corrosion- and weather-proof Polypropylene tank with a large capacity of 45 gallons, allowing you to treat large areas quickly with its 228cm / 90" spray width. The tank has level-markers for the accurate mixing of chemicals and water; and there's a drain for easy flushing. The inclusion of ample wiring ensures you'll have no trouble hooking it up to your tractor battery. A handy on/off control stops the battery draining when the sprayer is connected but not in use.



Tow Sprayer 45-0589	
Towing Mechanism	Hitchpin and Hole
Tank Capacity	205 Litres / 45 Gallons
Spray Width	Up to 228cm / 90"
Spray Pressure	100psi
Spray Lance	Yes - with 5.8m / 19ft. Hose
Pump	Remco 2.2 GPM

Tow Sprayer 45-0590

A heavy-duty, commercial-grade unit, this sprayer features a corrosion- and weather-proof Polypropylene tank with a large capacity of 60 gallons, allowing you to treat large areas quickly. The premium pistol grip spray gun, designed for single handed control lets you spray from a fine mist to heavy droplets. The tank has level-markers for the accurate mixing of chemicals and water; and there's a drain for easy flushing. The inclusion of ample wiring ensures you'll have no trouble hooking it up to your tractor battery. A handy on/off control stops the battery draining when the sprayer is connected but not in use.



Tow Sprayer 45-0590	
Towing Mechanism	Hitchpin and Hole
Tank Capacity	273 Litres / 60 Gallons
Spray Width	Up to 228cm / 90"
Spray Pressure	100psi
Spray Lance	Yes - with 5.8m / 19ft. Hose
Pump	Remco 4 GPM

Wireless Remote Control Kit 45-0580

This 12V / 15amps wireless remote control kit comes with 2 remote fobs and is compatible with any Agrifab electric sprayer that has a 2 wire moulded connector and does not exceed 12V / 15amps, so you can control your sprayer with ease.



WHY USE A TRAILER?

All Agri-Fab trailers are built to last and made to efficiently and easily carry the load. They are practical and sturdy with pneumatic tyres for easy manoeuvrability on any surface. All the trailers are supplied with a universal hitch-pin, compatible with all makes of ride-on mowers and garden tractors.

ATV Swivel Trailer 45-0579

The swivel feature on this trailer, up to 100°, and quick release lever allow for easy emptying exactly where you want it. The trailer also tips up to a 56° angle. The all terrain pneumatic tyres allow for easy manoeuvrability of the 1000lb large load capacity over the roughest ground. The trailer is supplied with a universal hitch pin which can be attached to most lawn tractors.



ATV Swivel Trailer 45-0579	
Bed Design	Polypropylene
Tipping	Yes
Tipping Mechanism	Latch system
Dump Angle	56°
Frame	1" square tubing
Tyres	Pneumatic
Wheel Size	18" x 8.5"
Dimensions	L: 208cm x W: 124cm x H: 84cm

Tow Utility Dump Trailer 45-0303

With its large load-capacity (159kg) and high-sided design, the Agri-Fab 45-0303 is ideal for the transportation of heavy and/or bulky loads around the garden. The single lever release dump mechanism and removable tailgate make for easy unloading.

Built to give year upon year of unflinching service, it's equipped with a heavy-duty steel tipper-bed that has a rust-resistant powder-coated paint finish, a robust 5/8" axle and a pair of large-diameter pneumatic tyres for easier turning on difficult terrain and a smooth ride generally.

Its wide stance and low centre-of-gravity makes it stable on rough ground. The universal pin means it can be attached to any lawn tractor.



Tow Utility Dump Trailer 45-0303	
Load Capacity	159kg / 350lbs
Body Material	Steel with Powder-Coated Finish
Tipping Mechanism	Yes
Chassis	Dichromate Steel
Axle Diameter	5/8"
Wheels	330mm x 100mm / 13" x 4"
Dimensions	L: 124cm x W: 82cm x H: 30cm / L: 49" x W: 32" x H: 12"
Weight	30kg / 68lbs

Steel Tipping Trailer 45-0101

The Agri-Fab 45-0101 Steel Tipping Trailer is supplied with a universal hitch-pin, so it's compatible with all makes of lawn tractors. With a removable tailgate and single lever release dump mechanism for easier tipping and with a set of 16" x 4" ribbed pneumatic tyres for a smooth ride and a 5/8" diameter axle for strong support. Additional benefits include a scratch-resistant, powder-coated finish for longevity; and grease nipples, which make it easy to keep the wheel-bearings lubricated.



Steel Tipping Trailer 45-0101	
Load Capacity	340kg / 750lbs
Load Volume	3.6m ³
Dimensions of Body	L: 124.5cm x W: 82.5cm x H: 30.5cm / L: 49" x W: 32" x H: 12"
Body Material	Steel with Powder-Coated Finish
Tipping Mechanism	Yes
Chassis	Steel
Axle Diameter	15cm
Wheels	360mm x 100mm / 14" x 4"
Dimensions	L: 178cm x W: 84cm x H: 74cm / L: 70" x W: 33" x H: 29"
Weight	46kg / 102lbs

Tow Trailer 45-0533

This tipping trailer has a large 650lbs / 295kg load capacity so you can unload and dump heavy materials in one easy trailer motion using the foot pedal. The durable coating on this trailer makes cleaning up a breeze. With a quick and easy assembly, you'll be set up in no time.



Tow Trailer 45-0533	
Load Capacity	295kg / 650lb / 10.cu.ft
Construction	Polypropylene
Tipping	Yes
Tipping Mechanism	Foot pedal release
Tyres	Pneumatic
Wheel Size	16" x 4"

Utility Polypropylene Trailer 45-0552

The 45-0552 towed garden cart has a considerable 700lb / 12 cubic foot heaped load capacity and is supplied with a universal hitch pin which can be attached to most lawn tractors.

The robust bed sits on a heavy-duty welded frame which has 1" square tubing, whilst the pneumatic turf tread tyres roll smoothly over uneven ground.

The Agri-Fab 45-0552 has a 12" ground clearance and features a latch system to easily dump the bed contents. Not only does the trailer tip to a 52 degree angle, the cart also swivels up to 110 degrees so you can empty the load exactly where you want it.



Utility Polypropylene Trailer 45-0552	
Bed Design	Polypropylene
Tipping	Yes
Tipping Mechanism	Latch system
Dump Angle	52°
Frame	1" square tubing
Tyres	Pneumatic
Wheel Size	15" x 6"
Dimensions	L: 167.1cm x W: 88.6cm x H: 68.3cm

Utility Polypropylene Swivel Trailer 45-0553

The 45-0553 towed garden cart has a substantial 1000lb / 18 cubic foot heaped load capacity and is supplied with a universal hitch pin which can be attached to most tractor drawbars.

The robust bed sits on a heavy-duty welded frame which has 1" square tubing, whilst the large 16" pneumatic turf tread tyres with powdered metal bearings allow for easy manoeuvrability over rough terrain.

The Agri-Fab 45-0553 features a latch system to easily dump the bed contents. Not only does the trailer tip at a 52 degree dump angle, the cart also swivels up to 110 degrees so you can empty the load exactly where you want it.



Utility Polypropylene Swivel Trailer 45-0553	
Bed Design	Polypropylene
Tipping	Yes
Tipping Mechanism	Latch system
Dump Angle	52°
Frame	1" square tubing
Tow Hitch	Clevis
Tyres	Pneumatic
Wheel Size	16.0" x 6.5"
Dimensions	L: 189.4cm x W: 105.5cm x H: 81cm

SCARIFIERS

WHY SCARIFY?

Twice a year - ideally a dry day in spring or autumn - you should free your lawn from moss so it can breathe again. The moss layer is a breeding ground for fungi, it binds moisture and inhibits powerful root growth of your lawn. Lawnflite has a selection of scarifiers, which will fulfil your needs.

ELECTRIC SCARIFIER

The powerful electric scarifier is lightweight and efficient. An ideal solution for small and medium sized lawns, it comes with a catcher bag and is designed for intuitive handling. The fixed tines take up moss and thatch with ease leaving a healthy lawn ready for growth.

PETROL SCARIFIERS

With our petrol scarifiers you have a machine with 15 or 16 blades. The working depth can be selected by adjusting a lever mounted on the handle, ensuring you select the correct setting for light scarification, or heavier verticutter applications without requiring the use of tools.

Fixed tines made of special hardened steel are effective at scarifying while the large rear mounted collector catches the raked-out material, making this a one pass operation.

MODELS AVAILABLE



Model	SMART 30VE
Working width	30 cm / 12"
Engine	1,200 W / 230 V electric motor
Deck material	Polypropylene
Tines	10 double, 145 mm diameter
Tine adjustment	0 to -12 mm
Tine shaft depth adjustment	5 positions, central
Deflector shaft	Standard
Grass bag	35 ltr
Wheels (f/r)	200 mm / 110 mm
Handle	Straight, foldable
Cable guide	Standard
Measurements (approx.)	L89 / W 58 / H 100 cm
Weight (approx.)	11 kg
LpA/LwA/LwAg (dB)	86 / 97 / 99

KEY BENEFITS

- 1 Scarifier shaft with fixed double tines for efficient results
- 2 Additional dethatcher shaft included
- 3 Catcher bag included
- 4 Central tine adjustment
- 5 Fully foldable ergo-handle
- 6 Remote transport position lever



MODELS AVAILABLE



Model	OPTIMA 38VO
Working width	38 cm / 15"
Engine	MTD ThorX 55H / 179 cc
Rated power (kW / min ⁻¹)	3.0 / 3,500
Deck material	Steel
Tines	16, 190 mm diameter
Tine adjustment	0 to -15 mm
Tine shaft depth adjustment	6 positions, central
Deflector / Aerator shaft	Standard
Grass catcher	50 ltr
Wheels (f/r)	200 mm / 200 mm
Handle	ErgoHandle, fully foldable
Measurements (approx.)	L34 / W 58 / H 114 cm
Weight (approx.)	39 kg
LpA/LwA/LwAg (dB)	87 / 98 / 100

Both electric and petrol models come standard with scarifier and aerator shaft.



Model	OPTIMA 35VO
Working width	35 cm / 14"
Engine	MTD ThorX 35H / 123 cc
Rated power (kW / min ⁻¹)	2.3 / 3,500
Deck material	Steel
Tines	15, 190 mm diameter
Tine adjustment	0 to -15 mm
Tine shaft depth adjustment	6 positions, central
Deflector / Aerator shaft	Standard
Grass bag	45 ltr
Wheels (f/r)	200 mm / 200 mm
Handle	ErgoHandle, fully foldable
Measurements (approx.)	L34 / W 58 / H 114 cm
Weight (approx.)	37 kg
LpA/LwA/LwAg (dB)	86 / 98 / 100

SCARIFIER ACCESSORIES	CODE
BLADE SHAFT FOR 35CM SCARIFIER	196-282-600
BLADE SHAFT FOR 38CM SCARIFIER	196-283-600
SPRING SHAFT FOR 30CM SCARIFIER	196-284-600
SPRING SHAFT FOR 34/37CM SCARIFIER	196-285-600
SPRING SHAFT FOR 35/38CM SCARIFIER	196-286-600

2 YEARS WARRANTY*

*2 years for domestic providing the machine is serviced by the supplying dealer.



WHEELED TRIMMER

When the mowing gets rough, you need a machine that meets the tough demands of rough grass where unknown debris may be lurking.

The HWLT wheeled trimmer with its dual line cutting system, large wheels, adjustable handle system, will wade through the rough areas.

Model	HWLT
Engine	Lawnflite OHV 160 cc, 5.5hp
Cutting width	56 cm / 22"
Cutting height	3.8 cm / 1.5" - 7.6 cm / 13"
Wheel	35 cm / 14"
Handle	Adjustable
Clutch system	Standard
Weight (approx.)	36 kg

KEY BENEFITS

- 1 Powerful Lawnflite engine
- 2 Dual line system
- 3 Adjustable handle
- 4 Large wheels
- 5 Blade engagement safety control



LOG SPLITTERS

Log splitters offer a safe and effort-free alternative to chopping up wood with a traditional axe.

Lawnflite offers a range of high quality electric logsplitters. For use in sensitive areas where noise will cause a problem we have electric models with a splitting force of up to 8 tonne. All Lawnflite log splitters are fitted with wheels for transportation and are operated by a 2 handed control system to ensure safe working practice.

Please note - if splitting particularly hard wood, the maximum log size stated may not be applicable.

The LS52200EH-KIT and LS72300EH-kit must be used with a stand due to new safety legislation. The stand comes as standard with both machines.

KEY BENEFITS

- Electric log splitters are quiet and effective
- Splitting force from 5 to 8 tonnes
- Two handed control systems ensure a safe working practice
- Wheels for easy transportation
- Comfortable hand-grips for easier working





ELECTRIC

Model	LS52200EH-KIT	LS72300EH-KIT	LS83000EV
Engine	230 volt 2200 watt	230 volt 2200 watt	230 volt 3000 watt
Splitting force	5 tonne	7 tonne	8 tonne
Log diameter	25 cm / 10"	25 cm / 10"	30 cm / 12"
Log length	52 cm / 20"	52 cm / 20"	55 cm / 21"
Weight	55 kg	60 kg	110kg
Stand	Standard	Standard	N/A
Wheels	Standard	Standard	Standard

ELECTRIC CHAINSAW

Our high-performance electric chainsaw is ideal for all types of sawing work around the garden which can be done within cord length. Alternatively this versatile machine can be run from a suitable generator. This includes tree trimming and the cutting-down of fruit trees, the building of an arbour in the garden, cutting firewood as well as small wood and branches.

- 1 Low vibration handles
- 2 Lightweight ergonomic design and well balanced construction
- 3 Suitable for a variety of applications from trimming and cutting firewood through to general purpose logging and tree felling



ELECTRIC

Model	ECS180035
Engine	1800 Watt electric motor
Voltage	230 Volt / 50 Hz
Bar length	35 cm / 14"
Bar manufacturer	Oregon
Chain	10 mm / 3/8" LP
Chain manufacturer	Oregon
Chain tensioner	Front
Chain oil tank	0.09 ltr
Automatic chain lubrication	Standard
Cutter guard	Standard
Weight (approx.)	4.8 kg
Vibration value body	3.0 m/s ²
LpA/LwA/LwAg (dB)	84 / 104 / 107

Mantis



MANTIS – EXPECT BIG THINGS

Mantis tillers and cultivators are designed for performance and power. Mantis introduced the first small tiller nearly 40 years ago and remain at the forefront in providing big results from a mini tiller. The range will help you grow great gardens and keep lawns looking the best. Trusted by over 2 million gardeners they are the best selling small tillers ever.

A full range of attachments including border edge, plough, aerator and planter furrower are also available.

WHY CHOOSE A MANTIS TILLER?

THE LIGHTEST AND MOST POWERFUL TILLER IN THE WORLD

Small but powerful, the Mantis tiller will surprise you with its performance. Thanks to its unique curved tines, it defies roots and stones, reduces clods and turns the soil to create great planting conditions.

FAST AND EASY TO USE

With the Mantis tiller you will save a lot of time in the garden. Plus, it's easy to start and with all of the controls at your fingertips, is easy to use.

EASY TO HANDLE AND POWERFUL

That's the magic of a Mantis. A compact size that works in the tightest spaces, a light weight tiller that is easy on your arms and back and a 40-year reputation for quality and efficiency.

VERSATILE


A Mantis tiller is several tools in one: it digs, hoes and weeds. With the optional attachments, it also breaks up the ground, digs furrows and holes, helps takes care of the lawn, edges borders and paths.

DESIGNED TO LAST

A Mantis is a long-term investment.

KEY BENEFITS

- 1 WORM GEAR TRANSMISSION**
Produces smooth, reliable power delivery with no mechanical efficiency loss
- 2 TINE GEOMETRY**
Specially designed tines maximise digging power, creating the ideal soil for root and plant health
- 3 ENGINE-OVER-TINE DESIGN**
Optimises weight placement for better digging power and less stress on the operator




1

MODELS AVAILABLE

POWERED BY HONDA

Model	7265 DELUXE
Tilling width	23 cm / 9"
Engine	Honda 4 cycle, 25 cc
Speed	Variable throttle
Handle	Sure grip
Kick stand	Included
Weight (approx.)	11 kg
Engine guard and handle	Standard



Model	7263 CLASSIC
Tilling width	23 cm / 9"
Engine	Honda 4 cycle, 25 cc
Speed	Variable throttle
Handle	Sure grip
Kick stand	Included
Weight (approx.)	11 kg



MODELS AVAILABLE

Model	7252 ELECTRIC TILLER
Tiller width	23cm / 9"
Motor	230V electric
Start	Push button
Speed	3 speed throttle
Emissions	ECO-friendly
Weight (approx.)	9.5 kg
Kickstand	Included



Model	3450 ELECTRIC CULTIVATOR
Tiller width	31 cm / 12"
Motor	1000w electric
Start	Push button
Speed	2 speed
Emissions	ECO-friendly
Weight (approx.)	11 kg



MANTIS TILLER ATTACHMENTS

PLOUGH ATTACHMENT (3333)

The plough attachment makes deeper furrows and higher mounds. This attachment helps you create ideal deep planted growing conditions for your potatoes, leeks, etc. Like a plough, set the furrower to the required depth, allow the tiller to move forward and the plough blade creates a wide furrow. This action can also be used to earth up around rows of potato plants.

The plough blade can be adjusted to any of the 5 height settings very easily, by removing a clevis pin, moving the blade and then re-inserting the pin. The depth of the furrows can therefore be easily controlled, from shallow rows to deep furrows. It is attached to the Mantis tiller in addition to the standard tiller tines and will plough the earth up to 18 -20" / 45-50cm wide.



AERATOR ATTACHMENT (4222)

The Mantis lawn aerator cuts thousands of tiny slits in your lawn, encouraging beneficial micro-organisms in the soil. It is the single most important measure for a healthy, green lawn. The lawn aerator allows oxygen, nutrients and water to penetrate to the soil below. The grass roots can grow down deeper, making your lawn more resistant to hot, dry spells. Not suitable for the Mantis Deluxe XP Tiller.



MANTIS TILLER ATTACHMENTS

THESE ATTACHMENTS ARE FOR THE MANTIS TILLERS ONLY.

BORDER EDGE ATTACHMENT (3222)

The Mantis border edger attachment makes it easy to beautify your property with sharp, clean edges around paths, flower beds and bushes. The wheel and hardened spring-steel blade attaches easily to your tiller. The Mantis border edger cuts neat, crisp edges to the turf where your flower beds meet the lawn. Can be used with the wheel kit (9222). Not suitable for the Mantis Deluxe XP Tiller.



DETHATCHER ATTACHMENT (5222)

This dethatcher quickly removes weeds, dead grass, moss, and the thatch that can choke your lawn. The 60 spring-steel picks let you dethatch a 15" / 38cm area with a single pass eliminating hours of back-breaking work. Thatch harbours insects, creates a water barrier, and prevents new grass from growing. Dethatch your lawn regularly, especially before feeding and fertilising. Not suitable for the Mantis Deluxe XP Tiller.



MANTIS TILLER ATTACHMENTS

PLANTER FURROWER ATTACHMENT (6222)

Two special tines dig deep, 6 wide furrows, perfect for tomato plants and corn, beans, potato eyes, asparagus roots, onion sets, and flower bulbs. You get drought-resistant root growth and excellent yields from root crops. Great for tilling in narrow areas. Saves time and energy in the garden.

The Mantis tiller planter attachment is also perfect for creating raised beds, cutting trenches for underground irrigation hoses, or low-voltage accent and patio lighting.



LAWN CARE ACCESSORY COMBO (7321)

The Lawn Care Accessory Combo includes a Lawn Dethatcher and a Lawn Aerator attachment. The Dethatcher quickly removes weeds, dead grass, moss, and the tan-looking built-up "thatch" that can choke your lawn. The 60 spring-steel picks let you dethatch a 15" / 38 cm swath with a single pass. Eliminate hours of back-breaking work. The Lawn Aerator cuts thousands of tiny slits in your lawn, encouraging beneficial micro-organisms in the soil. It is the single most important measure for a healthy, green lawn. Not suitable for the Mantis Deluxe XP Tiller.



CREVICE CLEANER ATTACHMENT (8222)

The Mantis crevice cleaner attachment removes dirt and debris from cracks and other hard-to-reach places, thanks to 38 tough steel bristle brushes fixed around a sturdy 3/4 wide wheel. Saves hours of time and backbreaking work! Quickly cuts through weeds, dirt, and debris. Easy to use. Fits on either axle. Comes complete with balancing wheel, a fender and a pair of protective goggles to protect your eyes from projectiles. It can be used with the optional wheel set. Not suitable for the XP Mantis Deluxe Tiller.



MANTIS TILLER ACCESSORIES

TILLER TINE SET (1622)

A pair of replacement tines for your Mantis tiller. The Exclusive and patented design of the serpentine tines can penetrate even the hardest soils – even clay – and reduce efficiently clumps of earth. Moreover, the tines are reversible for light weeding.




TINE DETANGLER (1322)

The specially shaped hook is designed for removing stones, tangled weeds and roots from around your tiller tines quickly and safely. Ergonomically shaped with a comfortable rubber grip. 11/28cm long. A useful tool to help you with your Mantis tiller.



WEED REDUCERS (1722)

The pair of weed reducers help reduce the number of stringy weeds and vines that wrap around the tine shaft of the transmission. If weeds do collect on the tine shaft, it's easier to remove them. Can be easily installed on the Mantis tiller tine shaft.



KICK STAND (4333)

A practical feature whenever you want to take a break, one quick kick of the stand and your Mantis tiller stands upright. Just tip up the kickstand when you are ready to start working again. Attaches easily to the base of the tiller handles, and flips up or down for instant use. Durable solid steel construction.



MANTIS TILLER ACCESSORIES

WHEEL KIT (9222)

The Mantis tiller wheel kit lets you have the option to roll or carry your Mantis tiller to your garden. Park your Mantis tiller in an upright position to add petrol, or store it upright when you don't have a wall to lean it against. Wheels add stability when you use the Crevice Cleaner or Border Edger attachments. Rubber wheels make the Mantis tiller easy to roll around your garden, over curbs, and up hills. Attaches to your tiller in a few minutes, wheels can be adjusted to six different heights and can be removed easily.



TILLER STORAGE RACK (811005)

The Storage Rack saves precious room in your garage, shed or cellar. Simply hang your Mantis tiller on the wall when it is not in use. A set of seven different hooks are delivered with the storage rack (screws and nuts also included). A great idea that keeps your Mantis attachments right at your fingertips. Tiller and attachments are sold separately.



MANTIS TILLER SERVICING

6 PACK OIL 1 GAL. MIX (1522)

100ml Bottles of 2-Stroke Oil (50:1 mix) for Mantis 2-stroke tillers. Mix each bottle with 5 litres of unleaded petrol to obtain the 50:1 mixture. Please note that once petrol and oil are mixed, its quality deteriorates rapidly, after about a month. That's why we recommend you mix only the required quantity each time you use the machine.



MANTIS TILLER SERVICING

HANDY ITEM KIT FOR SV4 2 STROKE ENGINE (1422)

The handy item kit contains the items you need to keep your 2-stroke petrol tiller in excellent working order. This kit is suitable for all Mantis Tillers with the red air filter cover bought before March 2003.

Contains:

- 2 bottles of 2 stroke oil
- 1 spark plug
- 2 air filter pads
- 1 tube grease
- 2 tine clips
- 1 plug spanner
- 1 gearbox gasket
- 1 fuel filter
- 1 fuel funnel

SUITABLE FOR TILLERS BOUGHT BEFORE MARCH 2003



HANDY ITEM KIT FOR GX25 4 STROKE ENGINE (3777)

Our special Handy Item Kits contain everything you'll require for the simple servicing of your Honda GX25 4-stroke petrol tiller engine. They help prevent engine damage and guarantee a smooth running of the Honda engine.

Each kit contains:

- 1 bottle of 1litre oil
- 1 spark plug
- 2 retaining clips
- 1 air filter pad
- 1 tube of gear grease
- 1 socket spanner
- 1 funnel
- 1 gearbox gasket

HANDY ITEM KIT FOR SV6 2 STROKE ENGINE (5444)

Everything you need to service your SV6 2 Stroke Engine.

Each kit includes:-

- 2 bottles of 2-stroke oil
- 1 spark plug
- 2 Air Filter pads
- 1 Tube Grease
- 2 tine clips
- 1 plug spanner
- 1 gearbox gasket
- 1 fuel funnel

The kit contains the items you need. This kit is suitable for all Mantis 2-stroke Tillers bought since March 2003. These machines have a black air filter cover.

SUITABLE FOR TILLERS BOUGHT AFTER MARCH 2003





PORTABLE COMPOSTER ROLLS DIRECT TO THE GARDEN

MAKES COMPOST IN 4 TO 6 WEEKS

The Back Porch ComposTumbler was developed for garden composting. If you have a city property or a very small garden, this little composter was designed just for you. The frame includes two wheels so you can take the compost right to your flower beds and garden areas. You can add to it each day for continuous composting.



Model	CT08001 BACK PORCH COMPOSTUMBLER
Drum capacity	140 litres
Size	37"/94cm H x 31"/79cm W x 26"/66cm D
Drum height	7"/18cm off the ground
Drum materials	Double-wall, high density Polyethylene with insulating air cell
Frame	Polyester powder-coated black steel tubing, with two wheels
Drainage	Aerator/drainage unit on the bottom
Air Circulation	Screened vents on each side
Turning	Indented grooves on drum allow grip for turning
Colour	Sage green
Assembly	Some assembly is required

MAKE COMPOST IN 3 EASY STEPS WITH A MANTIS COMPOSTUMBLER

HOW MANTIS COMPOSTERS WORK

Thanks to the Mantis ComposTumbler's unique design, it's quick and easy to create high-quality fertiliser from your kitchen and garden waste. Our composter models, designed for different household sizes, use the same technology to deliver the best results. Here's how it works.

1. COLLECT ORGANIC WASTE

Simply collect a variety of organic waste materials from your property and garden. Put them in your ComposTumbler composter, close the door, and immediately give the tumbler 5 turns.



2. TUMBLE YOUR COMPOST

Give the tumbler 5 turns every day. No heavy lifting!



3. FINISHED COMPOST IN ONLY A FEW WEEKS!

Open the door and tumble out your finished compost.



KEY BENEFITS

- HOLDS UP TO 140 LITRES OF MATERIAL** to make plenty of compost for smaller gardens and flower boxes
- TURNING GROOVES** let you grip the drum to turn it
- AERATOR/DRAINAGE UNIT** on the bottom combined with screened vents on each side allow the proper air intake and the release of excess moisture, without spilled compost
- INSULATED HIGH-DENSITY Polyethylene drum** lets you compost in cooler weather
- CONVENIENT WHEELS** let you take the compost directly to your flower beds and garden areas





GTM – WOOD CHIPPERS AND TREECARE

The GTM range of compact and powerful wood chippers are designed to offer a portable option to chipping branches and crops – perfect for tree care, landscaping, forestry and garden maintenance.

Efficient, effective and safe to operate due to their chipping system and unique drum design – a rotor with 2 blades, one counter blade and ejection through a large discharge chute. The system pulls branches up to 12 cm thick into the machine, chips them and ejects clean cut wood chips time after time. The chipped material is ideal to use as mulch or compost.

GTM Professional wood chippers and tree care – for expert gardeners and professionals.

GTS 750

Compact chipper, Powerful performance

The new GTS 750 is as compact as the GTS600, but with a greater performance due to a wider and heavier rotor system. Specially designed for semi-professionals and high demanding private users, this wood chipper can handle branches of fresh wood up to 7 cm (2.8") in diameter (dry wood: 5.5 cm / 2.2"). The chips are thrown out at a height of 77 cm, all standard wheelbarrows fit underneath.

The new GTS750 is light in weight, perfectly balanced and easy to manoeuvre with its large pneumatic wheels and double transport handles. The high handle serves to easily push the machine, whilst the low handle makes pulling the machine easy. The efficient rotor chipping system, directly mounted on the shaft, guarantees the highest possible working speed.

GTS 600

Powerful chipper for private users.

Branches with a diameter up to 5 cm (2") are easily pulled in and chipped. The GTS600 comes with double sharpened blades that last twice as long as regular blades.

The machine has several safety features including restart protection for the user and overload and overheat protection for the motor.

Compact storage mode: the hopper can be put straight up and the output chute can be stored in the hopper.

Model	MSGTS600G
Engine	196 cc Loncin
Branch diameter	5 cm / 2"
Input height	113 cm / 44"
Input dimensions	25 x 25 cm / 9.8" x 9.8"
Output height	81 cm / 32"
Output direction	Rear
Deflector	85° adjustable
Safety items	Rotor blocking system / Emergency button
Wheel diameter	26 cm / 10.2"
Wheels	Plain bearings
Cutter Drive	Direct Drive
Blades	Double sharpened blades
Dimensions (LxWxH)	125 x 57 x 133 cm / 49" x 22.5" x 52.4"
Weight	68 kg / 150 lbs



Model	MSGTS750G
Engine	270 cc Loncin G270F
Branch diameter	7 cm / 2.8"
Input height	111 cm / 44"
Input dimensions	25 x 31 cm / 10" x 12"
Output height	77 cm / 30"
Output direction	Rear
Deflector	55° adjustable
Safety items	Emergency button
Wheel diameter	26cm / 10.2"
Wheels	26cm with ball bearings
Cutter Drive	Direct Drive
Blades	Double sharpened blades
Dimensions (LxWxH)	183 x 62 x 144cm / 72" x 24" x 57"
Weight	90kg / 198 lbs

NEW



GTS 900

Extra wide input area for efficient processing.

The GTS900 chipper is a powerful machine for professional use in the field of tree maintenance, ground care and forestry. With an extra wide input area - 40 x 28cm (16 x 11") making it suitable for fast and efficient processing of branches up to 8cm (3").

The machine is equipped with a safety button that immediately stops the motor.

Model	MSGTS900G
Engine	302 cc Loncin
Branch diameter	8 cm / 3.1"
Input height	101 cm / 39.8"
Input dimensions	40 x 28 cm / 15.7" x 11"
Output height	138 cm / 54.36"
Output direction	Side
Deflector	80° adjustable
Safety items	Emergency switch
Wheel diameter	39 cm / 15.4"
Wheels	Ball bearings
Cutter Drive	Double V belts
Blades	PRO blades
Dimensions (LxWxH)	150 x 67 x 145 cm / 59.1" x 26.4" x 57.1"
Weight	140-151 kg / 309 - 333 lbs



GTS 1300

Powerful gravity-fed machine for professional use in tree maintenance, ground care and forestry.

The GTS1300 wood chipper can shred fresh cut wood with a maximum diameter of 10cm (4") and dry wood of 8cm (3"). With a maximum height of 150cm (59") and the engine sited under the hopper it is less than 80cm (32") wide making it the most compact chipper in its class.

The GTS1300 wood chipper is light and perfectly balanced so that one person can operate and move the machine safely.

Model	MSGTS1300G15
Engine	420 cc Loncin
Branch diameter	10cm / 4"
Input height	110 cm / 43.3"
Input dimensions	34 x 42 cm / 13.4" x 16.5"
Output height	155 cm / 61"
Output direction	Adjustable
Deflector	85° adjustable
Safety items	Panic bar, safety switches, rotor locking system
Wheel diameter	40 cm / 15.7"
Wheels	Ball bearings
Cutter Drive	Double V belts
Blades	PRO blades
Dimensions (LxWxH)	90 x 106 x 155 cm / 35.4" x 41.7" x 61"
Weight	210 kg / 463 lbs

GTS900 COMPO

Multifunctional chipper for branches and grass.

The GTS900C is a multifunctional chipper with two different outputs. The high output is suitable for shredding branches up to 8cm (3"). The low output is suitable for soft materials, such as grasses, hedge shavings or plant debris. The shredded material accelerates the composting process.

Model	MSGTS900COMPO
Engine	302 cc Loncin G300FA
Branch diameter	8 cm / 3.1"
Input height	101 cm / 39.8"
Input dimensions	40 x 28 cm / 15.7" x 11"
Output height	High 138cm / 54.36", Low 35cm / 13.8"
Output direction	Side - chipping / Rear - shredding
Deflector	Side - 80° adjustable / Rear - fixed
Safety items	Emergency switch
Wheel diameter	39 cm / 15.4"
Wheels	Ball bearings
Cutter Drive	Double V belts
Blades	PRO blades
Dimensions (LxWxH)	125 x 67 x 138cm / 49.2" x 26.4" x 54.3"
Weight	140-151 kg / 309 - 333 lbs



GTS1300 COMPO

Multifunctional chipper for branches and grass.

The GTS1300C wood chipper can shred fresh cut wood with a maximum diameter of 10cm (4") and dry wood of 8cm (3"). The GTS1300C is a multifunctional chipper with two different outputs. The high output is suitable for shredding branches up to 10cm (4"). The low output is suitable for soft materials, such as grasses, hedge shavings or plant debris. The shredded material accelerates the composting process.

Model	MSGTS1300COMPO
Engine	420 cc Loncin G420F
Branch diameter	10 cm / 4"
Input height	103 cm / 40.6"
Input dimensions	50 x 35cm / 19.7" x 13.8"
Output height	High 160cm / 63", Low 35cm / 13.8"
Output direction	Side - chipping / Rear - shredding
Deflector	Side - 85° adjustable / Rear - fixed
Safety items	Panic bar, safety switches, rotor locking system
Wheel diameter	40 cm / 15.7"
Wheels	Ball bearings
Cutter Drive	Double V belts
Blades	PRO blades
Dimensions (LxWxH)	203 x 77 x 160cm / 80" x 30.3" x 63"
Weight	198.5kg / 438lbs



SPARE PARTS AND ACCESSORIES

ITEM	NEW WOODEN PUSH TOOL (FOR MSGTS900COMPO)	NEW WOODEN PUSH TOOL (FOR MSGTS1300COMPO/E)	SWIVEL CHUTE (FOR MSGTS900V3 / 900CV2)	NEW SWIVEL CHUTE (FOR MSGTS1300G15)	TOW BAR ASSY (FOR MSGTS900 V2 & MSGTS1300G V4)	TOW BAR ASSY (FOR MSGTS900G & MSGTS1300G15)	NEW GRID (FOR MSGTS1300COMPO/E & MSGTS900COMPO)	HOUR COUNTER (FITS TO ALL MODELS)	BUMPER SUPPORT (FITS TO ALL MSGTS1300 MODELS)
Product code	GTSM110001000	GTSM110002000	MSGTSA030009000	GTSA070012000	GTSD070000015	GTSA070003000	GTSM033507000 & GTSM039084000	GTSE1100URCL	GTSM023015000

SPECIAL ORDER CHIPPERS

DESCRIPTION	MODEL NUMBER
GTS1300 Loncin G420FD E/S engine (Electric Start)	MSGTS1300GE15
GTS1300 On Caterpillar Tracks Loncin GTE E/S engine (Electric Start) NEW	MSGTS1300RGE15
GTS1300 Compo Loncin G420FD E/S engine Electric Start	MSGTS1300COMPOE
GTS1800 V5 GX630 V-twin Honda E/S engine wheel driven (Electric Start) NEW	MSGTS1800WD

GTS 1300RG

Powerful but compact tracked wood chipper.

The GTS1300RG wood chipper can shred fresh cut wood with a maximum diameter of 10 cm (4") and dry wood of 8 cm (3"). The GTS1300RG wood chipper is equipped with caterpillar tracks to operate on rough and hard to access terrain, suitable for gardens, parks and forestry. The new construction can easily manage steep hills up to 20° incline.

The chassis is specially lowered, making the input height only 10cm (4") higher than the GTS1300 on wheels.

Model	MSGTS1300RG15
Engine	420 cc Loncin
Branch diameter	10 cm / 4"
Input height	125 cm / 49.2"
Input dimensions	34 x 42 cm / 13.4" x 16.5"
Output height	160 cm / 63"
Output direction	Adjustable
Deflector	85° adjustable
Safety items	Panic bar, safety switches
Motion Drive	3 speed tracked
Width of tracks	18cm / 7"
Cutter Drive	Double V belts
Blades	PRO blades
Dimensions (LxWxH)	215 x 72 x 170 cm / 84.6" x 28" x 67"
Weight	345 kg / 760 lbs

GTS 1300 PTO

A robust wood chipper, suitable for coupling to a tractor.

The GTS1300PTO wood chipper is suitable for chipping fresh, green wood with a maximum diameter of 12cm / 4.7" and dry wood up to 10cm / 4" and can be coupled to a tractor up to 45hp with a 3-point attachment and power take-off. A trailer can be attached to the back of the machine; for wood chips to be blown into directly.

The GTS1300PTO meets the highest safety standards. The safety mechanism is entirely independent of the tractor and works with any tractor.

Model	MSGTS1300P
Engine	PTO
Branch diameter	12 cm / 4.4"
Input height	110 cm / 43.3"
Input dimensions	34 x 42 cm / 13.4" x 16.5"
Output height	155 cm / 61"
Output direction	Adjustable
Deflector	85° adjustable
Safety items	Panic bar, safety switches, rotor locking system
Cutter Drive	4 belt drive
Trailer hitch	Standard 50mm ball & pin hitch
Required power	Min. 15hp (11kW) / Max. 45hp (33kW)
PTO type	Cat. 1 3-point linkage
Blades	PRO blades
Dimensions (LxWxH)	90 x 106 x 155 cm / 35.4" x 41.7" x 61"
Weight	210 kg / 463 lbs



GTS 1300 WD

A self-propelled powerful wood chipper for professional use.

The GTS1300WD wood chipper can shred fresh cut wood with a maximum diameter of 10 cm (4") and dry wood of 8 cm (3").

The battery powered (2 x 12 V) self-propelled drive system has an impressive autonomy of 9.5 kms on flat paved ground and approximately 3 kms on hilly or muddy terrain. The driving system can handle slopes up to 15°.

Steering is easy thanks to the two swivelling wheels that are mounted on a swing axle so the chipper can go through rough and uneven terrain.

Model	MSGTS1300WDG15
Engine	420 cc Loncin
Branch diameter	10 cm / 4"
Input height	103 cm / 41"
Input dimensions	50 x 28 cm / 20" x 11"
Output height	163 cm / 64"
Output direction	Turnable 270°
Deflector	100° adjustable
Safety items	Rotor blocking system, panic bar, safety lever
Motion Drive	2 speed settings
Wheels	Rear 39cm. Swivel front 25cm
Cutter Drive	Double V belts
Blades	Double grinded blades (2x)
Dimensions (LxWxH)	150 x 73 x 163 cm / 59" x 29" x 64"
Weight	235 kg / 518 lbs





ELEPHANTS TRUNK HARNESS 2.2 **NEW**

The new GTM Professional Elephants Trunk Harness 2.2 will help you to trim hedges all day long without muscle strain and double your workspeed.


The comfortable harness is worn like a backpack and reduces the weight of the hedge trimmer by 3 kg (6.5 lbs). The length can be adjusted and is suitable for hedge trimmers or other handheld machines from 4.5 to 8 kg (10 - 17.5 lbs).

The aluminium tube is now fully rotatable, offering even more flexibility for you. The harness has been adapted for a better and more ergonomic fit with the adjustable straps on both the shoulders and the hips.

A clear view and an unlimited work area will help you to work quicker and with greater safety and improved accuracy.

KEY BENEFITS

- 1 Nylon ball bearings
- 2 Lightweight aluminium
- 3 Adjustable length
- 4 Tools 4.5 - 8kg
- 5 Turnable 360°
- 6 Adjustable straps
- 7 Improved ergonomic design



Model	MHH01010N 2.2
Length	Adjustable
Bearings	Nylon ball
Harness	Standard
Support	Balancer
Weight	4.5 - 8 kg / 10 - 17.5 lbs



RATTLEWEDGE

The GTM Professional Rattlewedge is a patented tool that has been developed by arborists for you – to improve the security and working conditions when you are felling trees or cutting up large pieces of wood. The Rattlewedge can be inserted into the notch made in the wood and tightened up to open up the notch, allowing you to control when and where the tree will fall. The Rattlewedge helps you control the wood without any effort, whether you are in the tree or on the ground.

Made of lightweight aluminium and weighing only 1.4 kg (3 lbs), it can be easily carried up into the tree and the weight of the tree will make the task of felling that much easier and safer.



Product Code
KSIRW0000



Classen are serious about manufacturing cutting-edge, durable and easy-to-use equipment for professional landscapers and homeowners.

The full product line incorporates features that enhance operator comfort and minimise maintenance. It's their way of taking the backache out of lawn care, so you stay productive and profitable.

AERATORS POWER STEER™ PRO TA25

Transform gruelling muscle-work into simple fatigue-free steering and comfortably move from one lawn or local authority ground to the next with the PRO TA25 Aerator.

Our PRO line offers productivity-enhancing features to help landscapers complete more projects quickly and increase profits. The PRO line's proven designs include the important extras, such as hydrostatic transmissions, anti-vibration grips and power steering.

KEY BENEFITS

- Tight hole pattern and all-tine propulsion produces more holes for the best quality of core results
- Patented split-drive technology allows power steering through the tines
- Simple controls allow operators to aerate straight, follow curves and turn left or right
- Protective chain guards help keep grass, leaves and cores out of chains and sprockets
- Removable weight and fillable water drum add weight for greater tine penetration in tough soil

Model	TA-25DE AERATOR
Engine	Honda® GX120
Aerating width	24.375"
Aerating depth	Up to 2.75"
BHole pattern	4.06" x 7"
Coverage	32,850 sq. ft. / hr
Tines	(36) 3/4" OD
Holes / ft²	6.5 per sq. ft.
Weight bar	42 lbs removable steel bar
Dimensions (HxWxL)	48.5" x 40.5" x 50"
Dry weight	362 lbs with weight (320 lbs without)

BEST SUITED FOR:
Landscapers and Turf Care Professionals
IDEAL LAWN SIZE:
Large Lawns or Local Authority



2-YEAR WARRANTY*

Engines are warrantied separately by manufacturer. *See website for terms & conditions.



AERATORS STEERABLE COMPACT TA18

The industry's most compact aerator is also the most productive.

Classen equipment is built with the professional in mind with quality components, productivity features and service and maintenance ease.

KEY BENEFITS

- Best Quality of Core®: Five rows of tines pull 15% more cores per square foot than competitive models
- Steerable tine bank enhances manoeuvrability and eases end of row turning
- Dual front drive wheels provide exceptional balance on hills
- Fold-down handle, removable weights and side lift/tie-down brackets ease transport
- Exclusive tine engagement system greatly reduces the effort required to lower and raise tines
- Honda® GX120 engine achieves the fastest speed in its class, 4.2 mph
- Easy-access drive sprocket and bail result in simple maintenance

BEST SUITED FOR:
Homeowners and Landscapers
IDEAL LAWN SIZE:
Small to moderate



2-YEAR WARRANTY*

Engines are warrantied separately by manufacturer. *See website for terms & conditions.

Model	TA18HE STEERABLE COMPACT
Engine	Honda® GX120
Aerating width	16"
Aerating depth	Up to 3"
Hole pattern	3.4" x 7"
Coverage	29,500 sq. ft. / hr
Tines	(30) 3/4" OD
Holes / ft²	6.5 per sq. ft.
Weight bar	2 x 21.5 lbs removable steel bars
Dimensions (HxWxL)	48" x 27.2" x 46"
Dry weight	257 lbs with weight (214 lbs without)



AERATORS RECIPROCATING RA21

Transform gruelling muscle-work into simple fatigue-free steering and comfortably move from one lawn or local authority ground to the next with the RA21.

The reciprocating tines of the RA21 punch clean holes in tough, hardened soil.

AERATOR COMPARISON CHART



Model	PRO TA25
Ideal lawn size	Large lawns, local authorities
Best suited for	Landscapers, lawncare professionals, local authorities and golf courses
Aerating width	24.75"
Coverage	32,850 sq. ft. / hr
Hole pattern	4" x 7"
Dry weight	164 lbs / 362 lbs

KEY BENEFITS

- Tines reciprocate at 450 revolutions per minute for exceptional coverage
- Lightweight design makes end of row turning easy
- Fold-down handle for compact transport and storage
- Lightweight, rust-resistant, two-piece hood reduces overall unit noise and allows easy access for maintenance
- Lifting and tie-down handles for easy and safe transportation
- Front and rear tyre scrapes keep tyres free from dirt and allow maximum tine penetration
- Front and rear pneumatic wheels offer better flotation on turf and easier manoeuvrability

BEST SUITED FOR:
Landscapers and Turf Care Professionals and homeowners
IDEAL LAWN SIZE:
Any size that involves straight-line aerating



Model	RA-21HE RECIPROCATING
Engine	Honda® GX160
Aerating width	16.25"
Aerating depth	Up to 2.75"
Hole pattern	2.6" x 7.5"
Coverage	26,000 sq. ft. / hr
Tines	(8) 5/8" OD
Holes / ft²	10 per sq. ft.
Weight bar	N/A
Dimensions (HxWxL)	39" x 31.5" x 64"
Dry weight	261 lbs



Model	TA18
Ideal lawn size	Any
Best suited for	Landscapers
Aerating width	16"
Coverage	29,500 sq. ft. / hr
Hole pattern	3.4" x 7"
Dry weight	116 lbs / 257 lbs



Model	RA21
Ideal lawn size	Any size involving straight-line aerating
Best suited for	Landscapers and homeowners
Aerating width	21"
Coverage	26,000 sq. ft. / hr
Hole pattern	2.6" x 7.5"
Dry weight	118 lbs / 261 lbs

2-YEAR WARRANTY*

Engines are warrantied separately by manufacturer. *See website for terms & conditions.

2-YEAR WARRANTY*

Engines are warrantied separately by manufacturer. *See website for terms & conditions.



TURF OVERSEEDER WALK-BEHIND TS20

Seed new lawn, overseed an existing lawn or easily convert the TS20 into a turf rake or vertical cutter for additional turf care projects. The blades feature a cutting edge on both ends, which doubles the blade life.

BEST SUITED FOR:
Homeowners and Landscapers
IDEAL LAWN SIZE:
Small to moderate



KEY BENEFITS

- **INDUSTRY'S TIGHTEST BLADE PLACEMENT** allows for better germination by planting 13 rows per 20" swath
- **FOLDING HANDLE** means easy transportation
- **5-POSITION HEIGHT ADJUSTMENT** gives optimal depth control
- **EASY TO REMOVE SEED BOX** allows for simple cleaning
- **TYRE SCRAPES** reduce soil build-up
- **26 HEAT-TREATED MULTI-PURPOSE BLADES** re-reversible and sharpened on all four edges for double the blade life
- **CONVERTS TO A TURF RAKE** or vertical cutter in minutes with optional blade assemblies

Model	TS-20HE
Engine	Honda® GX160
Seeding width	20"
Seeding blade	Double edged, heat treated blades, 1.5" spacing
Seedbox capacity	30 lbs
Dimensions (HxWxL)	39.5" x 27" x 51"
Dimensions (handle folded)	29.5" x 27" x 30.5"
Dry weight	150 lbs



SOD CUTTER HYDRO-DRIVE PRO HSC18

Maximise productivity for any application big or small with the PRO HSC18 Sod Cutter. Whether you are repositioning or relocating sod or expanding landscaping areas, the hydrostatic drive delivers high productivity with smooth power in both forward and reverse and the industry's fastest transport speed.

Our PRO line offers productivity-enhancing features to help landscapers complete more projects quickly and increase profits. The PRO line's proven design includes the important extras, such as hydrostatic transmission, anti-vibration grips and power steering.

KEY BENEFITS

- **POWERED FORWARD AND REVERSE** with industry-best 4.7 mph transport speed
- **INTEGRATED THROTTLE/CLUTCH CONTROL ON HANDLE** results in simple operation; releasing the handle puts the machine into idle
- **ADVANCED VIBRATION DAMPENING SYSTEM** and **NEW modified cam design** provides enhanced operator comfort even with extended run times
- **INTEGRATED REAR SWIVEL WHEEL** provides turning ease and locks in place for straight-line cutting
- **KNOBBY TREAD DRIVE WHEELS** grip the turf better and reduce dirt buildup
- **18" BLADE STANDARD.** Optional blade assemblies include 12", 16" or 20".

BEST SUITED FOR:
Landscapers and Turf Care Professionals
IDEAL LAWN SIZE: Any



Easy-to-operate thanks to user-friendly controls and quick view how-to panel



DESCRIPTION	MODEL NUMBER
SOD CUTTER ACCESSORIES	
Blade conversion 18" TO 12"	C900014
Blade conversion 18" TO 16"	C900037
Blade conversion 18" TO 20"	C900007
Blade conversion 18" TO 24" (Fits HSC188E only. Model suspended for 2022)	C900019

Model	HSC185E
Engine	Honda® GX160
Dimensions (WxD)	18" x 2.5"
Dimensions (LxWxH) (handle folded)	52" x 24.5" x 38"
Dry weight	336 lbs

2-YEAR WARRANTY*

Engines are warrantied separately by manufacturer. *See website for terms & conditions.



TURF RAKES HYDRO-DRIVE PRO TRS20

Dethatch large areas, hills and gradients easily with the PRO TRS20 Hydro-Drive Turf Rake featuring a productive and fatigue-free hydrostatic drive operation. For landscapers taking on a variety of projects, the PRO TRS20 converts to a turf seeder or vertical cutter in minutes.

Our PRO line offers productivity-enhancing features to help landscapers complete more projects quickly and increase profits. The PRO line's proven designs include the important extras, such as hydrostatic transmissions, anti-vibration grips and power steering.

KEY BENEFITS

- VARIABLE SPEED from 0 to 3.4 mph for greater productivity
- 5-POSITION, SINGLE-ACTION HEIGHT ADJUSTMENT LEVER moves in 1/4" increments for optimal depth
- 28 HEAT-TREATED FLAIL BLADES with spacing of 11/16" standard, adjustable up to 1-3/8" for greater flexibility
- FOLD-DOWN HANDLE makes hauling and stowing simple
- HYDROSTATIC DRIVE TRANSMISSION makes for fast manoeuvring on hills and slopes by saving the operator from intense muscle-work
- WHEELS WITH SEALED BEARINGS withstand challenging conditions and semi-pneumatic tyres smoothly move the unit across the turf

Model	TRS-20HE
Engine	Honda® GX160
Transmission	Hydrostatic, Hydro-Gear® T2
Operating width	20"
Blade/reel type	Flail
Dimensions (HxWxL)	12" x 16" x 20" & 24"
Dimensions (handle folded)	38" x 24.5" x 55"
Dry weight	215 lbs

BEST SUITED FOR:
Landscapers and Turf Care Professionals
IDEAL LAWN SIZE:
Any



2-YEAR WARRANTY*

Engines are warrantied separately by manufacturer. *See website for terms & conditions.



TURF RAKE WALK BEHIND TR20

Dethatch your lawn or easily convert the TR20 into an overseeder or vertical slice aerator for additional projects. The TR20 turf rake is portable and compact for easy storage.

Model	TR-20HE
Engine	Honda® GX160
Operating width	20"
Blade/reel type	Flail
Dimensions (HxWxL)	40" x 27" x 44"
Dimensions (handle folded)	29.58" x 27" x 30.5"
Dry weight	135 lbs

KEY BENEFITS

- 5-POSITION, SINGLE-ACTION HEIGHT ADJUSTMENT LEVER moves in 1/4" increments for optimal depth
- PROVIDES FLEXIBILITY by converting to a rake with catcher, turf seeder or vertical cutter in minutes
- CHOICE OF DOUBLE EDGED FLAIL BLADES OR SPRING TINE REEL for more gentle raking
- HEAVY-DUTY GREASABLE BEARINGS WITH CAST IRON HOUSINGS give added durability and easy maintenance
- SEALED BEARINGS IN WHEELS add durability while semi-pneumatic tyres provide better flotation on turf and easier manoeuvrability
- FOLD-DOWN HANDLE eases transportation and storage

BEST SUITED FOR:
Homeowners and Landscapers
IDEAL LAWN SIZE:
Small to moderate



DESCRIPTION	MODEL NUMBER
Turf Rakes Accessories	
Metal seed box assembly	C900055
Flail blade assembly	C900003
Multi-purpose blade assembly	C900026
Slicing blade assembly	C900027
Spring tine reel assembly	C900045
(ABOVE REEL ACCESSORIES INCLUDE THE COMPLETE REEL ASSEMBLED, END PLATES, BEARINGS, PULLEY, KEY AND FASTENERS)	

2-YEAR WARRANTY*

Engines are warrantied separately by manufacturer. *See website for terms & conditions.



Since 1922 Little Wonder has been offering landscape and debris management equipment and now has more products than any other manufacturer in this category. They know how to use air power to move and collect debris better than anyone else.

As a professional landscaper or a dedicated DIY homeowner, you demand quality, convenience and durability. You put in long hours and expect your equipment to do the same.

Little Wonder understand completely and engineer their powerful equipment to stand up to your needs, season after season.

PRO VAC SI DEBRIS VACUUM

The Pro Vac SI delivers the suction power to clear litter and debris faster. Serrated Steel Impeller Blade Technology with up to a 5:1 reduction ratio delivers superior suction and shredding capabilities in a compact footprint.

Keep your pace going with instant easy nozzle height adjustment from the operator's position. You'll get non-stop, efficient pavement-to-turf transition for faster cleaning up.

Throated nozzle design increases airspeed for improved vacuum capability. Unique rectangular discharge chute prevents debris clogs. The optimised 40-gallon, no-kick bag design prevents wear and tear.

The optional hose kit for cleaning out flower beds and hard to reach areas sits securely in a special contoured pocket that blocks air flow when not in use.

ACCESSORIES

- 1 HOSE KIT (5" x 7' Pro Vac SI) LW4176172
- 2 NOZZLE GUARDS (Pro Vac SI) LW4176173

PUSH

Model	LW5511-02-59 PRO VAC Si
Engine	Honda® GX190
Displacement	187 cc
Fuel capacity	0.25 gallon
Bag design	Mesh with dust skirt (optional felt bag)
Bag capacity	40 gallon (US)
Impeller	12" dia., 5 blades, 1/4" thick
Nozzle type	Fixed
Nozzle width	27.5"
Wheels	12" rubber tread cap wheels
Hose (optional)	5" diameter, 7' long
Weight	66 kg / 146 lbs
Dimension (LxWxH)	57.5" / 27" / 43.5"
Nozzle type / width	Height adjustable, floating / 29"


KEY BENEFITS

- 1 Optimal sized hose with adjustable handle to get debris in tight areas.
- 2 5-blade, serrated steel impeller technology with up to 5:1 reduction ratio.
- 3 40-gallon, angled bottom bag with plastic bottom reduces wear and tear.
- 4 Lightweight and easy to manoeuvre on and off trailers/ vans.
- 5 Throated nozzle design engineered for superior suction power.



Instant nozzle height adjustment from operator's position, for non-stop, pavement-to-turf leaf and debris clean-up.

5-blade steel impeller.



2-YEAR WARRANTY*

Engines are warrantied separately by manufacturer. *See website for terms & conditions.



OPTIMAX™ BLOWERS

Little Wonder Optimax™ maximum output blowers are perfect for moving leaves, debris and standing water — or for any job that requires hurricane-force air.

All models feature a split-stream air deflector, which minimises “blow-back”, and adjustable, ergonomic handles with anti-vibration grip for operator comfort.

Add a transport bracket for convenient tie-down and an industry-leading 5-year warranty, and you’ll see why Optimax is the only blower you need.

MODELS AVAILABLE

Model	LB270H
Product No.	9270-02-01
Engine	Honda® GX270
Displacement	270 cc
Fuel capacity	5.3 ltr / 1.4 gallon
Impeller (diameter, type)	17", 7-blade steel, reverse angle
Discharge chute area	25.8 sq. in.
Air volume	2260 cfm
Air speed*	143 mph
Integrated front / side discharge	yes
Air flow control	Remote
Front tyres	10" pneumatic tyres with tube
Rear tyres	
Handle	Ergonomic 2-position adjustable; anti-vibration grip
Housing	Continuously-welded steel; 1 piece engine keck
Dimensions (H x W x L)	43" x 28" x 58"
Weight	64 kg / 142 lbs

Model	LB390H
Product No.	9390-02-01
Engine	Honda® GX390
Displacement	389 cc
Fuel capacity	6.0 ltr / 1.6 gallon
Impeller (diameter, type)	17", 7-blade steel, reverse angle
Discharge chute area	25.8 sq. in.
Air volume	2530 cfm
Air speed*	160 mph
Integrated front / side discharge	yes
Air flow control	Remote
Front tyres	10" pneumatic tyres with tube
Rear tyres	
Handle	Ergonomic 2-position adjustable; anti-vibration grip
Housing	Continuously-welded steel; 1 piece engine keck
Dimensions (H x W x L)	43" x 28" x 58"
Weight	76 kg / 168 lbs

KEY BENEFITS

- 1 Powerful 7- or 9- blade fan and steel impeller produces high airflow while the scrolled housing allows uninterrupted air intake. Even if a portion of the housing is covered with leaves and debris, airflow can still enter the impeller area and be forced out the discharge chute.
- 2 Curved aerodynamic inlet draws air in smoothly for constant power and helps avoid clogging even if leaves are sucked in.
- 3 Strong, ergonomic adjustable handle with anti-vibration grip for added comfort.
- 4 Remote chute deflector control allows you to adjust the split-stream air deflector from the operator's position.
- 5 Split-stream air deflector moves piles of leaves further and faster without blow-back. You'll only have to go over the area once.
- 6 Integrated front/side discharge allows you to expel the air from the front of the unit or out the side without tools.
- 7 Optional swivel wheel kit, easy to install, for 360° turning and control. Wheel can also lock into a straight position. Minimises wear and tear on tyres.

Optional swivel wheel kit, easy to install, for 360° turning and control. Wheel can also lock into a straight position. Minimises wear and tear on tyres.



Chain/pulley system controlled from the handle position to adjust the split-stream air deflector.



SWIVEL WHEEL KIT 9050-00-01



5-YEAR WARRANTY*

Engines are warrantied separately by manufacturer. *See website for terms & conditions.



HYDRO BRUSHCUTTER

The Little Wonder Hydro Brushcutter navigates through weeds, heavy brush and overgrown vegetation with ease. Our tempered spring steel 26" blade cuts tall weeds, brush and saplings up to 2" thick.

Our welded steel frame design and engine positioning provide excellent balance regardless of the terrain.

And, unlike the competition, our hydrostatic transmission offers infinitely-variable, clutch-less speed selection—up to 4.2 mph forward and 1.7 mph reverse. So you can cut your own path at your own pace.



KEY BENEFITS

- 1 Ergonomic control system with forward / reverse and blade engagement levers positioned at handle grips.
- 2 Solid rods connect the operator to the transmission, park brake and cutter blade clutch—no cables to break or adjust.
- 3 Single belt pulley system.
- 4 1" diameter mower blade spindle is supported by top and bottom sealed ball bearings inside a machined steel hub.
- 5 Tempered spring steel 26" blade cuts tall weeds, brush and saplings up to 2" thick.
- 6 Adjustable 1.5" wide, .25" plate steel skid shoes provide excellent flotation over rough terrain.
- 7 16" foam-filled no-flat, puncture-proof bar tread tyres for excellent traction and ground clearance on rough terrain.
- 8 7-, 10- and 12-gauge welded steel engine base, cutting deck, rear frame and control handle construction holds up to the toughest conditions.

Model	5126-22-59 HYDRO BRUSH CUTTER
Product description	Hydro BRC-26 Honda™
Engine	Honda® GXV390
Displacement	390cc
Fuel capacity	2.1 ltr / 2.2 qts
Transmission	Hydro-Gear® T2™ Transaxle
Transmission type	Integrated hydrostatic pump / motor
Axle	.75" solid steel
Park brake	Standard
Differential lock	Open
Ground speed - forward	Infinitely-variable, 0-4.2 mph
Ground speed - reverse	Infinitely-variable, 0-1.7 mph
Cutting width	26" / 66cm
Spindle / bearings	1" diameter / Dual sealed ball bearing
Overall width	30" (32" at the handles)
Cut height / capacity	3" - 5" / Saplings up to 2" diameter
Tyres	16" / 40.6cm Puncture-proof, Bar tread, Foam-filled
Unit weight	183 kg / 405 lbs

2-YEAR WARRANTY*

Engines are warrantied separately by manufacturer. *See website for terms & conditions.

SERVICING AND PARTS

Our dealers will help you find the product to suit your requirements; they also offer advice, servicing, parts and product support from warranty to repairs on all our products. Spare parts are available and distributed through our dealer network in the UK.

Visit us online for product information and updates. The dealer locator on our website will help you find your nearest dealer.

www.lawnflite.co.uk

www.mantis.uk.com

www.gtmchippers.co.uk

www.littlewonder.com

www.classen.com

WARRANTY

A warranty is issued on all our garden machinery. This warranty covers faulty manufacture and materials of units which have been operated and maintained in accordance with the owner's instructions furnished with the unit and which have not been subject to misuse, abuse, neglect, accident, improper maintenance or alteration. Please see individual product pages for the length of warranty.

Annual servicing by an authorised Lawnflite specialist dealer will keep your equipment in top condition and ensure your machinery meets the Lawnflite two year warranty conditions.

Text and photographs, specifications of dimensions and performance are composed with the greatest care. The correctness of the information cannot be guaranteed, especially it is not guaranteed that the products comply with the images regarding colour, form and equipment or that the products comply with the proportion of the images. The engine horsepower information provided by the engine manufacturer is to be used for comparison purposes only.

Amendments due to misprints or errors are reserved. Please see the operator's manual and the warning labels posted on the item itself for more details. Subject to changes in prices.



**The Power
Behind The Brands**

Specifications and/or prices are subject to change without notice.
Every effort is made to produce sales literature and price lists that are accurate and current.

Lawnflite • Lawnflite Pro • AgriFab • GTM • Mantis • Classen • Little Wonder - Supported by Barrus
E. P. Barrus Ltd, Glen Way, Launton Road, Bicester, Oxfordshire, OX26 4UR.
Tel: 01869 363641 Fax: 0871 429 9206 www.barrus.co.uk