

**ESE 606 DHS-GT**

Art. no.: 112305

Availability: active product

**Fittings:**

HONDA OHV engine, Tank level indicator - optical, Automatic low oil shut-off, Alternator overload protection, Larger tank volume for longer operation, Folding handles, Compound regulated alternator at 400V, Alternator with Low Distortion Device for clear voltage

**Technical data**

|                                                |                                                  |
|------------------------------------------------|--------------------------------------------------|
| Alternator                                     | synchronous                                      |
| Max. output [LTP] kVA/kW 3~                    | 8,3 / 6,6                                        |
| Prime power [PRP] kVA/kW 3~                    | 7,0 / 5,6                                        |
| Max. output [LTP] kVA/kW 1~                    | 4,9 / 4,4                                        |
| Prime power [PRP] kVA/kW 1~                    | 3,5 / 3,2                                        |
| Nominal voltage 3~                             | 400 V 3~                                         |
| Nominal voltage 1~                             | 230 V 1~                                         |
| Nominal current 3~                             | 10,1 A 3~                                        |
| Nominal current 1~                             | 15,2 A 1~                                        |
| Power factor cos (phi)                         | 0,8 / 0,9                                        |
| Frequency                                      | 50 Hz                                            |
| Protection class                               | IP23                                             |
| Engine type                                    | Honda GX390                                      |
| Number of cylinders                            | 1                                                |
| Displacement                                   | 389 ccm                                          |
| Output 3000 RPM                                | 6,4 kW                                           |
| Fuel                                           | Petrol                                           |
| Tank capacity (litres)                         | 30                                               |
| Consumption l/h at 75% load                    | 2,1                                              |
| Running time (h) at 75% load                   | 14                                               |
| Start-up system                                | Recoil starter                                   |
| Sound power level LWA db(A)                    | 97                                               |
| Sound pressure level (7 m) db(A)               | 72                                               |
| Weight ca. (kg)                                | 81                                               |
| Dimensions L x B x H (mm)                      | 800 x 538 x 576                                  |
| Shockproof sockets                             | 1 x 230V 16A, 1 x 230V CEE 16A, 1 x 400V CEE 16A |
| Electric tools 230V up to                      | 3100 W                                           |
| Electric tools 400V up to                      | 5500 W                                           |
| Gardening or construction equipment 230V up to | 2100 W                                           |
| Gardening or construction equipment 400V up to | 3700 W                                           |
| Compressors or pumps 230V up to                | 1600 W                                           |
| Compressors or pumps 400V up to                | 2800 W                                           |
| Inverter welding equipment up to               | 3,25 mm                                          |

Stand: 2018-11-23

Technische Angaben und Abbildungen sind unverbindlich. Für Druckfehler und Irrtümer übernehmen wir keine Haftung.