

Chainsaw LXT®

DUC353

18V X2 • 20 m/s • 35 cm / 14"

Efficient brushless saw with a high chain speed for heavy-duty use

A versatile and efficient brushless saw with a chain speed of 20 m/s, designed for use at construction sites, at home or at the summer cottage. A high 36V is achieved with two 18V LXT® batteries. Equipped with a 14" guide bar and tool-less chain and bar tensioning.



■ Technical specifications

Nominal Battery Voltage	2 x 18 V
Max. Chain Speed (No Load)	20 m/s
Chain Pitch	3/8 "
Chain Gauge	0,043 "
Chain Gauge	1,1 mm
Number of Drive Links	52
Chain Oil Tank	0,2 L
Sound Power Level (L _{WA})	100,0 dB(A)
Sound Pressure Level (L _{pA})	89,0 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	5,9 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery	4,6 - 5,5 kg
Product Dimensions (L x W x H):	443 x 215 x 235 mm
Brushless Motor	✓
Voltage LXT	✓

■ User benefits

- 36V performance from two 18V batteries connected in series. The batteries are placed in parallel in separate battery docking stations.
- Tool chain and flange replacement, and tool-less tightening
- Adjustable automatic chain lubrication with large oil reservoir
- Brushless maintenance-free and long-life motor
- The compact design makes the saw easy to handle
- Battery protection system automatically shuts off power when the battery level is low

[Link to product - www.makita.com](http://www.makita.com)



Related products

Optional AC

165245-8

Guide Bar 12" / 30 cm, 3/8", -46, 1,1



165246-6

Guide bar, 14" / 35 cm, 3/8", 1,1 mm



165247-4

Guide bar, 16" / 40 cm, 3/8", 1,1 mm



196741-5

Saw Chain, -52, 3/8", 1.1 mm, 14" /



419288-5

Chain Protection Cover 14" / 35 cm



BL1830B

Battery LXT® 3,0 Ah



BL1840B

Battery LXT® 4,0 Ah



BL1850B

Battery LXT® 5,0 Ah



BL1860B

Battery LXT® 6,0 Ah



D-70948

Round File & Guide Set, Ø 4,0 mm



D-70954

Round File & Guide Set, Ø 4,5 mm



Other

[User manual](#)

[Parts drawing](#)