


HE RING STRIPNAIL 3,1X90MM CARBON STEEL STANDARD TENSILE



HE59ASBKR

APPLICATIONS

Framing, sheathing, subfloor, decking, trusses, pallets and crates


TECHNICAL SPECIFICATIONS

Collation angle	34 °
Collation type	Paper collated
Wire material	Carbon steel standard tensile
Finish	Hot-Dipped galvanised 3
Coating	Sencoted
Nail head type	Clipped head
Head width	6.71 - 7.21 mm
Head length	5 - 5.36 mm
Nail shank type	Ring shank
Point type	Diamond
Pointangle	40 °
Nail length	90 mm
Nail diameter	3.1 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274028538
Package quantity	2000 pieces
Net weight	10.78 kg

FASTENER SPECIFICATIONS



CE SPECIFICATIONS

CE fastener type	Round cross-section ring shank nail
Protection level in micron	55
Service class	3
Coating type	Coating type 3
Coating length	60 mm
Head cross sectional area	30 mm
Threaded/profiled length	62 mm
Characteristic yield moment	2936 Nmm
Characteristic head pull through parameter	20.72 N/mm ²
Characteristic tensile strength	633 N/mm ²