



STRIPPING MACHINES MS 330 Multistripper



Many years of experience in the design and operation of surface preparation equipment have been integrated with the latest computer design technology to produce the MS 330 Multistripper



Since the MS 330 launch, this heavy-duty, power-driven machine has proved to be a popular choice, setting new industry standards for all strippers of this type. By combining many unique features in one machine, the MS 330 offers the user a totally effortless high performance stripping machine for the removal of materials in the toughest possible conditions.

| Specifications | | | | |
|--------------------|----------------|----------------|----------------|----------------|
| Type | Electric | | | Petrol/Gas |
| | 1 Phase | | 3 Phase | |
| Part Number | MS 330-1 | MS 33021 | MS 330-3 | MS 330-4 |
| Power Output | 3.0hp | 3.0hp | 3.0hp | 5.5hp |
| Voltage | 110 | 220 | 400 | - |
| Cycles | 50hz | 50hz | 50hz | - |
| Machine Dimensions | | | | |
| Length | 1100mm (43.3") | 1100mm (43.3") | 1100mm (43.3") | 1100mm (43.3") |
| Width | 480mm (18.9") | 480mm (18.9") | 480mm (18.9") | 480mm (18.9") |
| Height | 1000mm (39.4") | 1000mm (39.4") | 1000mm (39.4") | 1000mm (39.4") |
| Weight | 132kg (291lbs) | 132kg (291lbs) | 132kg (291lbs) | 126kg (278lbs) |
| Working Width | 330mm (13") | 330mm (13") | 330mm (13") | 330mm (13") |
| Engine/Motor | 2800rpm | 2800rpm | 2800rpm | 2800rpm |

Features

- All support wheels power driven to provide excellent forward traction
- Handle height adjustable for operator comfort
- Manually operated positive drive clutch for forward drive/freewheel
- Minimal operator fatigue
- Extremely powerful, robust construction
- Simple clamp arrangement for quick and easy blade change
- Available in choice of electric or petrol/gas
- Blade angle adjustable to suit application



| Accessories | Part No. | Description |
|-------------|----------|-------------|
| MS 330 | 7007 | Std Blade |

Applications

- The removal of sheet vinyl, linoleum, bonded carpet
- Woodblock, tiles, debonded membranes, sports surfaces
- Failed latex
- Build-up of excess materials in factory production areas

| Specifications | | | | | | |
|----------------|-------|-----------|---------------------|------------------|-------------|-----------|
| Machine | Volts | Plug Size | Cable Size | Max Cable Length | Transformer | Generator |
| MS 330-1 | 110 | 32A 3 Pin | 4mm (0.2") 3 Core | 30m (98') | 5 kva | 8 kva |
| MS 330-2 | 220 | 16A 3 Pin | 2.5mm (0.1") 3 Core | 30m (98') | - | 8 kva |
| MS 330-3 | 400 | 16A 5 Pin | 2.5mm (0.1") 4 Core | 75m (246') | - | 8 kva |



1-866-501-1683
375 Annagem Blv. Mississauga,
ON, Canada, L5T 3A7
www.bartellmorrison.com



1-888-999-1570
200 Commerce Dr. Freehold,
NJ, U.S.A, 00728
www.bartellmorrison.com



44-(0)1673-860709
Honeyholes Lane, Dunholme
Lincoln. LN2 3SU. U.K.
www.spe-int.com



1-800-267-6682
832 80th St. SW. Everett,
Washington, U.S.A, 98203
www.innovatechproducts.com