

# Concrete Vibrator XGT®

## VR001G

40Vmax • 12 000 – 15 000 min<sup>-1</sup>

**XGT® Battery powered Concrete Vibrator for professionals**

Concrete vibrator powered by 40Vmax XGT battery with two 2 operating modes. VR001G series supports a larger vibration part diameter than the current model and transmits vibration to a wider range to improve compaction efficiency thanks to 40Vmax XGT® Li-Ion battery and BL motor. Without Flexible shaft. Two 5,0 Ah batteries and a fast charger.



### Technical specifications

Voltage XGT	✓
Nominal Battery Voltage	40 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Brushless Motor	✓
Vibrations per minute	12000 - 15500 min <sup>-1</sup>
Vibrator Shaft Diameter	32 - 38 mm
Vibration Level, Load with Flexible Hose	6,2 m/s <sup>2</sup>
Vibration Uncertainty (K Factor), Load with Flexible Hose	1,5 m/s <sup>2</sup>
Sound Power Level (L <sub>WA</sub> )	91 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	≤ 70 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Product Dimensions (L x W x H):	282 x 112 x 258 mm
Tool weight with battery	4,8 - 7,8 kg

### User benefits

- Trigger lock minimizes accidental start-up during transportation
- Ergonomically designed handle with sure grip provides more control and comfort

Link to product - [www.makitauk.com](http://www.makitauk.com)



# Related products

## Other

User manual

Parts drawing