

# Rotary Hammer

## HR4013C

1 100 W • SDS-MAX • 40 mm • 8.0 J

**Efficient dual-action hammer with integrated anti-vibration technology**

An efficient 1 100 W combi hammer with a unique AVT anti-vibration system for SDS-MAX blades. Masonry drilling capacity of 40 mm and impact energy of 8.0 J. With its drilling and chipping functions, this tool is an ideal choice for renovation and building work.



**AVT** **SOFT**  
ANTI VIBRATION TECHNOLOGY **NO LOAD**

### Technical specifications

Continuous Input Power	1100 W
No load speed	250 - 500 min <sup>-1</sup>
Impacts per Minute (IPM)	1450 - 2900 min <sup>-1</sup>
Max. Drilling Diameter in Concrete	40 mm
Optimum Drilling Diameter Range in Concrete	16 - 30 mm
Impact Energy	8,0 J
Drilling diameter with TCT core bit	105 mm
Power Supply Cord	5,0 m
Plastic Carrying Case	✓
Sound Power Level (L <sub>WA</sub> )	104 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	93 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Chiselling	4,8 m/s <sup>2</sup>
Weight Without Cable	6,8 kg

**EAN 0088381651332**

Link to product - [www.makita.com](http://www.makita.com)

### User benefits

- AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- Adjustable speed
- Vibration dampened handle design for tireless work
- The service light indicates the need for carbon brush replacement and malfunctions in the switch and connection cable
- Impact drilling and spike function
- Standard electronics: power boost under load
- Lock-on button for user convenience during longer work periods
- Vibration absorbing housing helps to reduce vibration



# Related products

## Optional AC

**123138-5**  
Straight Side Handle



**194683-7**  
Grease vessel set, 100 ml



**198993-4**  
Grease vessel for bit 100 ml



**199144-2**  
Dust Extraction Attachment



**321248-4**  
Depth Gauge



**331955-1**  
Depth Gauge



## Other

[User manual](#)

[Parts drawing](#)