



# UNDERC 125A 400V US-12202

Undercentral/Uttagscentral 125A i låsbart plåtskåp. Undercentral 125A  
 II: 1x125A UI: 1x16A-32A-63A-125A- 2xschuko RCCB: 2x40A/4P 1x63A  
 4P 300mA MCB: 2xC113-C316 -C332 1xC363

E-nummer	Artikelnummer
2466449	352767

## Allmänna egenskaper

Typnamn	UGBS 4125-6/01/12202
Material	Plåt
Skyddsklass [IP]	44
Färg	Röd
Nettovikt [kg]	63
Märkström [A]	125
Frekvens [Hz]	50
Standard	EN 61439-4
Bredd [mm]	736
Höjd [mm]	880
Djup [mm]	475
IEC-Intag	1st 125A 3P+N+E 230/400V
IEC-Uttag	2st 16A 3P+N+E 230/400V
Märkspänning [V AC]	230/400
Förpackningsstorlek[st]	1
IEC-Uttag	2st 32A 3P+N+E 230/400V
Kortslutningsström [kA]	17
Jordfelsbrytare [st]	2st 40A/4P
MCB	2st C113
MCB	2st C316
Schuko [st]	2
IEC-Uttag	1st 63A 3P+N+E 230/400V
MCB	2st C332
Jordfelsbrytare [st]	1st 63A/4P/300mA
MCB	1st C363
IEC-Uttag	1st 125A 3P+N+E 230/400V

## Specifika egenskaper

Namn	UNDERC 125A 400V US-12202
E-nummer	2466449
Artikelnummer	352767