

Portable Compressors MOBILAIR M 26 With the world-renowned SIGMA PROFILE **

Free air delivery 2.6 m³/min





MOBILAIR M 26

Portable compressor with the renowned SIGMA PROFILE **



High performance - perfect for two breakers

Capable of powering two breakers, the M 26 is a powerful and compact portable compressor that combines guiet operation with impressive fuel economy:

- SIGMA PROFIL[®] airend provides more air for less power consumption
- Highly efficient 1:1 drive ensures optimum power transmission for low speed operation and significantly extends service life
- Water-cooled, 3-cylinder Kubota engine with plenty of power in reserve



Lightweight and service-friendly

A high performance compressor doesn't necessarily mean a heavy compressor. The M 26 delivers maximum power in a compact, lightweight package:

- Rotation-sintered, double-walled sound enclosure provides corrosion- and scratch-resistance to ensure long-term value retention
- · Optimal component accessibility for ease of maintenance
- With compact design and an operational weight of less than 500 kg, the unit is particularly manoeuvrable



Patented Anti-Frost Control for low condensate compressed air

Specially developed for portable compressors, the patented Anti-Frost Control automatically regulates operating temperature in relation to ambient. The benefits speak for themselves:


- · Prevents breakers from freezing up
- · Significantly extends air-tool service life



Everything safely under control

The user-friendly control and instrument panel enables all information to be viewed at a glance.

- Operation is made simple via a single switch
- Clear icons further enhance user-friendliness



Technical specifications – MOBILAIR M 26

Model	Compressor unit		3-cylinder diesel engine (water-cooled)					Complete unit				
	Air delivery m³/min	Working pressure bar	Make	Model	Rated motor power kW	Speed at full load rpm	Idling speed rpm	Fuel tank capacity	Operational weight kg	Sound power level dB(A)*	Sound pres- sure level dB(A)**	Air connection
M 26	2.6	7	Kubota	D1105	17.9	2850	2100	30	498	≤98	69	2x G¾

^{*)} Guaranteed sound power level to directive 2000/14/EU - **) Surface sound pressure level to ISO 3744, (r = 10 m)





KAESER COMPRESSORS Australia Pty. Ltd.

Locked Bag 1406 – Dandenong South – Vic. 3164 45 Zenith Road – Dandenong – Vic. 3175

Phone: +61 3 9791 5999 - Fax: +61 3 9791 5733 www.kaeser.com - E-mail: air@kaeser.com.au