

SCARIFIERS



RELIABLE, VERSATILE & RUGGED SCARIFIERS

Coating removal and surface preparation

- Robust, precision construction with proven reliability
- Extensive range of cutters available
- Long life cutter drum assemblies
- 2 inch (5cm) dust extraction port (dust free when operated with a suitable dust collector)

Applications include:

- concrete texturing
- shaving
- scarifying
- planing
- grooving
- cleaning
- descaling
- removal of road markings, coatings, and membranes



POWERED by
HONDA™

TECHNICAL SPECS

MODEL	BEF200N		CT250		BEF275		BEF320		CT320
Part Number	BEF200N-2(A)	BEF200N-4(A)	CTPCT250 • CT-PCT250P •		BEF275-7 •	BEF275-1	BEF320-1A •	BEF320-3A •	CTPCT320 CTPCT320LC
Power Source	Electric	Gas	Electric	Gas	Electric	Gas	Electric	Diesel	Electric
Power Output	3hp / 2.2kW	5.5hp / 4kW	10hp / 7.5kW	12hp / 8.8kW	10hp / 7.5kW	11hp / 8.2kW	15hp / 11.2kW	10hp / 7.5kW	23hp / 16.9kW
Voltage	230V Single-Phase	-	230V 3-Phase	-	230V 3-Phase	-	460V 3-Phase	-	480V 3-Phase
Cutter Drum Speed	1738 rpm	1833 rpm	1571 rpm		1640 rpm		933 rpm	1333 rpm	1644 rpm
Cutter Diameter	up to 1.75"		up to 2.25"		up to 2.25"		up to 3"		3" (76mm)
Blade Diameter	-	-	7.9" (20cm)		-		-		11.8" (30cm)
Starter	Switch	Recoil	Switch	Recoil	Switch	Recoil	Star / Delta	Manual	Switch
Travel Method	Manually Propelled		Self Propelled		Manually Propelled		Self Propelled: 0-39 ft/min		Self Propelled
Length	39" (99cm)		41" (104cm)		48" (122cm)		48.5" (123cm)		43" (109cm)
Width	16" (43cm)		17" (43cm)		20" (51cm)		23.25" (59cm)		24" (61cm)
Height	37" (94cm)		39" (99cm)		35.4" (90cm)		48" (122cm)		43" (109cm)
Weight	137 lbs (62kg)	127 lbs (58kg)	298 lbs (135kg)		331 lbs (150kg)	319 lbs (145kg)	749 lbs (339kg)	702 lbs (319kg)	507 lbs (230kg)
Max Working Width	8" (20cm)		10" (24cm)		10.75" (27cm)		12.5" (32cm)		12.6" (32cm)
Working Distance from Wall	2.5" (7cm)	2" (5cm)	3.25" (8cm)		2.5" (7cm)		1.5" (4cm)		3.25" (8cm)
Engine/Motor Speed	2870 rpm	3000 rpm	2880 rpm	3600 rpm	2800 rpm	3600 rpm	1450 rpm		2935 rpm