



**WACKER
NEUSON**
all it takes!

DPU6555He

5100016940

[Home](#) >> [Catalog](#) >> [Products](#) >> [Compaction](#) >> [Vibratory Plates](#) >> [Reversible Vibratory Plates](#) >> **DPU6555He**



DPU6555He

Material number 5100016940

Reversible vibratory plate with a diesel engine and electric starter for heavy demands on performance and sturdiness in soil, asphalt and paving stone compaction.

Product details

- Sturdy and durable
- Very good accessibility to all maintenance points
- High surface performance

Comes with

- Vibratory plate
 - Operator's manual
- (Starting crank not included in standard package)

Technical specifications

DPU6555He

OPERATING FLUIDS	Metric
Tank capacity	6,00 l
Exciter oil volume	0,75 l
Hydraulic fluid type	Renolin MR 520
Hydraulic fluid volume	0,5 l
Exciter oil type	75W-90 API GL-4

ENGINE	Metric
Inclined position max.	25,0 °
Engine operating mode	four-stroke
Operating Engine speed	3.010 1/min
Fuel consumption	1,90 L/Std
Standard (Power max.)	ISO 3046 IFN
Standard (Effective power)	ISO 3046 IFN
Nominal Engine speed	2.800 1/min, 2.800 1/min
Oil filling max.	1,90 l
Effective power	9,6 kW, 9,6 kW
Battery capacity (nom. value)	45 Ah
Air cleaner	Dry air filter
Power rating max.	10,1 kW
Cooling	air cooling
Exhaust-gas limit	EU Stage V
Oil specification	SAE 10W-40
Starter battery Voltage	12 V
Engine speed (Power max.)	3.600 1/min
Starter type	E-starter
Upper idling speed ex load	3.080 1/min
Operating power	6,8 kW

Oil filling min.	1,00 l
Engine type	Diesel engine
Cylinder	1
Engine Manufacturer	Hatz
Standard (Operating power)	ISO 3046 IFN
Cylinder capacity	667 cm ³
Kraftstofftyp	Diesel EN 590
Oil volume incl. filter change	0,00 l

MECHANICAL - OUTPUT DETAILS

Metric

Vibrations	4.150 1/min
Forward running	28,00 m/min
Transmission	FKR
Gradeability	46,6 %
Centrifugal force	65,000 kN
Vibrations (Hz)	69,0 Hz
Area capacity	1.200 m ² /h

ENVIRONMENT DATA

Metric

Operating temperature range	-15 - 40 °C
Sound level LpA (Standard)	EN 500-4
Sound power LWA, guaranteed	109,0 dB(A)
Storage temperature range	-15 - 40 °C
HAV summation (average value)	2,5 m/s ²
Uncertainty in measurement HAV	0,5 m/s ²
HAV summation (Standard)	EN 500-4
Sound level LpA	97,0 dB(A)
Sound power LWA (Standard)	EN 500-4
Sound power LWA, measured	108,0 dB(A)

MECHANICAL DETAILS

Metric

Lenght Drawbar in op. pos.	1.664 mm
----------------------------	----------

Operating weight	504,0 kg
------------------	----------

Ground clearance	861 - 1.005 mm
------------------	----------------

Height	1.308 mm
--------	----------

Width	710 mm
-------	--------

Custom Attributes

Metric

Model serie	DPU
-------------	-----

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE