
Flexible couplings





Standard couplings, Adapter couplings and Plug adapters are used to connect two waste water pipes with the same or different dimension, material and surface textures. Suitable for both vertical and horizontal installation. It is important to consider the flow direction of the Plug adapter.

The flexible couplings are equipped with hose clamps on one or two sides depending on whether they are for internal or external installation. They are easy to install and approved for concealed installation. The materials are UV-resistant.

Example of application:



To connect to waste water pipes with different material and different diameter use Adaptor coupling.



Loosen the clamp bands a little.



Push the Adaptor coupling over the first cleaned pipe and tighten the clamp band.



Push the smaller pipe into the adaptor coupling (if necessary use lubricant) and tighten the second clamp band.



Completed installation.

Prod no.	Name	D1	D2	Prod no.	Name	D1	D2
3032526	Plug adaptor 73-85/69-75	73-85	69-75*	3032535	Standard coupling 40-50	40-50	40-50
3106989	Plug adaptor 100-120/100-105	100-120	100-105*	3032543	Standard coupling 48-56	48-56	48-56
3032527	Plug adaptor 120-141/117-125	120-141	117-125*	3032536	Standard coupling 50-65	50-65	50-65
3032529	Adaptor coupling 53-64/40-50	53-64	40-50	3106988	Standard coupling 70-85	70-85	70-85
3032530	Adaptor coupling 75-89/53-63	75-89	53-63	3032538	Standard coupling 80-95	80-95	80-95
3032531	Adaptor coupling 100-116/75-90	100-116	75-90	3106987	Standard coupling 100-116	100-116	100-116
3032532	Adaptor coupling 110-125/100-116	110-125	100-116	3032539	Standard coupling 110-125	110-125	110-125
3032533	Adaptor coupling 121-136/100-116	121-136	100-116	3032540	Standard coupling 120-137	120-137	120-137
3032534	Adaptor coupling 130-145/110-125	130-145	110-125	3032541	Standard coupling 135-150	135-150	135-150
3032544	Adaptor coupling 170-192/144-160	170-192	144-160	3032542	Standard coupling 150-170	150-170	150-170

D1 & D2 = external pipe dimension
* internal pipe dimension

- Suitable for all waste water pipes
- For horizontal and vertical installation
- Easy installation in some minutes
- Proofed material quality
- Sound-absorbing function
- Approved by RISE cert no. 0122/06

Our continual product development may result in changes to finish, design and construction, which we reserve the right to.

Purus is
ISO 9001
certified

Purus
info@purusinternational.com
www.purusinternational.com