

Boverket's regulations on safety during use of buildings. (BFS 2024:9):

Fixtures and fittings

BFS 2024:9, Ch. 2, Sec. 28

Boverket's Building Regulations (BBR) (BFS 2011:6 as amended up to and including BFS 2024:5) ¹:

Wastewater installations

BBR 6:641

Design

BBR 6:644

Fixtures, fittings and equipment

BBR 8:32

¹ May be applied to the extent stated in the transitional provisions of Boverket's regulations BFS 2024:14.

Associated documents

Installation instruction floor gullies 22733 dated 2025-03-31.

Maintenance instruction floor gullies and channels dated 2024.

Control

The factory production control (FPC) is monitored by an independent inspection body.

Control plan: Appendix A dated 2025-10-09 to control agreement 351. Inspection body: DTI

When the building proprietor performs inspection at the building site, markings shall be checked to ensure that the correct products have been supplied and that they are used in accordance with the conditions in this type approval and associated documents. Further the product shall be accompanied by a manufacturer's assurance, certifying that the product has been manufactured in accordance with the documents on which this type approval is based.

Manufacturing place

Production control includes the following place:

Vitas Group AB, Södra Dragongatan 15, 271 39 Ystad, Sweden

Marking

The products are to be marked at the factory. The marking consists of a text on every product and packing supplied and includes:

On product and packing:

Distributor

PURUS

Product type designation

trade name

Product code/RSK-no.

number

Boverket's registered trademark

†

Certification body

RISE

RISE accreditation number

1002

Inspection body

DTI

Product is also marked with:

Consecutive manufacture year/month of production

year/month

Approval number

0077/00

Basis for approval

Reports 270-9-0831A-55, 270-9-0831B-55, 270-9-0831C-55, 732649-1, 962948 Rev. 1 and 251425 from DTI.

Reports P901641-15B and P901641-15C from SP.

Type Approval 0077/00 | 2026-02-20

RISE Research Institutes of Sweden AB | Certification

Comments

Those floor gullies are approved according to standard SS-EN 1253-1, except for maximum flow (1,4 l/s) for Brage Mini 110. However, it complies with flow requirements for one shower head (0,4 l/s).
The removable water trap needs to be cleaned regularly.

Associated documents shall accompany the product or by other means be available to users of the product.

This type approval supersedes the previous type approval with the same number dated 2021-01-28.

Validity

Valid up to and including 2031-02-19.

The validity of this type approval can be verified at RISE homepage.

The validity of this type approval expires when the type approved products with the intended use according to this type approval shall be CE-marked according to the Construction Products Regulation (EU) 305/2011 or 2024/3110.

A handwritten signature in blue ink, appearing to read 'Stefan Coric'.

Stefan Coric

This is a translation from the Swedish original document. In the event of any dispute as to its content, the Swedish original shall take precedence.