

Page 1 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0003  
Replacing version dated / version: 28.05.2021 / 0002  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Beton zum Kneten  
9405 000 xx

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Beton zum Kneten**  
**9405 000 xx**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Concrete

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

Viva Decor GmbH  
Meierweg 8  
D-32108 Bad Salzufflen  
+49 (0) 5222 36336 0  
+49 (0) 5222 36336 36  
info@viva-decor.de  
www.viva-decor.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (VDR)  
+1 872 5888271 (VDR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**



## Danger

H335-May cause respiratory irritation. H315-Causes skin irritation. H318-Causes serious eye damage.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P261-Avoid breathing dust. P280-Wear protective gloves / eye protection / face protection.

P302+P352-IF ON SKIN: Wash with plenty of water and soap. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

P501-Dispose of contents / container in accordance with all local, regional, national and international laws.

Cement, portland, chemicals

Flue dust, portland cement

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

Low-chromate

This product contains components that hamper the initiation of sensitization.

In case of contact with water:

Note pH value.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

Cement, portland, chemicals	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	266-043-4
CAS	65997-15-1
content %	<100
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

Flue dust, portland cement	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	270-659-9
CAS	68475-76-3

GB

Page 3 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0003  
 Replacing version dated / version: 28.05.2021 / 0002  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Beton zum Kneten  
 9405 000 xx

<b>content %</b>	<3
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Do not rub.  
 Remove contact lenses.  
 Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.  
 Protect uninjured eye.  
 Follow-up examination by an ophthalmologist.

#### Ingestion

Rinse the mouth thoroughly with water.  
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.  
 The following may occur:

Corneal damage.  
 Reaction with humidity of skin.  
 Dermatitis (skin inflammation)  
 Irritation of the skin.  
 On dust formation:  
 Coughing  
 Irritant to mucosa of the nose and throat  
 Irritation of the respiratory tract

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Product is not combustible.  
 Adapt to the nature and extent of fire.  
 Water jet spray/foam/CO2/dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:  
 Oxides of carbon

Page 4 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0003  
Replacing version dated / version: 28.05.2021 / 0002  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Beton zum Kneten  
9405 000 xx

Metal oxides  
Toxic gases

### **5.3 Advice for firefighters**

For personal protective equipment see Section 8.  
In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **6.1.1 For non-emergency personnel**

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.  
Leave the danger zone if possible, use existing emergency plans if necessary.  
Avoid build up of dust.  
Ensure sufficient supply of air.  
Avoid inhalation, and contact with eyes or skin.

#### **6.1.2 For emergency responders**

See section 8 for suitable protective equipment and material specifications.

### **6.2 Environmental precautions**

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
Prevent from entering drainage system.

### **6.3 Methods and material for containment and cleaning up**

Pick up mechanically and dispose of according to Section 13.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### **7.1 Precautions for safe handling**

#### **7.1.1 General recommendations**

Avoid build up of dust.  
Do not breathe dust.  
Avoid contact with eyes or skin.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
Use working methods according to operating instructions.

#### **7.1.2 Notes on general hygiene measures at the workplace**

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### **7.2 Conditions for safe storage, including any incompatibilities**

Keep out of access to unauthorised individuals.  
Store product closed and only in original packing.  
Not to be stored in gangways or stair wells.  
Protect from humidity.  
Store in a dry place.  
Store cool.

### **7.3 Specific end use(s)**

No information available at present.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0003  
 Replacing version dated / version: 28.05.2021 / 0002  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Beton zum Kneten  
 9405 000 xx

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Cement, portland, chemicals		Content %:<100
WEL-TWA: 10 mg/m3 (total inh. dust), 4 mg/m3 (res. dust)	WEL-STEL: ---		---
Monitoring procedures:		---	
BMGV: ---	Other information: ---		
Chemical Name	Flue dust, portland cement		Content %:<3
WEL-TWA: 10 mg/m3 (total inh. dust), 4 mg/m3 (res. dust)	WEL-STEL: ---		---
Monitoring procedures:		---	
BMGV: ---	Other information: ---		
Chemical Name	Quartz		Content %:
WEL-TWA: 0,1 mg/m3 (silica, respirable, crystalline)	WEL-STEL: ---		---
Monitoring procedures:		INSHT MTA/MA-036/A00 (Determination of Quartz in Air – Membrane Filter Method/ Xray Diffraction) - 2000, 2004 MDHS 101/2 (Crystalline silica in respirable airborne dust – Direct on-filter analysis by infrared spectroscopy and X-ray diffraction) - 2015 - EU project - BC/CEN/ENTR/000/2002-16 card 52-1 (2004) NIOSH 7500 (Crystalline Silica, by XRD (filter redeposition)) - 2003 - EU project - BC/CEN/ENTR/000/2002-16 card 52-6 (2004) - NIOSH 7601 (SILICA, CRYSTALLINE, by VIS) - 2003 - NIOSH 7602 (Crystalline Silica, by IR (KBr pellet)) - 2003 - NIOSH 7603 (QUARTZ in coal mine dust, by IR (redeposition)) - 2017 - OSHA ID-142 (Quartz and Cristobalite in Workplace Atmospheres) - 2016	
BMGV: ---	Other information: ---		
Chemical Name	Calcium sulphate		Content %:
WEL-TWA: 4 mg/m3 (Gypsum, respirable), 10 mg/m3 (Gypsum, inhalable dust)	WEL-STEL: ---		---
Monitoring procedures:		---	
BMGV: ---	Other information: ---		
Chemical Name	Calcium carbonate		Content %:
WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust)	WEL-STEL: ---		---
Monitoring procedures:		---	
BMGV: ---	Other information: ---		
Chemical Name	general dust limit		Content %:
WEL-TWA: 10 mg/m3 (inhal. dust), 4 mg/m3 (respir. dust)	WEL-STEL: ---		---
Monitoring procedures:		---	
BMGV: ---	Other information: ---		

#### Calcium sulphate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	3811	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	5,29	mg/m3	

GB

Page 6 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0003  
 Replacing version dated / version: 28.05.2021 / 0002  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Beton zum Kneten  
 9405 000 xx

Consumer	Human - oral	Short term, systemic effects	DNEL	11,4	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,52	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	5082	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	21,17	mg/m3	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Chemical resistant protective gloves (EN ISO 374).  
 Recommended  
 Nitrile-soaked cotton gloves with CE sign (EN ISO 374).  
 Minimum layer thickness in mm:

0,15  
 Permeation time (penetration time) in minutes:  
 60  
 Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Page 7 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0003  
Replacing version dated / version: 28.05.2021 / 0002  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Beton zum Kneten  
9405 000 xx

Respiratory protection:  
Normally not necessary.  
If OES or MEL is exceeded.  
Filter P1 (EN 143), code colour white  
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Solid
Colour:	According to specification
Odour:	Slightly
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Not combustible.
Lower explosion limit:	Does not apply to solids.
Upper explosion limit:	Does not apply to solids.
Flash point:	Does not apply to solids.
Auto-ignition temperature:	Does not apply to solids.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture reacts with water.
Kinematic viscosity:	Does not apply to solids.
Solubility:	reacts with water
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	There is no information available on this parameter.
Relative vapour density:	Does not apply to solids.

### 9.2 Other information

Explosives:	There is no information available on this parameter.
Oxidizing solids:	No

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Protect from humidity.

### 10.5 Incompatible materials

See also section 7.



Page 8 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0003  
 Replacing version dated / version: 28.05.2021 / 0002  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Beton zum Kneten  
 9405 000 xx

Acids  
 Ammonium salts  
 Aluminium  
 Light metals

### 10.6 Hazardous decomposition products

See also section 5.2  
 No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Beton zum Kneten 9405 000 xx						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						This product contains components that hamper the initiation of sensitization.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Cement, portland, chemicals						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Intensively irritant
Serious eye damage/irritation:						Risk of serious damage to eyes.
Respiratory or skin sensitisation:						Low-chromate
Respiratory or skin sensitisation:						Low-chromate, Not sensitizing
Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract
Symptoms:						mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract



Page 9 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0003  
 Replacing version dated / version: 28.05.2021 / 0002  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Beton zum Kneten  
 9405 000 xx

Quartz						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Symptoms:						respiratory distress, coughing, mucous membrane irritation

Calcium sulphate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>1581	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by oral route:	LD50	>1581	mg/kg		OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by inhalation:	LC50	>2,61	mg/l	Rat	OECD 403 (Acute Inhalation Toxicity)	Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEL	790	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	
Symptoms:						coughing, constipation

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by oral route:	LD50	> 5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:						No (skin contact)

Page 10 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0003  
 Replacing version dated / version: 28.05.2021 / 0002  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Beton zum Kneten  
 9405 000 xx

Germ cell mutagenicity:					in vitro	Negative
Carcinogenicity:						Negative, administered as Ca-lactate
Reproductive toxicity:						Negative, administered as Ca-carbonate

## 11.2. Information on other hazards

Beton zum Kneten 9405 000 xx						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Beton zum Kneten 9405 000 xx							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

Quartz							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Page 11 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0003  
 Replacing version dated / version: 28.05.2021 / 0002  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Beton zum Kneten  
 9405 000 xx

Calcium sulphate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2980	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	LC50	96h	>1970	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	>79	mg/l	Lepomis macrochirus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>79	mg/l	Daphnia magna STRAUS	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>79	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>790	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Calcium carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:					Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Negative
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Not relevant for inorganic substances.
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Oncorhynchus mykiss		

Page 12 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0003  
 Replacing version dated / version: 28.05.2021 / 0002  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Beton zum Kneten  
 9405 000 xx

12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>200	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Allow product to harden.

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 02 plastic packaging

## SECTION 14: Transport information

### General statements

14.1. UN number or ID number: n.a.

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

Classification code:

n.a.

LQ:

n.a.

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

Marine Pollutant:

n.a.

14.5. Environmental hazards:

Not applicable

#### Transport by air (IATA)

14.2. UN proper shipping name:

Page 13 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0003  
 Replacing version dated / version: 28.05.2021 / 0002  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Beton zum Kneten  
 9405 000 xx

14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 14.5. Environmental hazards: Not applicable

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Regulation (EC) No 1907/2006, Annex XVII

Cement, portland, chemicals

Flue dust, portland cement

This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148.

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

### SECTION 16: Other information

Revised sections: 1-16

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

#### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

Page 14 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0003  
Replacing version dated / version: 28.05.2021 / 0002  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Beton zum Kneten  
9405 000 xx

ECHA Homepage - Information about chemicals.  
GESTIS Substance Database (Germany).  
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
National Lists of Occupational Exposure Limits for each country as amended.  
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
AOX Adsorbable organic halogen compounds  
approx. approximately  
Art., Art. no. Article number  
ASTM ASTM International (American Society for Testing and Materials)  
ATE Acute Toxicity Estimate  
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
BCF Bioconcentration factor  
BSEF The International Bromine Council  
bw body weight  
CAS Chemical Abstracts Service  
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
CMR carcinogenic, mutagenic, reproductive toxic  
DMEL Derived Minimum Effect Level  
DNEL Derived No Effect Level  
DOC Dissolved organic carbon  
dw dry weight  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
EC European Community  
ECHA European Chemicals Agency  
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
etc. et cetera  
EU European Union  
EVAL Ethylene-vinyl alcohol copolymer  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
Koc Adsorption coefficient of organic carbon in the soil  
Kow octanol-water partition coefficient  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
IUPAC International Union for Pure Applied Chemistry  
LC50 Lethal Concentration to 50 % of a test population

Page 15 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0003  
Replacing version dated / version: 28.05.2021 / 0002  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Beton zum Kneten  
9405 000 xx

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute for Occupational Safety and Health (USA)  
NLP No-longer-Polymer  
NOEC, NOEL No Observed Effect Concentration/Level  
OECD Organisation for Economic Co-operation and Development  
org. organic  
OSHA Occupational Safety and Health Administration (USA)  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
TOC Total organic carbon  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.