



According to EU regulation 1907/2006 (REACH)

Material Safety Data Sheet

SDS date: 25-06-2020

SDS version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Trade Name: Colortime Crayons

Product- no.: -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Creative and hobby use.

1.3. Details of the supplier of the safety data sheet

Company and address

Creotime.com

Rasmus Færchs Vej 23

7500 Holstebro

Tel.: +45 96 13 30 10

Contact person and E-mail:

info@creotime.com

The Safety data sheet is completed and validated by:

mediator A/S, Centervej 2, DK-6000 Kolding. Consultant: LMJ

1.4. Emergency telephone number

Use your national or local emergency number - See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

For the color Orchid, Carnation, Apricot, Grey, White, Pink, Brown, Ocean Blue, Cornflower Blue, Strawberry, Scarlet, Peach, Violet Red, Violet Blue, Lemon Yellow, Sky Blue, Lavendar, Bright Pink, Slate grey, Beige, Dark grey, Plum, Pale Violet Red, Fluorescein Red, Sea Blue, Tint Green, Slate Blue, Tint Light Green:

CLP (1272/2008): EUH212, EUH210.

See full text of H-phrases in section 16.

2.2. Label elements

For the color Orchid, Carnation, Apricot, Grey, White, Pink, Brown, Ocean Blue, Cornflower Blue, Strawberry, Scarlet, Peach, Violet Red, Violet Blue, Lemon Yellow, Sky Blue, Lavendar, Bright Pink, Slate grey, Beige, Dark grey, Plum, Pale Violet Red, Fluorescein Red, Sea Blue, Tint Green, Slate Blue, Tint Light Green:

Warning! Hazardous respirable dust may be formed when used. Do not breathe dust. (EUH212)

Safety data sheet available on request. (EUH210)



According to EU regulation 1907/2006 (REACH)

Signal word:

-

2.3. Other hazards

For the color Orchid, Carnation, Apricot, Grey, White, Pink, Brown, Ocean Blue, Cornflower Blue, Strawberry, Scarlet, Peach, Violet Red, Violet Blue, Lemon Yellow, Sky Blue, Lavendar, Bright Pink, Slate grey, Beige, Dark grey, Plum, Pale Violet Red, Fluorescein Red, Sea Blue, Tint Green, Slate Blue, Tint Light Green:

The product contains Titanium dioxide which is only regarded as carcinogenic in powdered products.

Additional labelling:

-

Additional warnings:

This product complies with the requirements of the standard set out by The Danish Joint Council of Creative & Hobby Materials (Fællesrådet for Formnings- og Hobbymaterialer), version 11 of 1 november 2018, on creative and occupational materials.

SECTION 3: Composition/information on ingredients

3.1./3.2. Substances/Mixtures

Substance	EU-Index no.	Cas / EINECS no.	CLP-classification	w/w%	Note
White mineral oil (petroleum)	-	8042-47-5/ 232-455-8	-	50-75	1
Talc	-	14807-96-6/ 238-877-9	-	10-15	1
The color Grey, Brown, Black, Olive Green, Dark Grey, Saddle Brown, Black Green, Tint Light Green, Erasable Black:					
Carbon Black	-	1333-86-4/ 215-609-9	-	0,1-10	1
For the color Orchid, Carnation, Apricot, Grey, White, Pink, Brown, Ocean Blue, Cornflower Blue, Strawberry, Scarlet, Peach, Violet Red, Violet Blue, Lemon Yellow, Sky Blue, Lavendar, Bright Pink, Slate grey, Beige, Dark grey, Plum, Pale Violet Red, Fluorescein Red, Sea Blue, Tint Green, Slate Blue, Tint Light Green:					
Titanium dioxide	-	13463-67-7/ 236-675-5	Carc. 2;H351(i)	0,1-5	1
For the color silver and light grey:					
Aluminium	013-002-00-1/-	7429-90-5/ 231-072-3	Flam. Sol. 1;H228, Water-react. 2;H261	0,1-5	1
For the color light orange:					
Iron Oxide	-/-	1309-37-1/ 215-168-2	-	0,1-2	1

1 = The substance has a national exposure limit.

For the wording of the listed risk phrases refer to section 16.

The remaining shades:

Contains no substances subject to reporting requirements.



According to EU regulation 1907/2006 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:	Not relevant.
Ingestion:	Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical advice in case of discomfort.
Skin contact:	Wash skin with soap and water. Seek medical advice in case of discomfort.
Eye contact:	Flush with water (preferably using eye wash equipment) until irritation subsides. Remove contact lenses. Seek medical advice if symptoms persist.

4.2. Most important symptoms and effects, both acute and delayed

May cause slight irritation to the skin and eyes.

4.3. Indication of any immediate medical attention and special treatment needed

When obtaining medical advice, show the safety data sheet or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Surrounding fire: Extinguish with powder, foam or carbon dioxide. Do not use water stream, as it may spread the fire.

5.2. Special hazards arising from the substance or mixture

The product is not directly flammable.

5.3. Advice for firefighters

Avoid inhalation of vapour and fumes – seek fresh air.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

None.

6.2. Environmental precautions

Avoid unnecessary release to the environment. Notify proper authorities in case of contamination of soil or aquatic environment or discharge to drains.

6.3. Methods and material for containment and cleaning up

Wipe up minor spills with a cloth. Rinse with water. See section 13 for instructions on disposal.

6.4. Reference to other sections

See above.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

None.

7.2. Conditions for safe storage, including any incompatibilities

Keep in tightly closed original packaging.



According to EU regulation 1907/2006 (REACH)

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits according to EH40/2005 Workplace exposure limits (Fourth Edition, 2020):

Substance	Long-term exposure limit	Short-term exposure limit	Note
Paraffin wax, fume	3,5 mg/m ³	7 mg/m ³	-
Talc, respirable dust	1 mg/m ³	-	-
Titanium dioxide			
Total inhalable	10 mg/m ³	-	-
Respirable	4 mg/m ³	-	-
Iron oxide, fume (as Fe)	5 mg/m ³	10 mg/m ³	-
Aluminium metal			
inhalable dust	10 mg/m ³	-	-
respirable dust	4 mg/m ³	-	-
Carbon Black	3,5 mg/m ³	7 mg/m ³	-

DNEL and PNEC values:

DNEL- White mineral oil (petroleum):

Workers

Inhalation - Chronic Systemic 160 mg/m³
 Dermal - Chronic Systemic 220 mg/kg bw/day

Consumers

Inhalation - Chronic Systemic 35 mg/m³
 Dermal - Chronic Systemic 93 mg/kg bw/day
 Oral - Chronic Systemic 40 mg/kg bw/day

DNEL- Talc:

Workers

Inhalation - Chronic Systemic 2.16 mg/m³
 Inhalation - Acute Systemic 2.16 mg/m³
 Inhalation - Chronic Local 3.6 mg/m³
 Inhalation - Acute Local 3.6 mg/m³
 Dermal - Chronic Systemic 43.2 mg/kg bw/day
 Dermal - Acute Systemic -
 Dermal - Chronic Local 4.54 mg/cm²

Consumers

Inhalation - Chronic Systemic 1.08 mg/m³
 Inhalation - Acute Systemic 1.08 mg/m³
 Inhalation - Chronic Local 1.8 mg/m³
 Inhalation - Acute Local 1.8 mg/m³
 Dermal - Chronic Systemic 21.6 mg/kg bw/day
 Dermal - Acute Systemic 2.27 mg/cm²
 Dermal - Acute Local 2.27 mg/cm²
 Oral - Chronic Systemic 160 mg/kg bw/day
 Oral - Acute Systemic 160 mg/kg bw/day

DNEL- Carbon Black:

Workers

Inhalation - Chronic Systemic 2 mg/m³
 Inhalation - Chronic Local 2 mg/m³



According to EU regulation 1907/2006 (REACH)

DNEL- Aluminium:

Workers

Inhalation - Chronic Systemic 3,72 mg/m³

Inhalation - Chronic Local 3,72 mg/m³

Consumers

Oral - Chronic Systemic 7,9 mg/kg bw/day

PNEC- Carbon Black:

Fresh water 5 mg/L

Marine water 5 mg/L

8.2. Exposure controls

There are no exposure scenarios for this product.

Appropriate engineering controls:

-

Personal protective equipment:

Respiratory protection:	Not required.
Hand protection:	Not required.
Eye/face protection:	Not required.
Skin protection:	Not required.

Environmental exposure controls:

Make sure that when using the product damming material is available in immediate vicinity.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	Crayons. Multiple colours
Odour:	-
Odour threshold:	-
pH:	-
Melting point/ Freezing Point (°C):	-
Initial boiling point and boiling range (°C):	-
Flash point (°C):	-
Evaporation rate:	-
Flammability (solid, gas)	-
Upper / lower flammability or explosion limits (vol-%):	-
Vapour pressure (mbar, 25 °C):	-
Vapour density (air=1)	-
Relative density (g/ml):	-
Solubility(ies):	-
Partition coefficient: n-octanol/water:	-
Auto-ignition temperature (°C):	-
Decomposition temperature (°C):	-
Viscosity (mPas, 25 °C):	-
Explosive properties:	-
Oxidising properties:	-



According to EU regulation 1907/2006 (REACH)

9.2. Other information

Content of solids (%):	-
Surface tension (mN/m, 25 °C):	-

SECTION 10: Stability and reactivity

10.1. Reactivity

Non-reactive.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid heating.

10.5. Incompatible materials

Avoid contact with strong oxidising agents.

10.6. Hazardous decomposition products

No special precautions regarding contact with other materials at the recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity: Based on the existing data, the classification is not met.

Substance	Route of exposure	Species	Test	Result
White mineral oil (petroleum)	Oral	Rat	LD50	> 5000 mg/kg bw
White mineral oil (petroleum)	Inhalation	Rat	LC50 / 4 Hours	> 5 mg/L air
White mineral oil (petroleum)	Dermal	Rabbit	LD50	> 2000 mg/kg bw
Talc	Oral	Rat	LD50	> 5 000 mg/kg bw
Talc	Inhalation	Rat	LC50 / 15 min	> 2.1 mg/L.
Talc	Dermal	Rabbit	LD50	> 2000 mg/kg bw
Titanium dioxide	Inhalation	Rat	LC50 / 4 Hours	> 6,82 mg/L
Iron(III) Oxide	Oral	Rat	LD50	> 5000 mg/kg bw
Carbon Black	Oral	Rat	LD50	> 8000 mg/kg bw
Carbon Black	Inhalation	Rat	LC50 / 4 Hours	> 4,6 mg/m ³ air
Aluminium	Oral	Rat	LD50	> 15900 mg/kg bw
Aluminium	Inhalation	Rat	LC50/ 4 Timer	> 2,3 mg/L air

Skin corrosion/irritation: May cause slight irritation.

Serious eye damage/irritation: May cause eye irritation.

Respiratory or skin sensitisation: Based on the existing data, the classification is not met.

Germ cell mutagenicity: Based on the existing data, the classification is not met.



According to EU regulation 1907/2006 (REACH)

Carcinogenicity:

For the color Orchid, Carnation, Apricot, Grey, White, Pink, Brown, Ocean Blue, Cornflower Blue, Strawberry, Scarlet, Peach, Violet Red, Violet Blue, Lemon Yellow, Sky Blue, Lavendar, Bright Pink, Slate grey, Beige, Dark grey, Plum, Pale Violet Red, Fluorescein Red, Sea Blue, Tint Green, Slate Blue, Tint Light Green:

Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

Reproductive toxicity: Based on the existing data, the classification is not met.

STOT-single exposure: Based on the existing data, the classification is not met.

STOT-repeated exposure: Based on the existing data, the classification is not met.

Aspiration hazard: Based on the existing data, the classification is not met.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Test duration	Species	Test	Result
Titanium dioxide	24 Hours	Daphnia	EC50	> 5600 mg/L
Iron(III) Oxide	48 Hours	Daphnia	EC50	> 100 mg/L
Carbon Black	48 Hours	Daphnia	EC50	> 5600 mg/L
Carbon Black	72 Hours	Algae	EC50	> 10000 mg/L
Aluminium	96 Hours	Fish	LC50	> 218644,1 µg/L
Aluminium	48 Hours	Daphnia	EC50	0,72 mg/L
Aluminium	72 Hours	Algae	EC50	200 µg/L

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
White mineral oil (petroleum)	No	OECD 301F	28 Days: 31%

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
Talc	-	-9,40	-

12.4. Mobility in soil

Test data are not available.

12.5. Results of PBT and vPvB assessment

The mixture does not meet the criteria for PBT or vPvB.

12.6. Other adverse effects

None.



According to EU regulation 1907/2006 (REACH)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product is not classified as hazardous waste according to Waste Management. Disposal of spillage and waste via the municipal waste collection service with the specifications below is recommended.

EWC Code

20 01 99

Specific labelling

-

Contaminated packaging:

Uncleansed packaging is to be disposed of via the local waste-removal scheme.

SECTION 14: Transport information

The product is not covered by the rules for transport of dangerous goods by road and sea according to ADR and IMDG.

14.1 -14.4.

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Sources:

-

Restrictions for application:

-

Demands for specific education:

-

Additional labelling:

-

15.2. Chemical safety assessment

Chemical safety assessment has not been performed.



According to EU regulation 1907/2006 (REACH)

SECTION 16: Other information

Other information:

This product complies with the requirements of the standard set out by The Danish Joint Council of Creative & Hobby Materials (Fællesrådet for Formnings- og Hobbymaterialer), version 11 of 1 november 2018, on creative and occupational materials.

Sources:

EC regulation 1907/2006 (REACH).

EC Regulation 1272/2008 (CLP).

EU regulation no. 276/2010

Directive 2000/532/EC

Full text of H-phrases as mentioned in section 2+3:

H351(i) - Suspected of causing cancer by inhalation.

EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

Classification according to Regulation (EC) Nr. 1272/2008:	
EUH212	Expert judgement

Abbreviations and acronyms used in the safety data sheet:

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals. Regulation (EC) No 1907/2006.

CLP: Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.

CAS-Number.: Chemical Abstracts Service number.

EC-Number.: EINECS and ELINCS Number (see also EINECS and ELINCS).

DNEL: Derived No Effect Level.

PNEC(s): Predicted No Effect Concentration(s).

STOT: Specific Target Organ Toxicity.

LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).

LC50: Lethal Concentration to 50 % of a test population.

EC50: The effective concentration of substance that causes 50% of the maximum response.

PBT: Persistent, Bioaccumulative and Toxic.

vPvB: Very Persistent and Very Bioaccumulative.

NOEC: The highest tested concentration at which, in a study, no statistically significant effect is observed in the exposed population compared with an appropriate control group.

NOAEL: The highest tested dose or exposure level at which there are no statistically significant increases in the frequency or severity of adverse effects between the exposed population and an appropriate control group; some effects may be produced at this level, but they are not considered adverse or precursors of adverse effects.

Other

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

Minor changes have been made in following sections:

1-16 – Update.

This material safety data sheet replaces version:

24-01-2017 (1.1).
