

Protan FPO/TPO 1.2

Product Description

Protan FPO/TPO 1.2 is a flexible roofing membrane based on polyolefins and reinforced with a polyester textile. It is designed for mechanically fastened roofing systems on flat and low-sloped roofs. The membrane is suitable for exposed roofing applications and is welded using hot air to ensure secure and durable joints.

Protan FPO/TPO 1.2 is particularly well-suited for solar roofs and cool roof applications due to its resistance to environmental exposure, UV radiation, and chemical influences. The membrane performs reliably under a wide range of climatic conditions.

Key Properties

- Superior weather and environmental resistance.
- Resistant to UV radiation.
- Classified for fire performance in accordance with EN standards.
- Strong, secure joints achieved through hot-air welding – no open flames required.
- Compatible with bitumen-based membranes.
- Recyclable with documented carbon footprint.
- Suitable for contact with cold potable water (WRAS approved).

Technical Properties

Essential characteristics	Performance	EN 13956
Thickness	1.2 mm	EN 1849-2
Mass per unit area	1.5 kg/m ²	EN 1849-2
Reaction to fire	Class E	EN 13501-1
Water tightness (10kPa)	Pass	EN 1928 (A)
Tensile strength L/T	≥ 1050 N/50 mm	EN 12311-2 (A)
Elongation L/T	≥ 15 %	EN 12311-2 (A)
Resistance to impact	≥ 500 mm	EN 12691 (A)
Resistance to static load	≥ 20 kg	EN 12730 (C)
Tear resistance L/T	≥ 400 N	EN 12310-2
Joint peel resistance	≥ 600 N/50 mm	EN 12316-2
Joint shear resistance	≥ 800 N/50 mm	EN 12317-2
Foldability at low temp.	≤ -25°C	EN 495-5
Exposure to UV	Pass > 5000 h	EN 1297
Radon gas resistance	2.8 × 10 ⁸ s/m	SP-method 3873
Water vapour resistance	Sd-value 250 m	EN ISO 12572
Dangerous substances	None	

L: Longitudinal (machine direction); T: Transverse (cross machine direction)

Dimensions

- Width: 1.60 m
- Length: 20 m
- Roll: 32 m² / 48 kg + core
- Pallet: 14 Rolls / 448 m² / 672 kg + core and pallet.

Colours

Colour	White	Grey White	Light Grey	Silver Grey	Dark Grey
Protan code	F01	F05	F91	F93	F94
~RAL code	9016	9003	7040	7001	7012
Samples					

Health, Environment, and Safety

- Environmental Product Declaration according to EN 15804 (the Norwegian EPD Foundation).
- Environmental Declaration registered in the Dutch Environmental Database (NMD).
- Safety Data Sheet (SDS) available upon request.
- The membrane does not contain any substances listed on REACH/ECHA's Candidate List and is free from priority environmental pollutants or other substances in quantities considered hazardous to health or the environment.

Storage

- Shelf life: 10 years from production date provided proper storage.
- Store in dry conditions, protected from direct sunlight.
- Keep rolls horizontally on a pallet. Avoid stacking pallets of rolls on top of one another or placing them under pallets with different materials during transport or storage.

Installation details

The product must be installed by experienced professionals. The membrane is hot-air welded and must be installed in accordance with the Protan technical specifications.

Certificates and approvals

- CE-marked in accordance with EN 13956.
- Fire classification according to EN 13501-5. Full system specifications are available upon request.
- WRAS approved for contact with cold potable water in accordance with BS 6920 (UK Water Regulations Approval Scheme).
- Overall migration: 4.5 mg/dm² (20% ethanol, 40 °C / 10 days), compliant with EU Regulation No. 10/2011, confirming low extractables and high chemical stability.

Protan Legal Notice

The information in this document is based on Protan's current knowledge and experience when the product is stored, handled, and installed according to recommendations. Due to variations in materials, substrates, and site conditions, no warranty of merchantability or fitness for a particular purpose is provided, and no liability can be inferred from this document. The user is responsible for ensuring suitability for the intended application. Protan reserves the right to modify product specifications without notice. Protan's current sales and delivery terms apply to all orders. Always refer to the latest version of the Product Data Sheet, available on our website.

