

Declaration of Performance

No: DoP315-SE12-E

Version: v7



Protan SE 1.2

1. Unique identification code of the product-type	Protan SE 1.2
2. Identification of product	Lot number on label and product
3. Intended use	Plastic sheets for roof waterproofing Exposed roofs
4. Manufacturer	Protan AS Baches vei 1, N-3413 Lier, Norway
5. Authorised representative	-
6. System of AVCP	System 2+
7. Harmonised standard Notified body	EN 13956:2012 SINTEF 1071
8. European assessment document Notified body	-

9. Declared performance

Essential characteristics	Performance	EN 13956:2012
External Fire performance	F _{ROOF} (t)	EN 13501-5
Reaction to fire	Class E	EN 13501-1
Water tightness (10kPa)	Pass	EN 1928 (A)
Tensile strength L/T	MLV ≥ 1100/1050 N/50 mm	EN 12311-2 (A)
Elongation L/T	MLV ≥ 15%	EN 12311-2 (A)
Resistance to impact	MLV ≥ 400 mm	EN 12691 (A)
Resistance to static load	MLV ≥ 20 kg	EN 12730 (C)
Tear resistance L/T	MLV ≥ 210 N	EN 12310-2
Joint peel resistance, maximum	MLV ≥ 200 N/50 mm	EN 12316-2
Joint shear resistance	MLV ≥ 1000 N/50 mm	EN 12317-2
Foldability at low temperature	MLV ≤ -30°C	EN 495-5
Exposure to UV	Pass > 5000 h	EN 1297
Dangerous substances	None	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Hege Gunnerud
Lab Manager and Principal Engineer
Drammen, 29.02.2024

This product is an article within the meaning of Regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. There are no registration requirements for substances in articles within the meaning of Article 7.1 of the Regulation. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) from the candidate list published by the European Chemicals Agency in concentrations above 0.1% (w/w).