

Arc Flash Face Shield S31200



S31201



S31200

S31202 + S69500



ORDERING INFORMATION

Product No.	Description	Suspension	Weight	Window Dimensions	Window Treatment
S31200	<ul style="list-style-type: none"> Black high-impact crown and chin protector 9.9 cal/cm² molded polycarbonate window 	Ratcheting Headgear	0.95 lb	7.5" x 15.75"	Uncoated
S31201	<ul style="list-style-type: none"> Black high-impact crown and chin protector Universal slotted dielectric hard hat adaptor 9.9 cal/cm² molded polycarbonate window 	Univ. Adapt.	0.82 lb	7.5" x 15.75"	Uncoated
S31202+ S69500 Kit	<ul style="list-style-type: none"> Black high-impact crown and chin protector Polycarbonate 9.9 cal anti-fog window with a white hard hat and headgear 	Ratcheting Hard Hat	1.75 lb	7.5" x 15.75"	Uncoated

Description and Performance:

Sellstrom's Arc Flash face shield provide the best possible clarity with absolutely no distortion. Rugged, polycarbonate shield is high impact and chemical splash resistant and provides excellent color definition. The shield curves naturally to fit facial contours ensuring reliable protection from low level arc flash hazards. Light green tint allows for 55% light transmittance for best clarity. Interchangeable parts extend the life of the face shield and lower cost of ownership. Face shield available with an adjustable thirty five position ratchet headgear suspension hard hat. Refer to NFPA 70E standards for complete PPE Arc Flash Safety Requirements.

Sellstrom Manufacturing Co.
Elgin, IL 60123
Phone: (800) 323-7402
Fax: (847) 717-8419
www.surewerx.com

MATERIALS

	Description
Hard Hat Adaptor	Dielectric ABS Plastic and rubber retainers
Window	High impact resistant .060" Molded Polycarbonate, light green tint
Hard Hat	HDPE (see 69500 for complete specifications)

STANDARD COMPLIANCE

Meets ANSI Z87+ High impact, ASTM F2178, NFPA 70E 2009 standards

ARC THERMAL PROTECTIVE VALUE

9.9 Cal/cm²