

MINER'S BELTS

- Designed for restraint only
- D-ring located on the back of the belt for fall restraint only
- Can be used in conjunction with full body harnesses when fall protection is required
- Meets or exceeds CSA Z259.1-05 and ANSI Z359.1-2007
- Polyester webbing
- 400 lb (181 kg) combined weight of person, tools, clothing, etc.
- Operating Temperature: -35°C to +35°C

Prod. No.	Mod. No.	D-Rings	Straps	Size
Miner's Belt - Non Padded				
V8051041	WB-1040-S	Back (1)	1	S
V8051042	WB-1040-M	Back (1)	1	M
V8051043	WB-1040-L	Back (1)	1	L
V8051044	WB-1040-XL	Back (1)	1	XL
V8051045	WB-1040-XXL	Back (1)	1	XXL
V8051051	WB-1050-S	Back (1)	2	S
V8051052	WB-1050-M	Back (1)	2	M
V8051053	WB-1050-L	Back (1)	2	L
V8051054	WB-1050-XL	Back (1)	2	XL
V8051055	WB-1050-XXL	Back (1)	2	XXL
Miner's Belt - Padded				
V8056041	WB-6040-S	Back (1)	1	S
V8056042	WB-6040-M	Back (1)	1	M
V8056043	WB-6040-L	Back (1)	1	L
V8056044	WB-6040-XL	Back (1)	1	XL
V8056045	WB-6040-XXL	Back (1)	1	XXL
V8056051	WB-6050-S	Back (1)	2	S
V8056052	WB-6050-M	Back (1)	2	M
V8056053	WB-6050-L	Back (1)	2	L
V8056054	WB-6050-XL	Back (1)	2	XL
V8056055	WB-6050-XXL	Back (1)	2	XXL



V8051041



V8051051



V8056041



V8056051



SECURING YOUR PEACE OF MIND.

This product is covered by SureWerx against defects in materials and workmanship when the product is used for the purpose for which it was designed. Please refer to surewerx.com for more warranty information.