

TANK TROLLEYS

- The PeakWorks Fall Protection Tank Trolley is designed for use on water and fuel storage tanks
- The Tank Trolley provides a 5,000 lb anchorage as required by OSHA and ANSI standards
- The Tank Trolley simply rides on the top lip of the storage tank and can be used with a standard lanyard or self-retracting lifeline
- Standards compliance: materials meet OSHA 1926.5 subpart M, 1910.66 app. C, ANSI A10.14
- Trolley: 1/4" steel rollers, powder-coated finish with forged steel O-ring attachment, polyurethane composite material
- Capacity: 310 lb designed working load
- V82235: For storage tanks with a minimum diameter of 10', fits 1/4" to 1" flange widths
- V82236: For storage tanks with a minimum diameter of 10', fits 1" to 1-7/8" flange widths
- Made in the U.S.



Materials meet
OSHA 1926.5 subpart M,
1910.66 app. C,
ANSI A10.14

Prod. No.	Mod. No.	Description	Weight
V82235	9900-Trolley6	Standard Tank Trolley	14 lb
V82236	9900-Trolley6A	Wide Flange Tank Trolley	14 lb



PEAKWORKS FALL PROTECTION

- PeakWorks stands behind the quality of all our professional products.
- Our knowledgeable staff are happy to serve you - please call our Inside Sales team.
- PeakWorks is proudly owned by SureWerx, a Canadian company dedicated to bringing quality tools and equipment to professional workers in Canada.



SECURING YOUR PEACE OF MIND.

This product is covered by SureWerx against defects in materials and workmanship when the product is used for the purpose for which it was designed. Please refer to surewerx.com for more warranty information.