



FLAME-GARDTM
MC

UTILI-GARD FR[®] RAINWEAR

PRODUCT NO. V2449320 / MOD. NO. J162 310DH

PRODUCT NO. V2440620 / MOD. NO. H162 502

PRODUCT NO. V2448450 / MOD. NO. P162 041

HIGH RISK PROTECTION FROM ELECTRIC ARC

UTILI-GARD FR[®] waterproof protective wear is designed to provide superior protection from electrical arc and flash fire while providing comfort and freedom of movement.

FLAME-GARDTM

Ranpro's FLAME-GARDTM FR Waterproof Protective Wear doesn't just live up to industry standards: It lives up to ours. Which means it'll live up to yours.



J162 310DH

H162 502

P162 041



TOTAL QUALITY IN ALL THAT WE DO

**This Ranpro product is covered by the Ranpro warranty against defects in materials and workmanship when the product is used for the purpose for which it was designed. Please refer to surewerx.com for more warranty information.*



surewerx.com





Utili-Gard® FR Jacket

- J162 310DH - 8 oz/yd² PVC on Dupont™ Nomex®/Kevlar®
- J163 310DH and J161 310DH - 10 oz/yd² PVC on Dupont™ Nomex®/Kevlar® • Meets CGSB 122.20, 2000 Type 3
- Meets CSA Z96-09/ANSI 107 Class 2 Level 2 high-visibility safety apparel standards, Class 3 when worn with Utili-Gard® pants
- Meets ASTM F1891-06 Standard Specification for Arc and Flame Resistant Rainwear, NFPA 70E-12 and CSA Z462-12
- J162 310DH - ATPV 12.9 cal/cm², EBTAS 41.2 cal/cm², HAF 80%
- J163 310DH - ATPV 14 cal/cm², EBTAS 42.6 cal/cm², HAF 84.6%
- J161 310DH - ATPV 10.8 cal/cm², EBTAS 47.6 cal/cm², HAF 82.2%
- 2" wide FR Star Tech™ silver striping on arms, torso, front, and X on back (CSA configuration)
- Dolman sleeve design for ease of movement • FR brass zipper
- Outer storm flap with top to bottom FR hook and loop closure
- Inner storm flap for reduced heat transmission
- Form-fitting collar has pouch for detachable hood with FR hook and loop closure
- Hood sold separately • Tab style FR hook and loop cuff adjustments
- Vented back • FR elastic drawstring on inner bottom hem to prevent arc exposure



PROD. NO.	MOD. NO.	Colour	Sizes
V2449320	J162 310DH	International Orange	XS-4XL
V2449560	J163 310DH	Fluorescent Yellow	M-2XL
V2449650	J161 310DH	Fluorescent Orange	M-2XL



Utili-Gard® FR Hood

- H162 502 - 8 oz/yd² PVC on Dupont™ Nomex® / Dupont™ Kevlar®
- H161 502/H163 502 - 10 oz/yd² PVC on Dupont™ Nomex® / Dupont™ Kevlar® • Fits easily over a hard hat
- Non-conductive, non-corrosive snaps • Drawstring for custom fit • 3-piece hood design



PROD. NO.	MOD. NO.	Colour	Sizes
V2440620	H162 502	International Orange	O/S
V2440660	H163 502	Fluorescent Yellow	O/S
V2440650	H161 502	Fluorescent Orange	O/S



Utili-Gard® FR Bib Pant

- P162 041 - 8 oz/yd² PVC on Dupont™ Nomex®/Kevlar®
- P163 041/P161 041 - 10 oz/yd² PVC on Dupont™ Nomex®/Kevlar®
- Meets CGSB 122.20, 2000 Type 3
- Meets CSA Z96-09/ ANSI 107 Class 3 Level 2 high-visibility safety apparel standards, when worn with CSA Class 2 Level 2 top featuring reflective arm bands
- Meets ASTM F1891-06 Standard Specification for Arc and Flame Resistant Rainwear, NFPA 70E-12 and CSA Z462-12
- P162 041 - ATPV 12.9 cal/cm², EBTAS 41.2 cal/cm², HAF 80%
- P163 041 - ATPV 14 cal/cm², EBTAS 42.6 cal/cm², HAF 84.6%
- P161 041 - ATPV 10.8 cal/cm², EBTAS 47.6 cal/cm², HAF 82.2%
- 2" FR silver Star Tech™ reflective striping meets CSA Z96-09 high-visibility safety apparel standards
- Single bib design with inner bib pocket
- Adjustable arc resistant fabric suspenders and spreader bar with elastic back and Kwik-Lok connectors • Adjustable spreader bar at back
- Roomy legs to easily put on boot • Durable reinforced waist ties for snug fit



PROD. NO.	MOD. NO.	Colour	Sizes
V2448450	P162 041	International Orange	XS-4XL
V2440260	P163 041	Fluorescent Yellow	M-2XL
V2440550	P161 041	Fluorescent Orange	M-2XL

