



TECHNICAL DATA SHEET

SELF-RETRACTING DEVICE (SRD)

PeakWorks offers a new series of Non-Leading Edge Class 1 SRDs approved for vertical use only and are third-party certified to the latest ANSI Z359.14-2021 standard. They feature an aluminum housing for maximum durability with a .21-inch galvanized cable lifeline and come equipped with a fixed handle anchor attachment point. Devices have a maximum arrest distance of 42 inches and a maximum arrest force of 1,800 lbs.

WARNINGS: See the Operating and Maintenance Instruction Manual for details.

FEATURES:

- Maximum Arrest Distance: 42 in (1.07 m)
- Average Arrest Distance: 32 in (0.82 m)
- Maximum Arrest Force: 1,800 lbs (8 kN)
- Average Arrest Force: 667 lbf (2.97 kN)
- Third-party certified to ANSI Z359.14 Class 1

ORDERING INFORMATION

PRODUCT #	NEW MODEL #	DESCRIPTION	LENGTH OF SRL
V8455331170	SRD-53302-170	Overhead Self-Retracting Device – 170'	170 FT

STANDARD COMPLIANCE

Standard Certified to ANSI Z359.14-2021

TECHNICAL SPECIFICATIONS

HOUSING STYLE		LIFELINE SPECIFICATIONS		BODY FALL ARREST D-RING CONNECTION	ANCHOR POINT STYLE
Aluminum		Galvanised Steel Cable 0.21 in (5.5 mm)		Snap Hook	Swivel w/Carabiner

SINGLE LEG/ TWIN LEG	FALL ARREST	RESCUE/ RECOVERY	ANCHOR MOUNTING POSITION	LE (Y/N)	EXTERNAL SHOCK PACK (FOR LE)
Single	Yes	No	Anchorage Connector	No	No

WEIGHT CAPACITY: 110-310 lbs (50-141 kg) capacity for 1 worker (combined weight of person, tools, clothing, etc.)

STORAGE: Store in a cool dry place away from chemicals, water, corrosive environments, and source of heat or spark

OPERATING TEMPERATURES: -40° F to 122° F (-40° C to 50° C)

