



TECHNICAL DATA SHEET

SELF-RETRACTING LIFELINES LE (SRL-LE)

PeakWorks offers a new series of self-retracting lifelines that are third-party certified to the newest CSA Z259.2.2 standard for leading-edge applications (LE) and for overhead use. Leading-edge SRLs are designed to protect a worker when working near an edge and a fall hazard exists. They provide additional protection against sharp or abrasive surfaces found on many construction sites. The lightweight, durable, aluminum housing unit is approved for use in vertical and horizontal applications. The attachment points include a swivel eye on housing and double-action locking snap hooks with fall indicator to connect to the worker's fall arrest D-ring.

WARNINGS: See the Operating and Maintenance Instruction Manual for details.

FEATURES:

- Approved for use in vertical and horizontal applications
- Tested and approved for foot level tie-off
- Maximum Deployment LE Applications (foot level): 1.20 m (48 in)
- Maximum Deployment Overhead Applications: 0.31 m (12 in)
- Average arrest force: 4.12kN (926 lbf)
- Minimum setback distance from edge: 30 cm (12 in); refer to the user manual
- Third-party certified to  CSA Z259.2.2 and ANSI Z359.14 Class B
- All LE products are clearly marked to ensure the correct SRL is used for Leading Edge applications



ORDERING INFORMATION

PRODUCT #	NEW MODEL #	DESCRIPTION	LENGTH OF SRL
V845625006LE	SRL-70502-6LE	6-ft Leading Edge SRL—Twin Leg with Snap and Pack—New CSA	6 FT

STANDARD COMPLIANCE

Standard Certified to CSA Z259.2.2-2017 & ANSI Z359.14-2014

TECHNICAL SPECIFICATIONS

HOUSING STYLE	LIFELINE SPECIFICATIONS			BODY FALL ARREST D-RING CONNECTION	ANCHOR POINT STYLE
Aluminum	Dyneema® Webbing 0.8 in wide x 0.07 in thick (20 mm wide x 1.75 mm thick)			Snap Hook	Swivel Mount Harness Attachment
SINGLE LEG/ TWIN LEG	FALL ARREST	RESCUE/ RECOVERY	ANCHOR MOUNTING POSITION	LE (Y/N)	EXTERNAL SHOCK PACK (FOR LE)
Twin	Yes	No	Anchorage Connector	Yes	Yes

WEIGHT CAPACITY: 310 lbs (141 kg) capacity for 1 worker (combined weight of person, tools, clothing, etc.)

STORAGE: Store in a cool dry place away from chemicals, water, corrosive environments, and source of heat or spark

OPERATING TEMPERATURES: -30° C to 50° C (-22° F to 122° F)



sureworx.com

Western Canada & Territories
 Sales Tel: 604-523-7600
 Toll Free Tel: 1-800-472-7685
 email: sales@sureworx.com

Eastern Canada
 Sales Tel: 905-565-8661
 Toll Free Tel: 1-800-387-3879
 email: salesod@sureworx.com