

# TECHNICAL DATA SHEET SELF-RETRACTING LIFELINE



PROD. NO.: V845525006LE  
MOD. NO.: SRL-50502-6LE

## DESCRIPTION

Leading edge twin leg self-retracting lifeline in a durable aluminum housing with web lifeline. Approved for use in vertical and horizontal applications.

## SPECIFICATIONS

**Material:** 25 mm (1") webbing

**Length:** 1.8 m (6 ft)

**Number of Workers:** 1

**Weight:** 5 lb (2.26 kg)

**Capacity:** 300 lb (136 kg) for one worker (combined weight of person, tools, clothing, etc)

**Operating Temperature:** -35° C to +35° C

## ATTACHMENT POINTS

Swivel eye on housing with connection pin for mounting below the dorsal D-ring and double-action locking swivel snap hook with fall indicator on web lifeline for connection to anchorage connector.

## STANDARDS

**Meets or exceeds:** CSA Z259.2.2-98 and ANSI Z359.14 Class A

Max Arrest Distance 24" (610 mm), Avg Arrest Force <1,350 lb (6 kN), Max. Arrest Force <1,800 lb (8 kN)

## COMPONENT COMPATIBILITY

Are designed for use with PeakWorks approved components or subsystems (full body harnesses, anchorage connectors, etc.) or as recommended by a Qualified Person.

## WARNINGS

See Operating and Maintenance Instruction Manual for details.

## STORAGE

Store in a cool dry place away from chemicals, water, corrosive environments, and sources of heat or spark.