




TECHNICAL DATA SHEET

SELF-RETRACTING LIFELINES

PeakWorks offers a new series of self-retracting lifelines that are third-party certified to the newest CSA Z259.2.2 standard for overhead use. The lightweight, durable, aluminum housing unit is approved for use in vertical and horizontal applications. The attachment points include a convenient carrying handle on housing and double-action locking snap hooks with fall indicator to connect to the worker's fall arrest D-ring.

WARNINGS: See the Operating and Maintenance Instruction Manual for details.

FEATURES:

- Approved for use in vertical applications
- Rescue/recovery units can be mounted on tripod (with optional bracket) and used for rescue in a confined space system
- Maximum Deployment Overhead Applications: 1.10 m (43 in)
- Average arrest force: 8kN (1350 lbf)
- Third-party certified to  CSA Z259.2.2 and ANSI Z359.14 Class B



ORDERING INFORMATION

PRODUCT #	NEW MODEL #	DESCRIPTION	LENGTH OF SRL
V845643096	SRL-73303-96	96-ft Cable SRL with Recovery—New CSA	96 FT

STANDARD COMPLIANCE

Standard Certified to CSA Z259.2.2-2017 & ANSI Z359.14-2014

TECHNICAL SPECIFICATIONS

HOUSING STYLE	LIFELINE SPECIFICATIONS		BODY FALL ARREST D-RING CONNECTION	ANCHOR POINT STYLE	
Aluminum	Galvanised Steel Cable 0.21 in (5.5 mm)		Swivel Snap Hooks	Requires Tripod-Mounted Bracket	
SINGLE LEG/ TWIN LEG	FALL ARREST	RESCUE/ RECOVERY	ANCHOR MOUNTING POSITION	LE (Y/N)	EXTERNAL SHOCK PACK (FOR LE)
Single	Yes	Yes	Anchorage Connector	No	No

WEIGHT CAPACITY: 310 lbs (141 kg) capacity for 1 worker (combined weight of person, tools, clothing, etc.)

STORAGE: Store in a cool dry place away from chemicals, water, corrosive environments, and source of heat or spark

OPERATING TEMPERATURES: -30° C to 50° C (-22° F to 122° F)