

# TECHNICAL DATA SHEET PEAKPRO PLUS HARNESS WITH POSITIONING BELT - 5D - CLASS APE



PROD. NO.: V800517X  
MOD. NO.: FBH-70110G-X

X Denotes Belt Size :

- 1 = S
- 2 = M
- 3 = L
- 4 = XL
- 5 = XXL



## DESCRIPTION

The PeakWorks **Peakpro Plus Harness** is a sure fit **Full Body Harness, Class APE**, with increased durability and comfort. All hardware components are made from **high-grade anodized aluminum** for reduced weight and no risk of corrosion, for added life expectancy. The **“peekaboo” webbing** is designed to aid in the inspection of the harness: as the webbing wears to a point requiring removal from service, the webbing shows a red indicator for easy inspection. In addition each harness is fitted with upgraded durable shoulder and leg pads as well as a comfortable padded belt.

As is with each and every PeakWorks product, this harness is thoroughly tested during the product development stage and is batch tested to confirm conformance.

## SPECIFICATIONS

**Material:** Polyester “peekaboo” webbing, anodized aluminum hardware

**Chest - Buckles :** Aluminum Stab Lock

**Leg Buckles:** Aluminum Stab Lock

**Weight:** 3 lb

**Number of Workers:** 1

**Class:** APE

**Capacity:** 140 kg (310 lb) combined weight of person, tools, clothing, etc.

**Operating Temperature:** -35° C to +35° C

## STANDARDS & COMPLIANCE

**Certified to:** CSA Z259.10, and ANSI Z359.11

## COMPONENT COMPATIBILITY

PeakWorks anchor slings are designed for use with PeakWorks approved components or subsystems (full body harnesses, lifelines, rope grabs, connectors, self-retracting lifelines, etc.) or as recommended by a Qualified Person.

## WARNINGS

See Operating and Maintenance Instruction Manual for details.

## STORAGE

Store in a cool dry place away from chemicals, water, corrosive environments, and sources of heat or spark.