



TECHNICAL DATA SHEET

SELF-RETRACTING LIFELINES

PeakWorks offers a new series of self-retracting lifelines that are third-party certified to the newest CSA Z259.2.2 standard for leading-edge applications (LE) and for overhead use. The lightweight, durable, aluminum housing unit is approved for use in vertical and horizontal applications. The attachment points include a swivel eye on housing and double-action locking snap hooks with fall indicator to connect to the worker's fall arrest D-ring.

WARNINGS: See the Operating and Maintenance Instruction Manual for details.

FEATURES:

- Certified to the ASTM F887 Arc Flash standard
- Approved for use in vertical applications only
- Total Arrest Distance Overhead Applications: 0.50 m (19 in)
- Average arrest force: 4.12kN (926 lbf)
- Third-party certified to  CSA Z259.2.2 and ANSI Z359.14 Class B

ORDERING INFORMATION

PRODUCT #	NEW MODEL #	DESCRIPTION	LENGTH OF SRL
V845682006AR	SRL-76105-6AR	6-ft Arc Flash Single Leg SRL—New CSA	6 FT

STANDARD COMPLIANCE

Standard Certified to CSA Z259.2.2-2017, ANSI Z359.14-2014, & Certified to the ASTM F887 Arc Flash standard

TECHNICAL SPECIFICATIONS

HOUSING STYLE	LIFELINE SPECIFICATIONS		BODY FALL ARREST D-RING CONNECTION	ANCHOR POINT STYLE	
Aluminum	Armead Webbing, ASTM F887 Arc Flash		Snap Hook	Swivel w/Carabiner	
SINGLE LEG/ TWIN LEG	FALL ARREST	RESCUE/ RECOVERY	ANCHOR MOUNTING POSITION	LE (Y/N)	EXTERNAL SHOCK PACK (FOR LE)
Single	Yes	No	Fall Arrest D-Ring or Anchorage Connector	NO	No

WEIGHT CAPACITY: 310 lbs (141 kg) capacity for 1 worker (combined weight of person, tools, clothing, etc.)

STORAGE: Store in a cool dry place away from chemicals, water, corrosive environments, and source of heat or spark

OPERATING TEMPERATURES: -30° C to 50° C (-22° F to 122° F)

