



TECHNICAL DATA SHEET

SELF-RETRACTING DEVICE (SRD)

PeakWorks offers a new series of self-retracting lifelines that are third-party certified to the new ANSI Z359.14-2021 standard for overhead use. The lightweight, durable aluminum housing unit is approved for use in vertical and horizontal applications. The attachment points include a convenient carrying handle on housing and double-action locking snap hooks with fall indicator to connect to the worker's fall arrest D-ring.

WARNINGS: See the Operating and Maintenance Instruction Manual for details.

FEATURES:

- Approved for use in vertical applications
- Rescue/recovery units can be mounted on tripod (with optional bracket) and used for rescue in a confined space system
- Maximum Arrest Distance: 42 in (1.07 m)
- Average Arrest Distance: 28 in (0.71 m)
- Maximum Arrest Force: 1,800 lbs (8 kN)
- Average Arrest Force: 618 lbf (2.75 kN)
- Third-party certified to ANSI Z359.14-2021 Class 1



ORDERING INFORMATION

PRODUCT #	NEW MODEL #	DESCRIPTION	LENGTH OF SRL
V8455341060	SRDR-53303-60	SRD – Single Leg Cable with Recovery – 60'	60 FT

STANDARD COMPLIANCE

Standard Certified to ANSI Z359.14-2021

TECHNICAL SPECIFICATIONS

HOUSING STYLE	LIFELINE SPECIFICATIONS			BODY FALL ARREST D-RING CONNECTION	ANCHOR POINT STYLE	
Aluminum	Galvanised Steel Cable 0.21 in (5.5 mm)			Swivel Snap Hooks	Requires Tripod-Mounted Bracket	
SINGLE LEG/ TWIN LEG	FALL ARREST	RESCUE/ RECOVERY	ANCHOR MOUNTING POSITION	LE (Y/N)	EXTERNAL SHOCK PACK (FOR LE)	
Single	Yes	Yes	Anchorage Connector	No	No	



WEIGHT CAPACITY: 110-310 lbs (50-141 kg) capacity for 1 worker (combined weight of person, tools, clothing, etc.)

STORAGE: Store in a cool dry place away from chemicals, water, corrosive environments, and source of heat or spark

OPERATING TEMPERATURES: -40° F to 122° F (-40° C to 50° C)



surewerx.com

325 Corporate Drive
Elgin, IL 60123
USA

Toll Free Tel: 1-800-323-7402
Fax: 847-717-8419
email: orders.usa@surewerx.com