

MINER'S BELTS

- Designed for restraint only
- D-ring located on the back of the belt for fall restraint only
- Can be used in conjunction with full body harnesses when fall protection is required
- Meets or exceeds CSA Z259.1-05 and ANSI Z359.1-2007
- Polyester webbing
- 400 lb (181 kg) combined weight of person, tools, clothing, etc.
- Operating Temperature: -35°C to +35°C

| Prod. No. | Mod. No. | D-Rings | Straps | Size |
|----------------------------------|-------------|----------|--------|------|
| Miner's Belt - Non Padded | | | | |
| V8051041 | WB-1040-S | Back (1) | 1 | S |
| V8051042 | WB-1040-M | Back (1) | 1 | M |
| V8051043 | WB-1040-L | Back (1) | 1 | L |
| V8051044 | WB-1040-XL | Back (1) | 1 | XL |
| V8051045 | WB-1040-XXL | Back (1) | 1 | XXL |
| V8051051 | WB-1050-S | Back (1) | 2 | S |
| V8051052 | WB-1050-M | Back (1) | 2 | M |
| V8051053 | WB-1050-L | Back (1) | 2 | L |
| V8051054 | WB-1050-XL | Back (1) | 2 | XL |
| V8051055 | WB-1050-XXL | Back (1) | 2 | XXL |
| Miner's Belt - Padded | | | | |
| V8056041 | WB-6040-S | Back (1) | 1 | S |
| V8056042 | WB-6040-M | Back (1) | 1 | M |
| V8056043 | WB-6040-L | Back (1) | 1 | L |
| V8056044 | WB-6040-XL | Back (1) | 1 | XL |
| V8056045 | WB-6040-XXL | Back (1) | 1 | XXL |
| V8056051 | WB-6050-S | Back (1) | 2 | S |
| V8056052 | WB-6050-M | Back (1) | 2 | M |
| V8056053 | WB-6050-L | Back (1) | 2 | L |
| V8056054 | WB-6050-XL | Back (1) | 2 | XL |
| V8056055 | WB-6050-XXL | Back (1) | 2 | XXL |



V8051041



V8051051



V8056041



V8056051



SECURING YOUR PEACE OF MIND.

This product is covered by SureWerx against defects in materials and workmanship when the product is used for the purpose for which it was designed. Please refer to surewerx.com for more warranty information.