



Printing date 09/23/2020 Reviewed on 11/06/2017

1 Identification

· Product identifier

· Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

· Article number: XB405-1KG-OS

· Application of the substance / the mixture Printing inks

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Static Control Components Inc.

P.O. Box 152

Sanford, North Carolina, 27331

info@scc-inc.com

· Information department: Product Safety Department

· Emergency telephone number:

During Normal Operating Hours: 919-774-3808

Emergency Telephone Number: 1-919-770-7984 or 1-919-770-6019

2 Hazard(s) identification

· Classification of the substance or mixture

Combustible Dust May form combustible dust concentrations in air.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

May form combustible dust concentrations in air.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1

Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Resin mixture

(Contd. on page 2)



Printing date 09/23/2020 Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

		(Contd. of page 1)
· Dangerous compo	nents:	
1333-86-4 Carbo	n black (bound)	>2.5-≤10%
8002-74-2 Paraff	n waxes and Hydrocarbon waxes	>2.5-≤10%
13463-67-7 titaniu	m dioxide (bound)	>2.5-≤10%
· Non-hazardous co	mponents	
Polyester Resin		>50-≤100%
Amorphous Silica		>2.5-≤10%

4 First-aid measures

- · Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: No Information Available
- · Special hazards arising from the substance or mixture
- Like most finely divided organic powders , toner dust may form an explosive mixture in air.
- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Vacuum or sweep the material into a sealed container. If a vacuum is used it must be dust explosion-proof. Dispose of in compliance with national, state, regional or provincial regulations.

- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 3)



Printing date 09/23/2020 Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

· Protective A	Action Criteria for Chemicals	(Contd. of page 2)
· PAC-1:		
1333-86-4	Carbon black (bound)	9 mg/m ³
13463-67-7	titanium dioxide (bound)	30 mg/m³
· PAC-2:		
1333-86-4	Carbon black (bound)	99 mg/m³
13463-67-7	titanium dioxide (bound)	330 mg/m³
· PAC-3:		
1333-86-4	Carbon black (bound)	590 mg/m ³
13463-67-7	titanium dioxide (bound)	2,000 mg/m ³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

No special precautions are necessary if used correctly.

Use only in well ventilated areas.

- Information about protection against explosions and fires: Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

· Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials as well as heavy-metal compounds.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from humidity and water.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

 1333-86-4 Carbon black (bound)

 PEL | Long-term value: 3.5 mg/m³

(Contd. on page 4)



Printing date 09/23/2020 Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

(Contd. of page 3)

REL	Long-term value: 3.5* mg/m ³
-----	---

*0.1 in presence of PAHs;See Pocket Guide Apps.A+C

TLV Long-term value: 3* mg/m³

*inhalable fraction

8002-74-2 Paraffin waxes and Hydrocarbon waxes

REL Long-term value: 2 mg/m³ TLV Long-term value: 2 mg/m³

13463-67-7 titanium dioxide (bound)

PEL Long-term value: 15* mg/m³

*total dust

REL See Pocket Guide App. A TLV Long-term value: 10 mg/m³

· Additional Occupational Exposure Limit Values for possible hazards during processing:

USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous Silica: USA OSHA (TWA/PEL): 20mppcf 80 mg/m3, ACGIH (TWA/TLV): 10 mg/m3

TRGS 900 (Luftgrenzwert): 10 mg/m3 (Einatembare partikel)). 3 mg/m3 (Alveolengängige fraktion)

UK WEL: 10 mg/m3 (Respirable Dust) 5 mg/m3 (Inhalible Dust)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale dust / smoke / mist.

· Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eve protection: Safety glasses

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Powder
Color: Black
Odor: Characteristic

· Odor threshold: Not determined.

pH-value: Not applicable.

(Contd. on page 5)





Printing date 09/23/2020 Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

		(Contd. of page 4
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 316 °C (600.8 °F)	
· Flash point:	220 °C (428 °F)	
· Flammability (solid, gaseous):	Not determined.	
· Ignition temperature:	>300 °C (>572 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard in its original state.	
· Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapor pressure:	Not applicable.	
Density at 20 °C (68 °F):	1.2 g/cm³ (10.014 lbs/gal) SG: 1.3-1.8	
· Relative density	Not determined.	
· Vapor density · Evaporation rate	Not applicable. Not applicable.	
· Solubility in / Miscibility with Water:	Insoluble.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity: Dynamic: Kinematic:	Not applicable. Not applicable.	
· Solvent content: VOC content:	0.00 %	
Solids content: Other information	100.0 % No further relevant information available.	

10 Stability and reactivity

- · Reactivity Non reactive.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.





Printing date 09/23/2020 Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

(Contd. of page 5)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No toxic irritating effect, according to Directive 67/548/EEC or Directive 199/45/EC.
- on the eye: No toxic irritating effect, according to Directive 67/548/EEC or Directive 199/45/EC.
- Sensitization: No toxic sensitizing effects known, according to EU Directive 67/548/EEC or Directive 199/45/EC.
- · Other information (about experimental toxicology):

Mutagenicity: Ames test Negative (According to the test result of similar composition.)

· Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

Only unbound carbon black considered a Group 2 Carcinogen by IARC

,	1 & 5		
1333-86-4	Carbon black (bound)	2B	
13463-67-7	titanium dioxide (bound)	2B	
· NTP (Natio	· NTP (National Toxicology Program)		
None of the	None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)			
None of the ingredients is listed.			

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Smaller quantities can be disposed of with household waste.

(Contd. on page 7)



Printing date 09/23/2020 Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

(Contd. of page 6)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information	
· UN-Number	Not a regulated material under the United States DOT, IMDG, ADR, RID, o ICAO/IATA.
· DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	Not a regulated material under the United States DOT, IMDG, ADR, RID, CICAO/IATA
· DOT, ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	Not a regulated material under the United States DOT, IMDG, ADR, RID, ICAO/IATA.
· DOT, ADR, ADN, IMDG, IATA	
Class	Void
· Packing group	Not a regulated material under the United States DOT, IMDG, ADR, RID, ICAO/IATA.
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

15 Regulatory information

None of the ingredients is listed.

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Sara			
· Section 355	· Section 355 (extremely hazardous substances):		
None of the	None of the ingredients is listed.		
· Section 313	(Specific toxic chemical listings):		
None of the	None of the ingredients is listed.		
· TSCA (Tox	ic Substances Control Act):		
1333-86-4	Carbon black (bound)	ACTIVE	
8002-74-2	Paraffin waxes and Hydrocarbon waxes	ACTIVE	
13463-67-7	titanium dioxide (bound)	ACTIVE	
· Hazardous Air Pollutants			

(Contd. on page 8)



Printing date 09/23/2020 Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

(Contd. of page 7)

· Propositio	n 65	(Conta. of page)
Chemicals	known to cause cancer:	
1333-86-4	Carbon black (bound)	
13463-67-7	7 titanium dioxide (bound)	
Chemicals	known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
Chemicals	known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
Chemicals	known to cause developmental toxicity:	
None of the	e ingredients is listed.	
Carcinoge	nic categories	
· EPA (Envi	ironmental Protection Agency)	
None of the	e ingredients is listed.	
· TLV (Thre	eshold Limit Value established by ACGIH)	
1333-86-4	Carbon black (bound)	A
13463-67-7	7 titanium dioxide (bound)	A
· NIOSH-Ca	a (National Institute for Occupational Safety and Health)	
1333-86-4	Carbon black (bound)	
13463-67-7	7 titanium dioxide (bound)	

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

May form combustible dust concentrations in air.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision 09/23/2020 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of

Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

(Contd. on page 9)





Printing date 09/23/2020 Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

(Contd. of page 8)

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

* Data compared to the previous version altered.

No changes to the Material Safety Data Sheet, all sections are current as the date of print seen above describes.

US