

Printing date 12/18/2014 Reviewed on 12/18/2014

1 Identification of the Substance/Mixture and of the Company/Undertaking

· Product identifier

· Trade name: Non-OEM Replacement Extra High Yield Yellow Cartridge for use in Lexmark C792, 20K

· Article number: RCC792X-Y

· Application of the substance / the mixture Printing inks

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Static Control Components Inc.

P.O. Box 152

Sanford, North Carolina, 27331

info@scc-inc.com

· Information department: Product safety department

· Emergency telephone number:

During Normal Operating Hours: 919-774-3808

Emergency Telephone Number: 1-919-770-7984 or 1-919-770-6019

2 Hazards Identification

· Classification of the substance or mixture

The product is not classified according to the Globally Harmonized System (GHS).

- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not applicable.
- · Information concerning particular hazards for human and environment:

The product does not have to be labeled due to the calculation procedure of international guidelines.

 \cdot Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system:
- · NFPA ratings (scale 0 4)



 $\begin{aligned} & Health = 1 \\ & Fire = 1 \end{aligned}$

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1

1 Fire = 1

REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 2)



Printing date 12/18/2014 Reviewed on 12/18/2014

Trade name: Non-OEM Replacement Extra High Yield Yellow Cartridge for use in Lexmark C792, 20K

(Contd. of page 1)

· vPvB: Not applicable.

3 Composition/Information on Ingredients

· Chemical characterization: Mixtures

· **Description:** Resin mixture

· Dangerous components: Void

· Non-hazardous components			
	Styrene Acrylate Copolymer	50-100%	
	Wax	2.5-10%	
	Yellow Pigment	2.5-10%	
67762-90-7	Silica	≤ 2.5%	

4 First Aid Measures

- · Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: No Information Available
- · Special hazards arising from the substance or mixture

Like most finely divided organic powders, toner dust may form an explosive mixture in air.

- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

• Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



Printing date 12/18/2014 Reviewed on 12/18/2014

Trade name: Non-OEM Replacement Extra High Yield Yellow Cartridge for use in Lexmark C792, 20K

(Contd. of page 2)

· Methods and material for containment and cleaning up:

Vacuum or sweep the material into a sealed container. If a vacuum is used it must be dust explosion-proof. Dispose of in compliance with national, state, regional or provincial regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

· Precautions for safe handling

No special measures required.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

No special precautions are necessary if used correctly.

Use only in well ventilated areas.

- · Information about protection against explosions and fires: Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

· Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials as well as heavy-metal compounds.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from humidity and water.

· Specific end use(s) No further relevant information available.

8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional Occupational Exposure Limit Values for possible hazards during processing:

USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous Silica: USA OSHA (TWA/PEL): 20mppcf 80 mg/m3, ACGIH (TWA/TLV): 10 mg/m3

TRGS 900 (Luftgrenzwert): 10 mg/m3 (Einatembare partikel)). 3 mg/m3 (Alveolengängige fraktion)

UK WEL: 10 mg/m3 (Respirable Dust) 5 mg/m3 (Inhalible Dust)

(Contd. on page 4)



Printing date 12/18/2014 Reviewed on 12/18/2014

Trade name: Non-OEM Replacement Extra High Yield Yellow Cartridge for use in Lexmark C792, 20K

(Contd. of page 3)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale dust / smoke / mist.

- · Protection of hands:
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection: Safety glasses

9 Physical and Chemical Properties				
· Information on basic physical and · General Information	chemical properties			
· Appearance:				
Form:	Powder			
Color:	According to product specification			
· Odor:	Odorless			
· Odour threshold:	Not determined.			
· pH-value:	Not applicable.			
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. Undetermined.			
· Flash point:	Not applicable.			
· Flammability (solid, gaseous):	Not determined.			
· Ignition temperature:				
Decomposition temperature:	Not determined.			
· Auto igniting:	Product is not selfigniting.			
· Danger of explosion:	Product does not present an explosion hazard in its original state.			
· Explosion limits:				
Lower:	Not determined.			
Upper:	Not determined.			
· Vapor pressure:	Not applicable.			
· Density at 20 °C (68 °F):	1.04 g/cm³ (8.679 lbs/gal) SG: 1.3-1.8			
· Relative density	Not determined.			
· Vapour density	Not applicable.			
· Evaporation rate	Not applicable.			
	(Contd. on page 5			

(Contd. on page 5)



Printing date 12/18/2014 Reviewed on 12/18/2014

Trade name: Non-OEM Replacement Extra High Yield Yellow Cartridge for use in Lexmark C792, 20K

		(Contd. of page 4)
· Solubility in / Miscibility with Water:	Insoluble.	
Partition coefficient (n-octano	ol/water): Not determined.	
· Viscosity: Dynamic: Kinematic:	Not applicable. Not applicable.	
· Solvent content: Organic solvents:	0.0 %	
Solids content: Other information	100.0 % No further relevant information available.	

10 Stability and Reactivity

- · Reactivity Non reactive.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No toxic irritating effect, according to Directive 67/548/EEC or Directive 199/45/EC.
- on the eye: No toxic irritating effect, according to Directive 67/548/EEC or Directive 199/45/EC.
- · Sensitization: No toxic sensitizing effects known, according to EU Directive 67/548/EEC or Directive 199/45/EC.
- · Other information (about experimental toxicology):

Mutagenicity: Ames test Negative (According to the test result of similar composition.)

· Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations: When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 6)



Printing date 12/18/2014 Reviewed on 12/18/2014

Trade name: Non-OEM Replacement Extra High Yield Yellow Cartridge for use in Lexmark C792, 20K

(Contd. of page 5)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods
- · Recommendation: Smaller quantities can be disposed of with household waste.
- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

Void	
Void	
Void	
Void	
No	
Not applicable.	
	Void Void Void No





Printing date 12/18/2014 Reviewed on 12/18/2014

Trade name: Non-OEM Replacement Extra High Yield Yellow Cartridge for use in Lexmark C792, 20K

(Contd. of page 6)

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- No further relevant information available.
- ·Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

67762-90-7 Silica

1306-38-3 cerium dioxide

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

1306-38-3 cerium dioxide

111

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.





Printing date 12/18/2014 Reviewed on 12/18/2014

Trade name: Non-OEM Replacement Extra High Yield Yellow Cartridge for use in Lexmark C792, 20K

(Contd. of page 7)

16 Other Information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact:

During Normal Operating Hours: 919-774-3808

Emergency Telephone Number: 1-919-770-7984 or 1-919-770-6019

· Date of preparation / last revision 12/18/2014 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

* Data compared to the previous version altered.

No changes to the Material Safety Data Sheet, all sections are current as the date of print seen above describes.

USA •