

Page 1/9

Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2020

Reviewed on 11/06/2017

- **1** Identification
- · Product identifier
- Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405
- · Article number: XB405-10KG-OS
- · Application of the substance / the mixture Printing inks
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Static Control Components Inc.
- P.O. Box 152 Sanford, North Carolina, 27331 info@scc-inc.com
- · Information department: Product Safety Department · Emergency telephone number: During Normal Operating Hours: 919-774-3808 Emergency Telephone Number: 1-919-770-7984 or 1-919-770-6019

2 Hazard(s) identification

· Classification of the substance or mixture

- Combustible Dust May form combustible dust concentrations in air.
- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements
- May form combustible dust concentrations in air.
- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)

HEALTH 0	Health = 0
FIRE 1	Fire = 1
REACTIVITY 0	Reactivity $= 0$

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Resin mixture

(Contd. on page 2)



Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2020

Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

	(Contd. of page 1)
· Dangerous components:	
1333-86-4 Carbon black (bound)	>2.5-≤10%
8002-74-2 Paraffin waxes and Hydrocarbon waxes	>2.5-≤10%
13463-67-7 titanium dioxide (bound)	>2.5-≤10%
· Non-hazardous components	
Polyester Resin	>50-≤100%
Amorphous Silica	>2.5-≤10%

4 First-aid measures

- · Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: No Information Available
- · Special hazards arising from the substance or mixture

Like most finely divided organic powders, toner dust may form an explosive mixture in air.

- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Vacuum or sweep the material into a sealed container. If a vacuum is used it must be dust explosion-proof. Dispose of in compliance with national, state, regional or provincial regulations.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 3)



Page 3/9

Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2020

Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

· Protective Action Criteria for Chemicals	
· PAC-1:	
1333-86-4 Carbon black (bound)	9 mg/m ³
13463-67-7 titanium dioxide (bound)	30 mg/m ³
· PAC-2:	
1333-86-4 Carbon black (bound)	99 mg/m ³
13463-67-7 titanium dioxide (bound)	330 mg/m ³
· PAC-3:	
1333-86-4 Carbon black (bound)	590 mg/m ³
13463-67-7 titanium dioxide (bound)	2,000 mg/m ³

7 Handling and storage

· Handling:

- · Precautions for safe handling
- No special measures required.
- Store in cool, dry place in tightly closed receptacles.
- Keep away from heat and direct sunlight.
- No special precautions are necessary if used correctly.
- Use only in well ventilated areas.
- · Information about protection against explosions and fires: Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and receptacles:** Store in a cool location. Store only in the original receptacle.
- Information about storage in one common storage facility:
- Do not store together with oxidizing and acidic materials as well as heavy-metal compounds.
- · Further information about storage conditions:
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- Protect from humidity and water.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

- 1333-86-4 Carbon black (bound)
- PEL Long-term value: 3.5 mg/m³

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS Page 4/9

Printing date 09/23/2020

Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

(Contd. of page 3)

REL Long-term value: 3.5* mg/m³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C

TLV Long-term value: 3* mg/m³ *inhalable fraction

8002-74-2 Paraffin waxes and Hydrocarbon waxes

REL Long-term value: 2 mg/m³

TLV Long-term value: 2 mg/m³

13463-67-7 titanium dioxide (bound)

PEL Long-term value: 15* mg/m³

*total dust

REL See Pocket Guide App. A TLV Long-term value: 10 mg/m³

• Additional Occupational Exposure Limit Values for possible hazards during processing: USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous Silica: USA OSHA (TWA/PEL): 20mppcf 80 mg/m3, ACGIH (TWA/TLV): 10 mg/m3

TRGS 900 (Luftgrenzwert): 10 mg/m3 (Einatembare partikel)). 3 mg/m3 (Alveolengängige fraktion)

UK WEL: 10 mg/m3 (Respirable Dust) 5 mg/m3 (Inhalible Dust)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist.

· Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. • **Eye protection:** Safety glasses

9 Physical and chemical properties

 Information on basic physic General Information Appearance: 	cal and chemical properties	
Form:	Powder	
Color:	Black	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not applicable.	
		(Contd. on page 5)

(Contd. on page 5



Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2020

Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

	(Contd. of page -
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 316 °C (600.8 °F)
· Flash point:	220 °C (428 °F)
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	>300 °C (>572 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard in its original state.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure:	Not applicable.
· Density at 20 °C (68 °F):	1.2 g/cm ³ (10.014 lbs/gal) SG: 1.3-1.8
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
 Solubility in / Miscibility with Water: 	Insoluble.
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity: Dynamic: Kinematic:	Not applicable. Not applicable.
· Solvent content: VOC content:	0.00 %
Solids content: • Other information	100.0 % No further relevant information available.

10 Stability and reactivity

- · Reactivity Non reactive.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)



Page 6/9

Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2020

Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

(Contd. of page 5)

2B

2B

11 Toxicological information

· Information on toxicological effects

- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No toxic irritating effect, according to Directive 67/548/EEC or Directive 199/45/EC.
- on the eye: No toxic irritating effect, according to Directive 67/548/EEC or Directive 199/45/EC.
- · Sensitization: No toxic sensitizing effects known, according to EU Directive 67/548/EEC or Directive 199/45/EC.
- Other information (about experimental toxicology):
- Mutagenicity : Ames test Negative (According to the test result of similar composition.)
- · Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations: When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

Only unbound carbon black considered a Group 2 Carcinogen by IARC

1333-86-4 Carbon black (bound)

13463-67-7 titanium dioxide (bound)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- \cdot Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

• Recommendation: Smaller quantities can be disposed of with household waste.



Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2020

Reviewed on 11/06/2017

(Contd. of page 6)

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

· Uncleaned packagings:

• **Recommendation:** Disposal must be made according to official regulations.

4 Transport information	
· UN-Number	Not a regulated material under the United States DOT, IMDG, ADR, RID, o ICAO/IATA.
[·] DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	Not a regulated material under the United States DOT, IMDG, ADR, RID, o ICAO/IATA
· DOT, ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	Not a regulated material under the United States DOT, IMDG, ADR, RID, CICAO/IATA.
· DOT, ADR, ADN, IMDG, IATA	
·Class	Void
· Packing group	Not a regulated material under the United States DOT, IMDG, ADR, RID, or ICAO/IATA.
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· UN "Model Regulation":	Void

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. • Sara

 • Section 355 (extremely hazardous substances):

 None of the ingredients is listed.

 • Section 313 (Specific toxic chemical listings):

 None of the ingredients is listed.

 • TSCA (Toxic Substances Control Act):

 1333-86-4
 Carbon black (bound)

 8002-74-2
 Paraffin waxes and Hydrocarbon waxes

 13463-67-7
 titanium dioxide (bound)

 • Hazardous Air Pollutants

 None of the ingredients is listed.



Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2020

· Proposition 65

Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

(Contd. of page 7)

A4

A4

· Chemicals known to cause cancer:

1333-86-4 Carbon black (bound)

13463-67-7 titanium dioxide (bound)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

1333-86-4 Carbon black (bound)

13463-67-7 titanium dioxide (bound)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black (bound)

13463-67-7 titanium dioxide (bound)

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms Void

· Signal word Warning

· Hazard statements

May form combustible dust concentrations in air.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 09/23/2020 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety





Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2020

Reviewed on 11/06/2017

Trade name: High Image Density Toner for use in Xerox® Phaser ® 3610 and Versalink® B400/B405

(Contd. of page 8)

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

• * Data compared to the previous version altered.

No changes to the Material Safety Data Sheet, all sections are current as the date of print seen above describes.