

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/27/2021

Reviewed on 09/27/2021

1 Identification

- **Product identifier**
- **Trade name:** Odyssey® 3 Toner for use in Lexmark® C Series - Black
- **Article number:** LCS-KOS3
- **Application of the substance / the mixture** Printing inks
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Static Control Components Inc.
P.O. Box 152
Sanford, North Carolina, 27331
info@sc-inc.com
- **Information department:** Product Safety Department
- **Emergency telephone number:**
During Normal Operating Hours: 919-774-3808
Emergency Telephone Number: 1-919-770-7984 or 1-919-770-6019

2 Hazard(s) identification

- **Classification of the substance or mixture**
Combustible Dust May form combustible dust concentrations in air.
- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** Void
- **Signal word** Warning
- **Hazard statements**
May form combustible dust concentrations in air.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**
 Health = 1
Fire = 1
Reactivity = 0
- **HMIS-ratings (scale 0 - 4)**

HEALTH	1
FIRE	1
REACTIVITY	0

 Health = 1
Fire = 1
Reactivity = 0
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Resin mixture

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/27/2021

Reviewed on 09/27/2021

Trade name: Odyssey® 3 Toner for use in Lexmark® C Series - Black

(Contd. of page 1)

· Dangerous components:		
1333-86-4	Carbon black (bound)	>2.5-≤10%
· Non-hazardous components		
	Resin	>50-≤100%
9002-88-4	Polyethylene low density	>2.5-≤10%
67762-90-7	Silica	>2.5-≤10%

4 First-aid measures

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **For safety reasons unsuitable extinguishing agents:** No Information Available
- **Special hazards arising from the substance or mixture**
Like most finely divided organic powders, toner dust may form an explosive mixture in air.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Vacuum or sweep the material into a sealed container. If a vacuum is used it must be dust explosion-proof. Dispose of in compliance with national, state, regional or provincial regulations.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 3)

US

Safety Data Sheet
 acc. to OSHA HCS

Printing date 09/27/2021

Reviewed on 09/27/2021

Trade name: Odyssey® 3 Toner for use in Lexmark® C Series - Black

(Contd. of page 2)

· Protective Action Criteria for Chemicals
· PAC-1:

9002-88-4	Polyethylene low density	16 mg/m ³
1333-86-4	Carbon black (bound)	9 mg/m ³
67762-90-7	Silica	120 mg/m ³
13463-67-7	titanium dioxide (bound)	30 mg/m ³

· PAC-2:

9002-88-4	Polyethylene low density	170 mg/m ³
1333-86-4	Carbon black (bound)	99 mg/m ³
67762-90-7	Silica	1,300 mg/m ³
13463-67-7	titanium dioxide (bound)	330 mg/m ³

· PAC-3:

9002-88-4	Polyethylene low density	1,000 mg/m ³
1333-86-4	Carbon black (bound)	590 mg/m ³
67762-90-7	Silica	7,900 mg/m ³
13463-67-7	titanium dioxide (bound)	2,000 mg/m ³

7 Handling and storage

· Handling:
· Precautions for safe handling

- No special measures required.
- Store in cool, dry place in tightly closed receptacles.
- Keep away from heat and direct sunlight.
- No special precautions are necessary if used correctly.
- Use only in well ventilated areas.

· Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

· Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and receptacles:

- Store in a cool location.
- Store only in the original receptacle.

· Information about storage in one common storage facility:

- Do not store together with oxidizing and acidic materials as well as heavy-metal compounds.

· Further information about storage conditions:

- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- Protect from humidity and water.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/27/2021

Reviewed on 09/27/2021

Trade name: Odyssey® 3 Toner for use in Lexmark® C Series - Black

(Contd. of page 3)

· Control parameters
· Components with limit values that require monitoring at the workplace:
1333-86-4 Carbon black (bound)

PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction

13463-67-7 titanium dioxide (bound)

PEL	Long-term value: 15* mg/m ³ *total dust
REL	See Pocket Guide App. A
TLV	Long-term value: 10 mg/m ³

· Additional Occupational Exposure Limit Values for possible hazards during processing:

 USA OSHA (TWA/PEL): 15 mg/m³ (Total Dust), 5 mg/m³ (Respirable Fraction)

 ACGIH (TWA/TLV): 10 mg/m³ (Inhalable Particulate), 3 mg/m³ (Respirable Particulate)

 Amorphous Silica: USA OSHA (TWA/PEL): 20mppcf 80 mg/m³, ACGIH (TWA/TLV): 10 mg/m³

 TRGS 900 (Luftgrenzwert): 10 mg/m³ (Einatembare partikel), 3 mg/m³ (Alveolengängige fraktion)

 UK WEL: 10 mg/m³ (Respirable Dust) 5 mg/m³ (Inhalible Dust)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale dust / smoke / mist.

· Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

9 Physical and chemical properties

· Information on basic physical and chemical properties
· General Information
· Appearance:
Form: Powder

Color: Black

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/27/2021

Reviewed on 09/27/2021

Trade name: Odyssey® 3 Toner for use in Lexmark® C Series - Black

(Contd. of page 4)

· Odor:	Light
· Odor threshold:	Not determined.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>3,000 °C (>37.400 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not determined.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard in its original state.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not applicable.
· Density at 20 °C (68 °F):	1 g/cm ³ (8.345 lbs/gal) SG: 1.3-1.8
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
VOC content:	0.00 %
Solids content:	100.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** Non reactive.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/27/2021

Reviewed on 09/27/2021

Trade name: Odyssey® 3 Toner for use in Lexmark® C Series - Black

(Contd. of page 5)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **Primary irritant effect:**

· **on the skin:** No toxic irritating effect, according to Directive 67/548/EEC or Directive 199/45/EC.

· **on the eye:** No toxic irritating effect, according to Directive 67/548/EEC or Directive 199/45/EC.

· **Sensitization:** No toxic sensitizing effects known, according to EU Directive 67/548/EEC or Directive 199/45/EC.

· **Other information (about experimental toxicology):**

Mutagenicity : Ames test Negative (According to the test result of similar composition.)

· **Additional toxicological information:**

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

Only unbound carbon black considered a Group 2 Carcinogen by IARC

9002-88-4	Polyethylene low density	3
1333-86-4	Carbon black (bound)	2B
13463-67-7	titanium dioxide (bound)	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/27/2021

Reviewed on 09/27/2021

Trade name: Odyssey® 3 Toner for use in Lexmark® C Series - Black

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Smaller quantities can be disposed of with household waste.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	Not a regulated material under the United States DOT, IMDG, ADR, RID, or ICAO/IATA.
· DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	Not a regulated material under the United States DOT, IMDG, ADR, RID, or ICAO/IATA
· DOT, ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	Not a regulated material under the United States DOT, IMDG, ADR, RID, or ICAO/IATA.
· DOT, ADR, ADN, IMDG, IATA	Void
· Class	Void
· Packing group	Not a regulated material under the United States DOT, IMDG, ADR, RID, or ICAO/IATA.
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

9002-88-4	Polyethylene low density	ACTIVE
1333-86-4	Carbon black (bound)	ACTIVE

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/27/2021

Reviewed on 09/27/2021

Trade name: Odyssey® 3 Toner for use in Lexmark® C Series - Black

(Contd. of page 7)

67762-90-7	Silica	ACTIVE
13463-67-7	titanium dioxide (bound)	ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65
· Chemicals known to cause cancer:

1333-86-4	Carbon black (bound)
13463-67-7	titanium dioxide (bound)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

1333-86-4	Carbon black (bound)	A4
13463-67-7	titanium dioxide (bound)	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4	Carbon black (bound)
13463-67-7	titanium dioxide (bound)

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms Void

· Signal word Warning

· Hazard statements

May form combustible dust concentrations in air.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 09/27/2021 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/27/2021

Reviewed on 09/27/2021

Trade name: Odyssey® 3 Toner for use in Lexmark® C Series - Black

(Contd. of page 8)

NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit

*** Data compared to the previous version altered.**

No changes to the Material Safety Data Sheet, all sections are current as the date of print seen above describes.

US