



• paint • passion • people



Endurance High Gloss, Satin & Primer

As a craftsman you go for the best painting. With the Ralston Endurance exterior paints you can deliver outstanding performance in all conditions. An Endurance paint system offers the ultimate power of protection and long-term protection of your real estate.



Ralston Endurance High Gloss

- · Extremely long life span
- Fast initial drying
- Very high initial gloss & long gloss retention
- · Excellent application properties



Exterior

Intended Use

As finishing coat on pre-treated wood, metal and plastic.





- · Excellent outdoor durability
- Good gloss retention
- **Excellent flow characteristics**
- Can be applied year-round



Intended Use

As finishing coat on pre-treated wood, metal and plastic.





Ralston Endurance Primer

- · For optimum gloss performance
- · Neat and smooth surface
- · High filling
- · Good (edge) coverage

Intended Use

As wood primer, and as undercoat on pre-treated wood, metal and plastic.

	Ralston Endurance High Gloss	Ralston Endurance Satin
Theoretical Coverage *	13 m2/l	14,2 m2/l
Drying Time Condition	20 °C / 65 % R.H.	20 °C / 65 % R.H.
Dust-Free Drying Time **	2	2,5
Tack-Free Time **	3	4
Time To Recoat **	16	18
Wet Film Thickness	77 Mµ	70 Μμ
Dry Film Thickness	50 Μμ	45 Mµ
Gloss Level	High gloss, approx. 85 G.U. at 60 °	Satin gloss, approx. 30 G.U. at 60 °

	Ralston Endurance Primer
Theoretical Coverage *	16 m2/l
Drying Time Condition	20 °C / 65 % R.H.
Dust-Free Drying Time **	1,5
Tack-Free Time **	3
Time To Recoat **	16
Wet Film Thickness	63 Mµ
Dry Film Thickness	40 Μμ
Gloss Level	Satin gloss, approx. 20 G.U. at 60 °

- Depends on application method, applied wet film thickness and surface
- Drying time in hours

For more information visit www.ralstoncolour.com

